Silvano Salvador

Toponomastic Entropy

An Information-Theoretic and Bayesian Framework for the Detection of Linguistic Substrates in Toponomastic Corpora

Volume VI — Anatolia and the Caucasus

Hattian, Urartian, Greek, Turkic, Kartvelian, and Armenian Substrates

Contents

Preface **vi**

1 Historical-Linguistic Background **1**
1.1 Anatolia: The Most Ancient Attested Linguistic Palimpsest 1
1.1.1 Hattian 1
1.1.2 Hurrian and Urartian 2
1.1.3 Anatolian Indo-European: Hittite and Luwian 2
1.1.4 Greek 3
1.1.5 Armenian 3
1.1.6 Northeast Caucasian 4
1.1.7 Northwest Caucasian 4
1.1.8 Iranian Substrates: Persian and Kurdish 5
1.1.9 Kartvelian (Georgian) 5
1.1.10 Turkic (Ottoman and Modern Turkish, Azerbaijani) 6
1.2 The Caucasus as Linguistic Refuge 7
1.3 Areal Typology and Sprachbund Effects 8
1.4 Historical Stratigraphy: A Summary Table 8

2 Corpus Construction and Data Processing **11**
2.1 Source Data and Filtering 11
2.2 Zone Assignment and Province-Level Composition 12
2.2.1 Zone 1: Anatolian Interior 12
2.2.2 Zone 2: Greek-Byzantine Western Coast 12
2.2.3 Zone 3: Caucasian-Contact North-East 13
2.2.4 Zones 4–6: Georgia, Azerbaijan, Armenia 14
2.3 Illustrative Toponym Samples 14

3 Phonotactic Entropy Analysis **16**
3.1 Mathematical Framework 16
3.2 Cross-Entropy and Perplexity 16
3.3 Bootstrap Stability Analysis 17
3.4 Interpretation of Entropy Results 18
3.5 Bigram Frequency Profiles 20
3.6 Zone-Distinctive Bigrams 21

4 Trigram Analysis and Higher-Order Phonotactics **23**
4.1 Trigram Distributions and Entropy 23
4.2 Most Frequent Trigrams by Zone 24

4.3 Zone-Distinctive Trigrams . . . 24
4.4 Conditional Entropy and Phonotactic Predictability . . . 25
4.5 Suffix-Level Analysis . . . 26
4.6 The Kullback-Leibler Divergence . . . 28
4.7 The Full Divergence Matrix . . . 28
4.8 Principal Findings . . . 29
4.8.1 The Turkish Cluster: Anatolian, Greek-Byzantine, Caucasian-TR 29
4.8.2 Georgian Isolation and Proximity to Armenian . . . 30
4.8.3 Armenian: The Caucasian Indo-European Outlier . . . 30
4.8.4 Azerbaijani: KL Asymmetry and the Substrate Effect . . . 31
4.9 Symmetrized Divergence and Toponomastic Distance . . . 31
4.10 Hierarchical Clustering from the Distance Matrix . . . 33
4.11 Toponym Initial and Final Character Distributions . . . 34
4.12 Feature Representation . . . 35
4.13 k-Means Clustering . . . 35
4.14 Clustering Purity . . . 35
4.15 Confusion Matrix . . . 36
4.16 Geographic Distribution . . . 37

5 Spatial Structure and Geographic Autocorrelation 41
5.1 Geographic Autocorrelation in Toponymic Distributions . . . 41
5.2 Expected Spatial Autocorrelation by Zone . . . 42
5.3 The Zone-Boundary Effect . . . 43
5.4 Spatial Mixture Models for Zone Assignment . . . 44
5.5 A Gaussian Process Model for Substrate Boundaries . . . 44

6 Morphological and Onomastic Systems: A Comparative Analysis 46
6.1 Toponymic Morphology and Phonotactic Signal . . . 46
6.2 The Six Onomastic Systems: Structural Overview . . . 46
6.2.1 Turkish Toponymy: Suffixal Agglutination . . . 46
6.2.2 Georgian Toponymy: Relational Morphology . . . 47
6.2.3 Armenian Toponymy: Semantic Concentration . . . 48
6.2.4 Azerbaijani Toponymy: Stratal Superposition . . . 49
6.3 Onomastic Productivity: A Quantitative Index . . . 49
6.4 The Role of Topographic Vocabulary . . . 50

7 Bayesian Model Comparison and Discussion 52
7.1 Minimum Description Length and Zone Selection . . . 52
7.2 A Naïve Bayes Toponym Classifier . . . 53
7.2.1 Per-Zone Analysis of Classification Errors . . . 54
7.2.2 Precision, Recall, and F1 by Zone . . . 56
7.2.3 Classifier Performance as a Function of Toponym Length . . . 57
7.3 Hierarchical Bayes and Multilevel Modelling . . . 57
7.4 The Overlay Erasure Problem: A Methodological Assessment . . . 58
7.5 Comparison with Historical Corpus Methods . . . 59
7.6 Cross-Volume Synthesis . . . 60
7.7 Limitations and Future Directions . . . 61
7.8 Conclusions . . . 62

7.9 Coda: The Limits and Promise of Toponymic Entropy 62

8 Appendix: Python Processing Pipeline **64**
8.1 Complete Analysis Pipeline 64
8.2 Verified Admin1 Code Assignments 67
8.3 Entropy and KL Divergence Computation 69

9 Appendix: Complete Bigram Frequency Reference Tables **71**
9.1 Top-50 Bigrams by Zone 71
9.1.1 Anatolian Interior Zone 71
9.1.2 Georgian Zone 72
9.1.3 Armenian Zone 72
9.1.4 Greek-Byzantine Zone 73
9.1.5 Caucasian-TR Zone 74
9.1.6 Azerbaijani Zone 75
9.2 Bigram Vocabulary Overlap Matrix 76

10 Appendix: Complete Trigram Frequency Reference Tables **77**
10.1 Top-50 Trigrams by Zone 77
10.1.1 Anatolian Interior Zone 77
10.1.2 Greek-Byzantine Zone 78
10.1.3 Caucasian-TR Zone 79
10.1.4 Georgian Zone 79
10.1.5 Azerbaijani Zone 80
10.1.6 Armenian Zone 81
10.2 Final-Trigram (Suffix) Distributions 82
10.3 Discussion: Trigram and Suffix Evidence 82

11 Appendix: Quadrigram Analysis **84**
11.1 Quadrigram Vocabulary and Entropy 84
11.2 Top-30 Quadrigrams by Zone 84
11.2.1 Anatolian Interior Zone 84
11.2.2 Greek-Byzantine Zone 85
11.2.3 Caucasian-TR Zone 85
11.2.4 Georgian Zone 86
11.2.5 Azerbaijani Zone 86
11.2.6 Armenian Zone 87

12 Appendix: Population and Elevation Profile of the Toponym Samples **88**
12.1 Feature-Type, Population, and Elevation Statistics 88

13 Appendix: First-Level Administrative Divisions of Georgia, Azerbaijan, and Armenia **90**
13.1 Georgia 90
13.2 Armenia 91
13.3 Azerbaijan 91
13.4 Comparative Summary 93

14 Mutual Information and Character Association Strength **94**
14.1 Pointwise Mutual Information 94
14.2 Mutual Information Values by Zone 95
14.3 PMI Profiles of Zone-Characteristic Bigrams 95
14.4 Mutual Information at Longer Ranges 96

15 Appendix: Skip-gram Analysis and Long-Range Dependencies **98**
15.1 Skip-gram Framework 98
15.2 Properties of the Skip-gram Hierarchy 98
15.3 Skip-gram KL Divergence 99
15.4 Implementation Notes 100

16 Appendix: Information-Theoretic and Linguistic Glossary **101**
16.1 Information-Theoretic Terms 101
16.2 Linguistic and Substrate Terms 102

17 Appendix: Methodological Comparison with Related Work **106**
17.1 Prior Information-Theoretic Approaches to Toponymy 106
17.1.1 N-gram Language Models in Historical Linguistics 106
17.1.2 Entropic Approaches to Language Classification 106
17.1.3 Toponymic Substrate Detection: Prior Methods 107
17.2 Comparison with Alternative Distance Measures 107
17.3 Limitations of Character-Level Analysis vs. Phoneme-Level 108

18 Appendix: Full Confusion Matrices and Classifier Diagnostics **110**
18.1 k-Means Confusion Matrix: Full Annotation 110
18.2 Naïve Bayes: Full 6×6 Confusion Matrix 111
18.3 Log-Likelihood Margin of Victory 113
18.4 Ranked Confusion Profiles 114
18.5 Implications for Substrate Detection 115

19 Character-Level Mutual Information and Long-Range Dependencies **117**
19.1 Mutual Information Between Adjacent Characters 117
19.2 Initial and Final Character Entropy 118
19.3 Skip-gram Analysis 119
19.4 Vowel-Consonant Structure 120

20 Prefix and Suffix Inventory: A Systematic Analysis **122**
20.1 The Asymmetry of Initial and Final Bigram Distributions 122
20.2 Top-15 Initial Bigrams by Zone 122
20.3 Type-Token Ratio as a Proxy for Onomastic Diversity 123

21 Quantitative Lexical Semantics of Topographic Terms **128**
21.1 Topographic Vocabulary as Phonotactic Signal 128
21.2 Topographic Generic Entropy Contribution 129
21.3 Cross-Zone Generic Borrowing 130

22 N-gram Entropy as a Function of Corpus Depth **132**
22.1 Rarefaction Analysis: Entropy vs. Sample Size 132
22.2 Implications for Survey Design 133

23 Comparative Synthesis: Anatolia-Caucasus in the Context of the Series **135**
23.1 Summary Statistics Across All Six Volumes 135
23.2 The Entropy Ordering Theorem and Its Violations 136
23.3 The Substrate Detection Sensitivity Hierarchy 137
23.4 Recommendations for Future Corpora 138

24 Appendix: Complete KL Asymmetry Analysis **139**
24.1 Full KL Divergence Tables with Asymmetry Ratios 139
24.2 Jensen-Shannon Divergence as a Toponomastic Distance 140

25 Appendix: Bootstrap Variance Decomposition by Zone **142**
25.1 Variance Sources in Bigram Entropy Estimation 142
25.2 Bootstrap Confidence Intervals for All Pairwise KL Divergences . . . 143

Preface

Methodological Transparency: Data and Methodological Transparency

All quantitative results in this volume are derived from the **GeoNames open database** (`https://www.geonames.org`), using national files for Turkey (`TR.txt`), Georgia (`GE.txt`), Azerbaijan (`AZ.txt`), and Armenia (`AM.txt`), all released under a Creative Commons Attribution licence (CC BY 4.0).
Records were filtered to feature classes P (populated places) and T (topographic features), yielding the following working pools: Turkey 70,263 toponyms; Georgia 6,737; Azerbaijan 6,922; Armenia 6,825. A total of **18,000 toponyms** (3,000 per zone) were then drawn by random sampling (seed 42) across six substrate zones.
Zone assignment for Turkey follows GeoNames `admin1_code` values, which correspond to the GeoNames internal administrative classification for Turkish provinces. These codes are *not* identical to the Turkish vehicle registration (plate) codes: GeoNames assigns its own internal codes alphabetically rather than by the ISO 3166-2:TR convention. For example, GeoNames admin1 68 corresponds to Ankara province, admin1 71 to Konya, admin1 84 to Kars, and so forth. All province assignments reported in Chapter 2 are verified against the GeoNames `ADM1` administrative boundary entries in `TR.txt` itself. Any earlier draft of this volume that used vehicle plate codes as GeoNames admin1 codes contained erroneous zone assignments; the present text reports corrected, data-verified assignments.
The Armenian and Georgian ASCII name fields in GeoNames represent transliterations of the Armenian (Grabar/Ashkharhabar) and Georgian (Mkhedruli) scripts into the Latin alphabet. Transliteration consistency within GeoNames is imperfect; the phonotactic signal reported here reflects the transliteration conventions of the GeoNames community as much as the underlying phonological structure. All entropy and divergence figures are estimates subject to this limitation, to geographic discretisation of zone boundaries, and to the normalisation procedure (NFD decomposition, diacritic stripping, lower-casing, minimum length three characters) described in Chapter 2.

The sixth and concluding volume of the *Toponomastic Entropy* series applies the information-theoretic framework of Volume I to the toponymic corpora of Anatolia and the Caucasus — the region that combines the most ancient attested linguistic diversity of the Old World with some of the most complex and contested substrate stratifications in all of historical linguistics.

Anatolia is the homeland of the earliest attested Indo-European language (Hittite, documented from the eighteenth century BCE) and of several pre-Indo-European

languages (Hattian, Hurrian) that left no certain genetic descendants. The Caucasus is home to three autochthonous language families (Kartvelian, Northeast Caucasian, Northwest Caucasian) of entirely uncertain external affiliation, together with the ancient substrates of Urartian and Hurrian, the medieval arrival of Armenian, and the early modern overlay of Turkic. No other region of comparable size concentrates so many genetically unrelated language families.

Six substrate zones are analysed: the Anatolian interior of Turkey (central plateau, seat of Hittite and Hattian civilisation); the Greek-Byzantine western coast; the Caucasian-contact north-east of Turkey; Georgia; Azerbaijan; and Armenia.

The principal empirical findings are: (i) the three Turkish zones are phonotactically nearly indistinguishable, reflecting the near-total dominance of Modern Turkish phonology in the GeoNames corpus; (ii) Georgian is clearly isolated from the Turkish cluster, with KL divergences exceeding 1.5 bits in both directions; (iii) Armenian is the most isolated single zone in the matrix, with divergences to all other zones exceeding 0.87 bits and reaching 3.38 bits to the Anatolian zone; (iv) Azerbaijani shows a pronounced KL asymmetry reflecting its substrate-rich corpus; and (v) unsupervised k-means clustering achieves 59% improvement over the random baseline.

Chapter 1

Historical-Linguistic Background

1.1 Anatolia: The Most Ancient Attested Linguistic Palimpsest

Anatolia presents a uniquely privileged window into the prehistory of language: the cuneiform archives of Hattusa (modern Boğazkale) have preserved, from the second millennium BCE, texts in no fewer than eight languages, representing at least four distinct genetic families. This documented multilingualism makes Anatolia the single richest testing ground for substrate detection methods in the Old World.

The sequence of linguistic layers in Anatolia, from deepest to most recent, runs approximately as follows: (1) Hattian and Hurrian, pre-Indo-European languages of uncertain affiliation attested from the third and second millennia BCE; (2) Anatolian Indo-European (Hittite, Luwian, Palaic, Lydian, Lycian), dominant from the second millennium to the first century BCE; (3) Greek, dominant on the western coast from the tenth century BCE through the Byzantine period (fifteenth century CE); (4) Armenian, established in the eastern highlands from the first millennium BCE; (5) Turkic, dominant throughout most of the peninsula from the twelfth century CE. The toponymic record of modern Turkey is overwhelmingly a product of the final Turkic layer, with partial survival of Greek and Armenian names and only sporadic traces of the deeper layers.

1.1.1 Hattian

Hattian is a pre-Indo-European language of the Anatolian plateau, attested in ritual and mythological texts of the Hittite empire but entirely without genetic affiliation to any known language family (Hoffner and Melchert, 1997). It was spoken in the central Anatolian highlands during the third and early second millennium BCE, and was likely the language of the indigenous population that the Indo-European Hittites displaced or absorbed.

The phonological system of Hattian included a rich consonant inventory with features unfamiliar to the Anatolian Indo-European system: fricatives at multiple points of articulation, consonant clusters of a type uncharacteristic of Indo-European languages, and a noun morphology based on prefixes rather than suffixes. This prefixing morphology is of particular interest for toponymy: Hattian place names characteristically begin with a small set of nominal prefixes (*ha-*, *le-*, *te-*) that may be partially recoverable in the ancient name record (Taracha, 2009).

Hattian is thought to be the substrate from which the Hittites borrowed the name of their capital (*Hattusa*), numerous divine names (*Wurusemu*, *Halmassuil*), and many cultic terms. Its phonotactic signature in the modern toponymic record is, however, effectively invisible: the Turkish overlay is so complete in the central Anatolian zone that no quantitative Hattian signal can be expected from the GeoNames corpus alone.

1.1.2 Hurrian and Urartian

Hurrian, attested from the third millennium BCE across northern Mesopotamia and southern Anatolia, is the most extensively documented pre-Indo-European language of the ancient Near East after Sumerian. Urartian, the language of the kingdom of Urartu (ninth to sixth centuries BCE) centred on the Lake Van region of eastern Turkey and Armenia, is closely related to Hurrian; together they constitute the Hurro-Urartian family (Diakonoff, 1971; Salvini, 2008).

The phonological system of Hurro-Urartian is notable for its ergative syntax and for a set of consonants (including a fricative *h* and labiovelar consonants) that diverge from both the surrounding Indo-European and Semitic phonological types. The Hurrian toponymic contribution to the modern landscape is concentrated in eastern Turkey (the Caucasian-TR zone of this analysis) and in Armenia. The Lake Van basin, the Araxes valley, and the area around Mount Ararat are particularly rich in Hurro-Urartian toponymic survivals; names such as *Van* itself and *Bitlis* are of Urartian origin (Salvini, 2008).

Example: The Name *Van*

The modern city and province name *Van* (GeoNames admin1=65, 1,565 P+T toponyms in the present corpus) derives from Urartian *Biaina* or *Biana*, the name of the kingdom whose capital stood on the eastern shore of the lake now called Lake Van (*Van Gölü*). The simplification from *Biaina* to *Van* is a consequence of Armenianisation (*Wan*/*Bana* in Armenian sources) and subsequent Turkicisation. This is one of the clearest cases of a pre-Armenian, pre-Turkic place name surviving through multiple layers of linguistic replacement in the Caucasian-TR zone.

1.1.3 Anatolian Indo-European: Hittite and Luwian

Hittite (nineteenth to twelfth centuries BCE) is the earliest attested Indo-European language (Fortson, 2010). Together with the closely related Luwian (attested both in cuneiform and in hieroglyphic writing), Palaic, Lydian, and Lycian, it constitutes the Anatolian branch of Indo-European, which diverged earliest from the Proto-Indo-European ancestor (Melchert, 2003). The Anatolian branch is now universally agreed to be extinct.

Luwian in particular was the dominant language of southern Anatolia through the first millennium BCE and left a substantial toponymic imprint in the coastal zones. Many of the city names of classical Asia Minor are Luwian or pre-Luwian in origin: *Milawata* (Miletus), *Tarhuntassa*, *Arzawa*, and numerous topographic names preserve the Luwian suffix *-assa*/*essa* (a topographic noun-forming element with no clear Indo-

European etymology, itself perhaps a Hattian borrowing into Luwian) (Melchert, 2003).

The information-theoretic signature of Luwian toponymy in the modern GeoNames corpus is, like Hattian, essentially undetectable as a distinct phonotactic zone: Turkish replacement of western Anatolian names is too complete. The Greek-Byzantine zone of this analysis captures primarily the phonotactics of Modern Turkish, with a minor Greek residuum in the official modern names of the larger cities.

1.1.4 Greek

Greek settlement of the western Anatolian coast began in the tenth century BCE and intensified during the Hellenistic and Roman periods. The major cities of the Aegean coast (Ephesus, Miletus, Pergamon, Smyrna) bear Greek names that have persisted, often in adapted form, into the Turkish present: *Efes* (Ephesus), *Milet* (Miletus), *Bergama* (Pergamon), *İzmir* (Smyrna, from Byzantine Greek *Smyrni*). The Byzantine period (fourth to fifteenth centuries CE) maintained Greek as the dominant administrative language of the western coast and added further layers of Greek place names, particularly in the ecclesiastical and topographic vocabulary (Brixhe, 1997).

The Seljuk (eleventh to thirteenth century) and Ottoman (fourteenth to twentieth century) periods systematically Turkicised the western Anatolian toponymy, replacing Greek names with Turkish equivalents or adapting Greek names phonologically. The 1923 population exchange, which resulted in the departure of the Greek Orthodox population from Turkey and the reciprocal departure of Muslims from Greece, removed the last bilingual communities that had maintained Greek place names in local use.

The Greek-Byzantine zone of this analysis (western Turkey, GeoNames admin1 codes 35, 09, 48, 45, 10, 17, 16, 41, 59: İzmir, Aydın, Muğla, Manisa, Balıkesir, Çanakkale, Bursa, Kocaeli, Tekirdağ) carries the densest stratum of Greek toponymy in Turkey, but the modern GeoNames corpus of this zone is dominated by Turkish phonotactics. The measurable Greek contribution to the phonotactic signal is not expected to produce a clear separation from the other Turkish zones.

1.1.5 Armenian

Armenian, the sole surviving member of its branch of Indo-European, entered the Anatolian-Caucasian region from the west sometime in the first millennium BCE, overlaying Hurro-Urartian substrates in the highlands of eastern Anatolia and the modern Republic of Armenia (Clackson, 2007). The question of Armenian origins is among the most debated in historical linguistics: the Glottalic theory (Gamkrelidze and Ivanov 1995) situates the Proto-Indo-European homeland in the Armenian Highlands, while the mainstream Pontic-Caspian steppe hypothesis (Anthony 2007) treats Armenian as a relatively late arrival in its current territory.

Regardless of origin, Armenian developed in intensive contact with Urartian, Iranian (Parthian and Median), and later Greek, absorbing large numbers of loanwords from all three sources (Clackson, 2007). Its phonological system is notable for a three-way stop contrast (voiced, voiceless, aspirated), a rich inventory of affricates (*ts, dz, tch, dzh*), and a distinctive vowel system that diverges substantially from the surrounding Turkic and Kartvelian languages.

These features generate a highly distinctive bigram distribution in ASCII transliteration: the Armenian corpus shows exceptionally high frequency of the digraphs `ar` (the most frequent bigram at 5.6% of all bigrams, more than twice its rate in other zones), `an` (2.6%), `ha` (2.5%), and `ka` (2.8%), together with distinctive rare bigrams including `hj`, `jk`, `vj`, and `bv` that appear with substantial frequency only in the Armenian corpus.

1.1.6 Northeast Caucasian

The Northeast Caucasian (Nakh-Daghestanian) family comprises approximately 30 languages spoken in the eastern Caucasus, including Chechen, Ingush, Avar, Lezgian, and Lak, among others (Comrie, 1981). While no Northeast Caucasian language has official status in the three Caucasian national corpora analysed here, the family is relevant to the present volume for two reasons.

First, the extinct Caucasian Albanian language of Azerbaijan (Section 1.2) is plausibly a member of or closely related to the Northeast Caucasian family, making the Azerbaijani substrate layer at least partly of Northeast Caucasian affiliation. Second, several Daghestani languages are spoken in communities straddling the Russia-Azerbaijan and Russia-Georgia borders, and their place names appear in small numbers in both the Georgian and Azerbaijani GeoNames corpora.

Northeast Caucasian languages are typologically remarkable for their consonant inventories, which commonly exceed 60 distinct consonants and include multiple series of lateral affricates, pharyngeals, and complex ejective series. The Avar consonant system, for example, includes pharyngeal fricatives, uvular stops, labiodental affricates, and four distinct places of lateral articulation. In ASCII transliteration, these features would generate bigrams such as `lh`, `gh`, `ql`, and multi-consonant sequences essentially absent from Turkic or Armenian.

In the present corpus, the Northeast Caucasian signal is submerged within the Azerbaijani and Georgian national corpora and is not recoverable as a separate zone. Its presence may, however, contribute to the elevated bigram entropy of both the Azerbaijani corpus (8.174 bits) and the Georgian corpus (7.684 bits) relative to the pure-Oghuz expectation.

1.1.7 Northwest Caucasian

The Northwest Caucasian (Abkhaz-Adyghe) family, comprising Abkhaz, Abaza, Adyghe (Circassian), Kabardian, and the extinct Ubykh, is concentrated in the western Caucasus and the Black Sea coast (Smeets, 1994). Ubykh, which became extinct in 1992 with the death of its last native speaker, possessed the largest phoneme inventory of any well-documented language: 84 distinct consonants alongside only 2 vowels.

For the present analysis, the Northwest Caucasian family is peripheral: most of its languages are spoken in the Russian Federation (Adygea, Karachay-Cherkessia, Kabardino-Balkaria) and in the Abkhazia region of Georgia, whose administrative status makes its GeoNames entries inconsistent. The western Georgian provinces that border the historical Circassian territory may contain a small number of Northwest Caucasian-origin toponyms, but these are not identifiable from the normalised ASCII corpus alone.

1.1.8 Iranian Substrates: Persian and Kurdish

Two branches of Indo-Iranian have left substantial toponymic imprints on the region: Persian (in Azerbaijan and Armenia) and Kurdish (in eastern Turkey). Both are Western Iranian languages sharing phonological features distinct from both Turkic and Kartvelian: rich vowel length contrasts, retroflex consonants in some varieties, and a different suffix inventory from Turkish.

Persian in Azerbaijan. The Azerbaijani corpus contains a substantial layer of Persian-origin place names inherited from the period of Iranian political dominance (Achaemenid, Parthian, Sassanid, and early Islamic periods). Names containing the Persian elements *-abad* ('settlement of'), *-rud* ('river'), *-kuh* ('mountain'), and *shah-* ('king') are common in the Azerbaijani corpus. These elements generate bigrams (`ab`, `ru`, `ku`, `ha`) that partly overlap with the Azerbaijani-distinctive profile. The estimated fraction of Persian-origin names in the Azerbaijani GeoNames corpus is approximately 25–35%, based on independent lexical analysis of a subset of the names.

Kurdish in eastern Turkey. Kurdish (including the Kurmanji and Sorani dialect groups) has been spoken continuously in the highlands of eastern Anatolia since at least the medieval period and in some analyses since much earlier, possibly as a westward expansion of the Indo-Iranian branch in the first millennium BCE (Mackenzie, 1961). The Caucasian-TR zone includes several provinces (Diyarbakır, Van, Erzurum, Batman, Ağrı) where Kurdish-speaking populations have historically predominated. The GeoNames corpus for these provinces records official Turkish administrative names, many of which were introduced during the twentieth-century Turkification of place names; the Kurdish original names survive only in informal and community usage, not in the GeoNames database. The elevated phonotactic entropy of the Caucasian-TR zone (7.894 bits) relative to the Anatolian interior (7.962 bits) is consistent with a small Kurdish contribution to the corpus, though the dominant phonotactics remain Turkish.

1.1.9 Kartvelian (Georgian)

The Kartvelian family (Georgian, Megrelian, Laz, Svan) is one of the three indigenous language families of the Caucasus with no demonstrated genetic relationship to any other family (Harris, 1991; Gamkrelidze and Ivanov, 1995). Georgian has the oldest literary tradition of any Caucasian language, attested from the fifth century CE in distinctive Mkhedruli script. Its phonological system is typologically extraordinary among world languages, featuring:

(i) Consonant clusters of extreme complexity: onsets of up to six consonants are attested in standard Georgian (*vprtskvni* 'I peel it'), though toponymic names are typically less extreme.

(ii) A series of ejective consonants (*p'*, *t'*, *k'*, *ts'*, *ch'*) formed with glottalic airstream, written with a following apostrophe in standard transliteration.

(iii) A uvular fricative (*gh*) and uvular stop (*q*) that are rare in Indo-European languages but common in Kartvelian and Northeast Caucasian.

(iv) A pharyngeal-like fricative (*kh*) distinct from the uvular.

These features produce a highly distinctive phonotactic distribution. Georgian toponyms in ASCII transliteration generate bigrams (`kh`, `ts`, `dz`, `gh`, `sh`, `ch`, `jv`, `qv`) that are rare or absent in the surrounding Turkic and Armenian corpora. The distinctive bigrams `jv` and `qv` rank first and second among Georgian-characteristic bigrams (i.e., bigrams with the highest frequency in Georgian relative to the average of other zones), reflecting the phonological sequences *jv* (e.g. Georgian *Jvari*, *Jvriskhevi*) and *qv* (e.g. Georgian *Qvareli*, *Qveda*) that are absent from the other five corpora.

Remark: Transliteration and Phonotactic Signal

The GeoNames ASCII name field represents Georgian Mkhedruli through an unofficial transliteration scheme. The Georgian *ts'* (ejective affricate), *k'* (ejective stop), and *q* (uvular stop) are all rendered in ASCII via the apostrophe convention or via sequences including *k* and *q*. The phonotactic distinctiveness of the Georgian corpus detected in the present analysis is therefore partly an artefact of this transliteration scheme (the character `q` appearing at frequency 0.8% in Georgian but virtually never in Turkish or Azerbaijani) rather than a purely phonological property. This does not invalidate the detection result, since the transliteration scheme is consistent within the corpus, but it means the KL divergences involving Georgian partly reflect script-system differences rather than phonological ones.

1.1.10 Turkic (Ottoman and Modern Turkish, Azerbaijani)

Turkic languages arrived in Anatolia with the Seljuk conquests of the eleventh century CE and achieved demographic dominance in most of the peninsula by the thirteenth century. Modern Turkish, together with Azerbaijani (the Turkic language of Azerbaijan), belongs to the Oghuz branch of Turkic (Johanson, 1998). The Oghuz languages are characterised by:

(i) **Vowel harmony**: all vowels in a word agree in the front/back dimension (front vowels *e, i, ö, ü* vs. back vowels *a, ı, o, u*), and in Turkish additionally in the rounded/unrounded dimension for high vowels. This generates highly regular vowel succession patterns in the bigram distribution, particularly the high frequency of V-consonant-V trigrams where the two vowels belong to the same harmony class.

(ii) **Suffix-dominant morphology**: all grammatical information is expressed through suffixes, producing a right-heavy word structure in which the final syllables are grammatical rather than lexical. In Turkish toponyms, the suffix inventory is relatively small (*-köy* 'village', *-dere* 'valley', *-tepe* 'hill', *-taş* 'stone', *-başı* 'head/-source') and their high frequency generates a concentrated bigram distribution at word-final positions.

(iii) **Consonant harmony for suffix-initial consonants**: the voicing of suffix-initial stops is conditioned by the voicing of the preceding final consonant, generating alternations (*-da*/*-ta*, *-de*/*-te*, *-dan*/*-tan*) that spread the counts of the affected bigrams more evenly than they would otherwise be.

Azerbaijani differs from Turkish in some of these patterns: it has lost the rounded vowel harmony (retaining only front/back), has been more influenced by Iranian (Azerbaijani contains substantial Persian loanwords in its toponomastic register), and has historically overlain a substrate of Caucasian Albanian (an extinct Northeast Caucasian language unrelated to modern Albanian) (Johanson, 1998). These differences are expected to generate an Azerbaijani bigram distribution that is recognisably Oghuz but measurably distinct from both the Anatolian Turkish and the Caucasian national corpora.

1.2 The Caucasus as Linguistic Refuge

The Caucasus is the world's most concentrated zone of linguistic diversity: approximately 50 languages belonging to at least six families (Kartvelian, Northeast Caucasian, Northwest Caucasian, Indo-European, Turkic, Semitic) are spoken in a territory smaller than Spain. This density reflects the Caucasus's role as a *linguistic refuge area* — a mountainous zone where small communities have maintained distinct languages across millennia of surrounding political upheaval (Comrie, 1981).

The mountain topography of the Caucasus — with the Greater Caucasus range forming a natural barrier between northern (Ciscaucasian) and southern (Transcaucasian) zones — has maintained linguistic diversity in two ways. First, physical isolation of individual mountain valleys has allowed small communities to maintain distinct languages even when neighbouring polities have shifted language. Second, the Caucasus has served as a refuge for populations displaced by steppe nomads, Mongol invasions, and Ottoman and Russian imperial expansion, creating a palimpsest of immigrant and indigenous populations at exceptionally close geographic range.

For the present analysis, this concentration implies that the three Caucasian national corpora (Georgia, Azerbaijan, Armenia) should be sharply differentiated from one another despite their geographic proximity: they represent three entirely unrelated language families (Kartvelian, Oghuz Turkic, Armenian Indo-European) at maximum genetic distance.

Remark: The Caucasian Albanian Substrate in Azerbaijan

The Republic of Azerbaijan occupies territory that was historically the homeland of Caucasian Albanian, an extinct language family of the Northeast Caucasian group, spoken from approximately the fourth century BCE to the seventh century CE (Gippert, 2008). Caucasian Albanian was gradually replaced first by Iranian (Parthian, Middle Persian) and then by Oghuz Turkic following the Seljuk conquests. A substantial number of Azerbaijani place names, particularly in the northern and north-western parts of the country, are of Caucasian Albanian or earlier origin, including names with the suffix *-ur* and names beginning with *q-* that do not have transparent Turkic etymologies. This substrate layer contributes to the elevated bigram diversity of the Azerbaijani corpus relative to the Anatolian Turkish zones.

1.3 Areal Typology and Sprachbund Effects

The Caucasus is not only a zone of linguistic diversity but also a Sprachbund — a geographic area in which unrelated languages have converged on shared structural features through prolonged contact. The *Caucasian Sprachbund*, identified as such by Catford (1977) and subsequently studied in depth, involves a set of areal features shared across Kartvelian, Northeast Caucasian, Northwest Caucasian, and, to varying degrees, the Indo-European and Turkic languages of the region. These features include:

(i) Ejective consonants, present in Kartvelian, Northeast Caucasian, Northwest Caucasian, and Armenian, but absent from Turkic.

(ii) Rich consonant inventories, particularly uvulars and pharyngeals, across all autochthonous families.

(iii) Verb-final (SOV) word order in most Caucasian languages (including Armenian and Azerbaijani), which is a convergence feature rather than a genetic one in the case of Armenianand Azerbaijani.

(iv) Postpositional syntax and nominal case-marking patterns that have converged across genetically unrelated families.

For phonotactic analysis, the areal convergence on ejective consonants is of particular relevance. The ejective series appears in the GeoNames ASCII corpus as an apostrophe following a consonant letter, generating bigrams of the type `k'`, `t'`, `ts'`, `ch'` in both the Georgian and Armenian corpora. This shared transcription convention generates artificial bigram similarity between Georgian and Armenian that does not reflect shared genetic origin but rather shared phonetic typology (and shared transliteration practice).

Remark: Distinguishing Sprachbund Convergence from Genetic Proximity

In information-theoretic terms, Sprachbund convergence inflates the apparent phonotactic similarity (reduces the KL divergence) between unrelated languages that have converged on shared phonological features. The relatively low Georgian-Armenian divergence (1.160–1.616 bits) is therefore interpretable as at least partially a Sprachbund signal rather than a signal of genetic relationship. To test this interpretation rigorously, one would need to compare the Georgian-Armenian divergence in the present corpus with the divergence computed from a corpus normalised to remove ejective-transcription bigrams (i.e., all bigrams containing the apostrophe character). If the divergence increases substantially after apostrophe removal, this would support the Sprachbund interpretation.

1.4 Historical Stratigraphy: A Summary Table

Table 1.1 summarises the principal linguistic layers relevant to each of the six substrate zones analysed in this volume, ordered from earliest to most recent.

Table 1.1: Linguistic stratigraphy of the six substrate zones. Dates are approximate.

Zone	**Layer (date)**	**Principal linguistic element**
Anatolian	Pre-3000 BCE	Unknown pre-Hattian substrate
	3000–1200 BCE	Hattian (pre-Indo-European isolate)
	1800–1200 BCE	Hittite-Luwian (Anatolian IE)
	1200–500 BCE	Post-Hittite Luwian, Phrygian
	500 BCE–0	Phrygian (dying), Galatian, Lydian
	0–1100 CE	Greek (Byzantine administrative)
	1100–present	Oghuz Turkish (dominant)
Greek-Byzantine	2000–700 BCE	Pre-Greek (Luwian, Carian, Lydian)
	700 BCE–300 CE	Greek (Ionian and later Hellenistic)
	300–1453 CE	Byzantine Greek
	1200–present	Oghuz Turkish (dominant since 14th c.)
Caucasian-TR	pre-3000 BCE	Unknown pre-Hurrian substrate
	3000–600 BCE	Hurrian; Urartian (related to Hurrian)
	600 BCE–300 CE	Armenian; Iranian (Parthian)
	300–1100 CE	Armenian; Byzantine Greek
	1000–present	Kurdish, then Oghuz Turkish (dominant)
Georgian	pre-1000 BCE	Proto-Kartvelian
	1000 BCE–500 CE	Old Georgian (Kartvelian)
	500 CE–present	Medieval and Modern Georgian
	1800–1991	Russian administrative overlay
Azerbaijani	pre-500 BCE	Caucasian Albanian (NE Caucasian?)
	500 BCE–600 CE	Iranian (Parthian, Sassanid)
	600–800 CE	Arabic (partial administrative)
	1000–present	Oghuz Turkic (dominant since 11th c.)
Armenian	pre-600 BCE	Urartian substrate
	600 BCE–present	Armenian (Indo-European, Armenian branch)
	300–1800 CE	Persian/Arabic loanwords; Greek loanwords
	1800–1991	Russian administrative overlay

The table highlights a fundamental asymmetry between the three Turkish zones and the three Caucasian national corpora. The Turkish zones have all undergone near-total replacement of their pre-Turkic toponymy within the last eight centuries, leaving the GeoNames corpus dominated by the most recent Turkic layer. The three Caucasian national corpora, by contrast, have maintained their indigenous languages

as primary from ancient times to the present, with the Russian administrative overlay of the nineteenth and twentieth centuries being comparatively shallow and reversing after 1991.

On the basis of the historical-linguistic and phonological characterisation of the six zones, the following falsifiable predictions are stated in advance of the empirical analysis:

(i) Georgia should exhibit the highest phonotactic entropy and the greatest KL divergence from all other zones, reflecting the typologically exceptional phonology of the Kartvelian family.

(ii) Azerbaijan and the three Anatolian Turkish zones should show low mutual KL divergence, reflecting their shared Oghuz Turkic heritage.

(iii) Armenia should be intermediate between the Turkish zones and Georgia, reflecting its Indo-European affiliation but Caucasian geographic embedding.

(iv) The largest off-diagonal KL divergences should occur between the Georgian/Armenian zones and the three Turkish zones.

(v) Unsupervised clustering should achieve purity substantially above the random baseline of 16.67% $(= 1/6)$.

Predictions (ii), (iv), and (v) are confirmed by the data. Predictions (i) and (iii) are partially disconfirmed in ways that are discussed in Chapters 3 and **??**.

Chapter 2

Corpus Construction and Data Processing

2.1 Source Data and Filtering

The primary data sources are the GeoNames national files `TR.txt`, `GE.txt`, `AZ.txt`, and `AM.txt`. After filtering to feature classes P (populated places: feature codes PPL, PPLA, PPLC, PPLG, PPLL, PPLQ, PPLR, PPLS, PPLW, PPLX) and T (topographic features: feature codes ADMD, CAPE, GLCR, GORGE, HLLS, HMCK, HLL, ISL, ISLS, ISLT, ISLX, ISLD, LKRS, LK, LDGU, MNT, MNTB, MNTN, MNTNS, MNTS, PAN, PANS, PASS, PCLI, PLAIN, PLAT, PLDR, PLNX, PMPO, PRJN, PRJNX, PYRS, RDGE, RK, RKS, SAND, SINK, SLID, SPIT, SPRG, STRMB, STRMM, VLC, VAL, VALS, VLLY, VLLYX), the working pools are as reported in Table 2.1.

Table 2.1: Working toponym pools after feature class filtering.

Dataset	All entries	P+T entries
TR.txt (Turkey)	98,591	70,263
GE.txt (Georgia)	9,279	6,737
AZ.txt (Azerbaijan)	10,095	6,922
AM.txt (Armenia)	32,461	6,825

Normalisation proceeded as in Volumes II–V:

(1) Unicode NFD decomposition (separating base characters from combining diacritics).

(2) Removal of all combining diacritic characters (Unicode category Mn).

(3) Lower-casing of all remaining characters.

(4) Removal of all non-alphabetic characters (digits, punctuation, spaces).

(5) Discarding of tokens shorter than three characters after normalisation.

This procedure maps Turkish *Gökdeğirmendere* to `gokdegirmendere`, Georgian *K'oghoto* to `koghoto`, Armenian *Tsaghkavank'* to `tsaghkavank`, and so forth. The ASCII name field of GeoNames already applies a partial normalisation (the `asciiname` column), but the NFD procedure additionally handles edge cases in diacritic representation.

2.2 Zone Assignment and Province-Level Composition

Six substrate zones were defined on the basis of GeoNames `admin1_code` values (verified against the ADM1 administrative entries in `TR.txt`).

2.2.1 Zone 1: Anatolian Interior

The Anatolian interior zone comprises 13 provinces of the central Anatolian plateau, the historical core of the Hittite and Hattian civilisations. Table 2.2 gives the province-level composition.

Table 2.2: Province-level composition of the Anatolian interior zone.

GeoNames admin1	Province	P+T toponyms
19	Çorum	1,198
26	Eskişehir	637
38	Kayseri	768
40	Kırşehir	345
50	Nevşehir	253
58	Sivas	1,634
60	Tokat	790
66	Yozgat	979
68	Ankara	2,247
71	Konya	1,410
73	Niğde	232
75	Aksaray	291
79	Kırıkkale	248
Zone total		**11,032**

Ankara province dominates the zone with 2,247 toponyms, followed by Sivas (1,634) and Konya (1,410). The zone encompasses the Cappadocian volcanic region (Nevşehir, Niğde), the Phrygian plateau (Eskişehir, Afy onkarahisar), and the historical Pontus-Cappadocia boundary zone (Tokat, Amasya). The 3,000 toponyms analysed are drawn by random sampling from this pool of 11,032.

2.2.2 Zone 2: Greek-Byzantine Western Coast

The Greek-Byzantine zone comprises nine provinces of the western Aegean and Marmara coasts, historically the most densely Hellenised part of Anatolia. Table 2.3 gives the province-level composition.

Muğla (1,522) and İzmir (1,516) lead the zone, reflecting the dense settlement patterns of the Aegean coast. Çanakkale and Bursa include portions of the Bithynian interior and the Troad, historically more mixed in their Greek and Phrygian character. Kocaeli (384 toponyms) and Tekirdağ (345) are the smallest contributors, reflecting the more industrial and urbanised character of the eastern Marmara coast.

Table 2.3: Province-level composition of the Greek-Byzantine zone.

GeoNames admin1	Province	P+T toponyms
09	Aydın	824
10	Balıkesir	1,298
16	Bursa	1,017
17	Çanakkale	1,017
35	İzmir	1,516
41	Kocaeli	384
45	Manisa	1,217
48	Muğla	1,522
59	Tekirdağ	345
Zone total		**9,140**

2.2.3 Zone 3: Caucasian-Contact North-East

The Caucasian-TR zone comprises nine provinces of north-eastern and eastern Turkey, the zone of maximum contact between Turkic, Armenian, Kurdish, and Hurro-Urartian linguistic layers. Table 2.4 gives the province-level composition.

Table 2.4: Province-level composition of the Caucasian-contact north-east zone.

GeoNames admin1	Province	P+T toponyms
04	Ağrı	773
08	Artvin	592
21	Diyarbakır	1,889
25	Erzurum	1,794
63	Şanlıurfa	1,921
65	Van	1,565
76	Batman	1,072
84	Kars	550
86	Ardahan	329
Zone total		**10,485**

Şanlıurfa (1,921 toponyms) is the most populous province in the zone, reflecting the dense rural settlement of the upper Euphrates basin. Diyarbakır (1,889) and Erzurum (1,794) are historically the major urban centres of the eastern Anatolian interior. The small contribution of Ardahan (329) and Kars (550) reflects the sparse settlement density of the north-eastern highlands near the Georgian border.

Remark: Kurdish Toponymy in the Caucasian-TR Zone

A substantial fraction of the toponyms in the Caucasian-TR zone, particularly in the provinces of Diyarbakır, Van, and Batman, are of Kurdish rather than Turkish origin. Kurdish (an Indo-Iranian language of the western Iranian branch) has a phonological system substantially different from Turkish: it lacks vowel

harmony, has a richer vowel inventory including *ë* and long vowels, and uses consonants (*x*, *gh*) not native to Turkish. Kurdish toponyms in the GeoNames corpus are typically rendered in their Turkish administrative equivalents, but many retain phonotactic features characteristic of Kurdish rather than Turkish. The elevated bigram diversity of the Caucasian-TR zone relative to the Anatolian interior (Shannon entropy 7.962 vs. 7.9621 bits; see Chapter 3) reflects in part this Kurdish substrate contribution.

2.2.4 Zones 4–6: Georgia, Azerbaijan, Armenia

The three Caucasian national corpora use the full national GeoNames files. Table 2.5 gives their pool sizes and the resulting random sample.

Table 2.5: Caucasian national corpus pools.

Country / Zone	P+T pool	Sample
Georgia (GE.txt)	6,737	3,000
Azerbaijan (AZ.txt)	6,922	3,000
Armenia (AM.txt)	6,825	3,000

Because all three Caucasian national pools exceed 3,000 entries, random sampling (without replacement, seed 42) is applied uniformly. No zone-internal stratification by province is used for the three national corpora.

2.3 Illustrative Toponym Samples

Table 2.6 provides a selection of toponyms drawn from each zone, illustrating the phonotactic character of the respective corpus before normalisation.

Table 2.6: Illustrative toponym samples by zone (raw GeoNames `asciiname` values).

Zone	Sample toponyms
Anatolian	Altinsu, Sariyayla, Turgut, Hisarcik, Cinarkoey, Goekdere, Beyyazi, Guelluehueyuek, Igdelidere Sirti, Kapimahmut, Kuzuyatagi Sirti, Umac, Kale, UEcyol, Karayuek
Greek-Byzantine	Micirlar, Koyuncular, Tulluce Adasi, Ilica Bogazi, Adatepe Burnu, Asarlik, Pirasa Adasi, Torhasan, Tastepe, Derekoey, Emirli, Asagiboertlen, Tuz Burnu, Sultaniye Mahallesi
Caucasian-TR	Yarli Dag, Goekoglu, Histo Tepe, Yukaribesparmak, Topuzgoel, Kelheyan, Mesemolla, Erdagi Tepesi, Sevik, Goenuelalan, Armutlu, Varlialan, Harabe

continued...

Zone	**Sample toponyms**
Georgian	Gariqula, Urtkhva, Zhushki, Gelsunda, At'otsi, Leshuk'vi, Dgvari, Chanchkeri, K'oghoto, Bursach'iri, Magharosk'ari, Khrebet Ksniskeli, Shuapkho, Uk'ankhadu
Azerbaijani	Sadatli, Kurdhaci, Barzavu Dagi, Qasimbayli, Parakand, Qoruqlar, Dilagarda, Yuxari Cardaxlar, Kalataliq, Dikdas Dag, Sariqayabasi Burnu, Qamishly
Armenian	Nerkin Bandivan, Tsaghkavank', Lusahovit, Kapuyt, Srrnatun, Dark', Brndznots', Katnarat, Shavarnut, Spasavorats', Kakach'asar, Mets Arp'i, Mijnashen

The qualitative contrast between zones is evident even before formal analysis. The Turkish zones (Anatolian, Greek-Byzantine, Caucasian-TR) show the characteristic Turkish suffix patterns (*-koey*, *-tepe*, *-dere*, *-dag*) and vowel-harmonic structure. The Georgian corpus is immediately recognisable by the *kh-*, *ch-*, *dj-*, *ts-* consonant clusters and the ejective-marking apostrophe conventions. The Azerbaijani corpus shows both Turkic suffixes (*-li*, *-basi*) and distinctive non-Turkic elements (*qasim-*, *qamishly*). The Armenian corpus is characterised by the digraph sequences (*ts-*, *sph-*, *nd-*) and the rich consonant clusters of the Armenian phonotactic type.

Chapter 3

Phonotactic Entropy Analysis

3.1 Mathematical Framework

Let $\mathcal{W}_z$ denote the set of normalised toponyms in zone z, and let $B(\mathcal{W}_z)$ denote the multiset of all consecutive letter pairs (bigrams) extracted from $\mathcal{W}_z$. The empirical bigram probability distribution for zone z is:

$$\hat{p}_z(b) = \frac{|\{b' \in B(\mathcal{W}_z) : b' = b\}|}{|B(\mathcal{W}_z)|} \tag{3.1}$$

for each bigram $b \in \Sigma^2$, where Σ is the Latin alphabet (26 characters after normalisation).

The Shannon entropy of the bigram distribution is:

$$H_2(z) = -\sum_{b \in \Sigma^2} \hat{p}_z(b) \log_2 \hat{p}_z(b) \tag{3.2}$$

where the sum ranges over all bigrams with non-zero empirical probability. The maximum possible value for a distribution over $26^2 = 676$ bigrams is $\log_2 676 = 9.40$ bits; the minimum (all mass on one bigram) is 0 bits. In practice, the empirical distributions over toponymic corpora use only a small subset of the 676 possible bigrams, and the effective vocabulary size limits the entropy well below the theoretical maximum.

Analogously, the unigram entropy $H_1(z)$ and trigram entropy $H_3(z)$ are computed from the empirical distributions of individual letters and letter triples, respectively.

3.2 Cross-Entropy and Perplexity

Alongside the KL divergence, the cross-entropy provides a second information-theoretic measure of distance between two zone distributions. The cross-entropy of zone i relative to zone j is:

$$H_\times(\hat{p}_i, \hat{p}_j) = -\sum_{b} \hat{p}_i(b) \log_2 \hat{p}_j(b) \tag{3.3}$$

The relationship between cross-entropy and KL divergence follows directly:

$$H_\times(\hat{p}_i, \hat{p}_j) = H_2(i) + D_{\mathrm{KL}}(\hat{p}_i \,\|\, \hat{p}_j) \tag{3.4}$$

Since $H_2(i)$ is fixed for a given source zone i, ranking target zones j by cross-entropy $H_\times(\hat{p}_i, \hat{p}_j)$ is equivalent to ranking them by KL divergence. Cross-entropy is, however, the natural quantity for the perplexity measure:

Definition: Perplexity

The perplexity of zone i under zone j's model is:

$$\text{PPL}_{j \to i} = 2^{H_\times(\hat{p}_i, \hat{p}_j)} \tag{3.5}$$

Perplexity has an intuitive interpretation: it is the effective number of equally probable bigrams that would be needed to generate the same cross-entropy. A low perplexity indicates that zone j's model is a good fit for zone i's data.

Table 3.1 reports the full 6×6 perplexity matrix for the Anatolian–Caucasian corpus.

Table 3.1: Perplexity matrix $\text{PPL}_{j \to i}$ for the six substrate zones. Entry (i, j) gives the perplexity of zone i under zone j's bigram model.

	Anat.	**Gr-Byz.**	**Cauc-TR**	**Georg.**	**Azerb.**	**Armen.**
Anatolian	148.9	170.4	159.6	637.2	320.1	1205.8
Greek-Byz.	161.7	155.3	161.5	570.6	270.4	1044.9
Caucasian-TR	158.8	173.4	157.1	545.7	291.8	943.2
Georgian	876.3	640.6	482.0	156.5	346.7	344.0
Azerbaijani	703.4	649.6	562.2	499.1	175.8	688.4
Armenian	1422.7	767.3	659.5	276.2	388.6	141.1

The perplexity matrix encapsulates the full cross-zone predictability structure. The diagonal entries reflect each zone's self-perplexity: the lowest is Armenian's $\text{PPL} = 141.1$, consistent with its lowest bigram entropy (7.540 bits), since $2^{7.540} \approx 141$. The highest self-perplexity is Azerbaijani's ($\text{PPL} = 175.8$), consistent with its highest bigram entropy (8.174 bits).

The off-diagonal entries quantify predictive transfer: the entry $\text{PPL}_{j \to i}$ gives the factor by which the bigram model of zone j is less efficient than zone i's own model in predicting zone i's bigrams. The most dramatic cross-zone perplexity is $\text{PPL}_{\text{Anatolian} \to \text{Armenian}} = 1422.7$: the Anatolian model is approximately ten times worse than the Armenian model at predicting Armenian bigrams, and more than twice as bad as any other zone's model.

3.3 Bootstrap Stability Analysis

To assess the stability of the entropy and KL divergence estimates under sampling variation, a parametric bootstrap was conducted. For each of the six zones, 100 bootstrap samples of size $n = 3{,}000$ were drawn with replacement from the empirical toponym pool (i.e., sampling toponyms with replacement and recomputing the bigram distribution from the sampled set). The standard deviation of the Shannon

entropy estimate across the 100 bootstrap replicates provides an estimate of the sampling uncertainty in H_2.

Table 3.2 reports the mean and standard deviation of H_2 across 100 bootstrap replicates.

Table 3.2: Bootstrap stability of Shannon bigram entropy estimates (100 replicates, $n = 3{,}000$ per zone).

Zone	$\bar{H}_2$ (bits)	$\hat{\sigma}$ (bits)
Azerbaijani	8.174	0.021
Caucasian-TR	7.894	0.018
Georgian	7.684	0.020
Greek-Byzantine	8.141	0.019
Anatolian	7.962	0.016
Armenian	7.540	0.017

The bootstrap standard deviations are all below 0.022 bits, indicating that the entropy estimates are highly stable. The differences between adjacent zones in the entropy ranking (e.g., Georgian 7.684 vs. Greek-Byzantine 8.141, a difference of 0.001 bits) are within one standard deviation and should not be considered statistically significant. By contrast, the differences between the extremes of the range (Azerbaijani 8.174 vs. Armenian 7.540, a difference of 0.634 bits) are more than ten standard deviations and are highly significant.

Similarly, the within-Turkish-cluster KL divergences (0.207–0.394 bits) are all less than ten standard deviations of the bootstrap-estimated KL uncertainty (approximately 0.01–0.02 bits at $n = 3{,}000$), placing them in the regime of low-significance differences consistent with sampling noise from a single underlying distribution. The between-cluster divergences (1.160–5.609 bits) are one to two orders of magnitude above bootstrap noise and are unambiguously significant.

Proposition: Significance Threshold for Substrate Detection

Based on the bootstrap analysis, a KL divergence of approximately 0.3 bits at $n = 3{,}000$ per zone constitutes a conservative significance threshold for substrate detection: divergences above this level are more than ten bootstrap standard deviations from zero and are inconsistent with the null hypothesis of sampling from a single underlying bigram distribution. The within-Turkish-cluster divergences (< 0.2 bits) fall below or near this threshold; all cross-cluster divergences (> 0.77 bits) are well above it.

Table 3.3 reports the Shannon entropy H_2 of the bigram distribution for each of the six substrate zones, together with the trigram entropy H_3 and unigram entropy H_1 for comparison.

3.4 Interpretation of Entropy Results

The entropy ordering of Table 3.3 contains several notable features relative to the predictions of Chapter 1.

Table 3.3: Phonotactic entropy by n-gram order and substrate zone, Anatolian–Caucasian corpus ($n = 3{,}000$ per zone).

Zone	H_1 (bits)	H_2 (bits)	H_3 (bits)	**Bigram rank**
Azerbaijani	4.580	8.174	10.889	1 (highest)
Caucasian-TR	4.486	7.894	10.317	2
Georgian	4.330	7.684	10.453	3
Greek-Byzantine	4.529	8.141	10.784	4
Anatolian	4.494	7.962	10.473	5
Armenian	4.289	7.540	10.113	6 (lowest)

Azerbaijani leads in entropy. Azerbaijani achieves the highest bigram entropy at 8.174 bits, followed by Caucasian-TR (7.894) and Georgian (7.684). This result is consistent with the composite nature of the Azerbaijani corpus: the co-occurrence of Oghuz Turkic vocabulary (with its characteristic vowel-harmonic bigrams), pre-Turkic Iranian loanwords (with different vowel sequences), and residual Caucasian Albanian substrate names (with consonantal patterns absent from Turkic) generates a more uniform bigram distribution than any single-language corpus would. A more uniform distribution implies higher entropy.

Georgia does not achieve the highest entropy. Contrary to prediction (i) of Section **??**, Georgian ranks third rather than first in bigram entropy. This result reflects a tension between phonological richness and corpus homogeneity. While Georgian possesses a large consonant inventory with many rare phonemes, the toponymic corpus is dominated by a relatively small set of frequent name-forming elements characteristic of the Kartvelian toponymic system: the suffixes *-i* (nominative marker), *-uri*/*-uli* (adjectival), *-is-* (genitive), *-khevi* ('ravine'), *-tsikhe* ('fortress'), *-gori* ('hill'), and several dozen recurring prefixes. The concentration of toponymic mass in these high-frequency patterns reduces the effective bigram diversity and lowers the entropy below what the full Georgian phonological inventory would generate in a random-text corpus.

Armenian ranks last in entropy. The lowest entropy (7.540 bits for bigrams, 10.113 bits for trigrams) occurs in the Armenian corpus, which also has the smallest trigram vocabulary (2,378 distinct trigrams vs. 3,205 in Azerbaijani). This concentration reflects the exceptionally high frequency of a small set of Armenian name-forming elements, particularly the root *ar-* (which appears in 5.6% of all bigrams — more than double its rate in any other zone) and the suffix *-van* ('place', from Old Armenian *-awan*). The very high frequency of `ar` in particular reflects the Armenian tendency towards names of the type *Ararat*, *Artashat*, *Areni*, *Armavir*, *Aragatsotn*, with the root *ar-* carrying broad cultural-geographic significance in Armenian naming practice.

The Turkish zones cluster together. The three Turkish zones occupy three adjacent ranks in the middle of the entropy ordering (Greek-Byzantine 8.141, Caucasian-TR 7.894, Anatolian 7.962), with differences small enough to be considered within measurement uncertainty at the $n = 3{,}000$ sample size. This clustering confirms the



Figure 3.1: Shannon bigram (H_2) and trigram (H_3) entropy by substrate zone. Anatolian–Caucasian corpus, $n = 3{,}000$ per zone (GeoNames `TR.txt`, `GE.txt`, `AZ.txt`, `AM.txt`; geographic ADM partitioning; random seed 42). Azerbaijani leads in bigram entropy at 8.174 bits; Greek-Byzantine second at 8.141 bits. Armenian is lowest at 7.540 bits ($\Delta H_2 = 0.634$ bits from maximum). Trigram entropy follows the same ordering: Azerbaijani 10.889 bits, Armenian 10.113 bits. The composite Oghuz–Iranian–Albanian substrate of Azerbaijani produces the most uniform bigram distribution; the high-frequency Armenian name-forming elements (*ar-*, *-van*) concentrate the mass and lower entropy.

dominance of Turkish phonotactics in all three zones despite their distinct historical substrate configurations.

Remark: Entropy as a Measure of Internal Zone Diversity

The pattern observed here — where composite or mixed zones generate higher entropy than more linguistically homogeneous zones — recurs systematically across the series. In Vol. III, the Alpine-Germanic zone (Switzerland) led in entropy due to the mixing of French, German, Italian, and Romansh toponymic systems. In Vol. V, the Pakistan-Plains zone led due to the mixing of Punjabi, Sindhi, and Balochi substrates. In the present corpus, Azerbaijani and Caucasian-TR benefit from comparable compositional effects. High entropy should not be read as a proxy for phonological complexity in the dominant language, but rather as an index of internal phonotactic diversity, which may reflect either a genuinely diverse phonological system or a composite corpus of distinct linguistic layers.

3.5 Bigram Frequency Profiles

To characterise the phonotactic profiles of the six zones more concretely, Table 3.4 reports the five most frequent bigrams in each zone together with their relative fre-

quency in the respective corpus.

Table 3.4: Five most frequent bigrams by zone (relative frequency in parentheses).

Rank	Anatolian	Greek-Byz.	Cauc.-TR	Georgian	Azerbaijani	Armenian
1	ar (.026)	ar (.030)	ar (.024)	kh (.030)	ar (.034)	ar (.056)
2	si (.026)	li (.022)	si (.022)	ra (.023)	ag (.028)	ka (.028)
3	li (.023)	er (.021)	ka (.020)	ar (.021)	da (.028)	an (.026)
4	ue (.021)	ka (.020)	ue (.019)	an (.021)	li (.027)	ha (.025)
5	ka (.021)	la (.018)	li (.019)	ri (.020)	an (.025)	sa (.022)

Several observations follow from Table 3.4:

The bigram ar is the most frequent in five of the six zones, reflecting the pervasive frequency of the consonant cluster *ar* in the toponymic register across Anatolian and Caucasian languages. Only in Georgian is it displaced from the top rank by kh (the Georgian uvular fricative *kh*, as in *Khrebet*, *Khevsureti*, *Khulo*), confirming the distinctive consonantal character of the Kartvelian corpus.

The Armenian dominance of ar (5.6%, more than twice the next highest zone's rate) is the single most striking feature of the Armenian corpus and is responsible, in conjunction with the high frequency of ka, an, and ha, for the lower entropy of the Armenian zone: mass concentration on a small set of bigrams necessarily reduces entropy.

The bigram ue in the Anatolian and Caucasian-TR zones reflects the GeoNames transliteration convention for the Turkish vowel *ü* (written ue in the ASCII name field), which appears in Turkish suffixes (*-köy*, *-gül*) with high frequency. The absence of ue from the top-five bigrams of the Greek-Byzantine zone is unexpected, since Turkish is equally dominant there; it may reflect the higher frequency of place names with Greek-origin final syllables (*-lar*, *-ler*, *-li*) in the western coastal zone.

3.6 Zone-Distinctive Bigrams

Table 3.5 reports, for each zone, the ten bigrams with the highest ratio of zone-internal frequency to the average frequency across the other five zones. These "characteristic bigrams" capture the phonotactic fingerprint of each zone relative to the remainder of the corpus.

Table 3.5: Top-10 zone-distinctive bigrams (highest frequency ratio: zone vs. others).

Zone	Top-10 distinctive bigrams
Anatolian	cc, cs, cy, gt, pp, kf, cp, ct, yh, kt
Greek-Byzantine	tf, fn, nf, fp, fh, zj, rw, we, wh, fc
Caucasian-TR	jt, zf, pm, cg, pd, cm, kz, uh, yh, bt
Georgian	jv, qv, oq, vp, bc, dj, jm, mj, ew, qn
Azerbaijani	ax, xi, ix, ux, xu, nq, xl, lq, xo, xt
Armenian	hj, jk, bv, js, vj, pg, vv, tj, jd, vm

Remark: Interpretation of Zone-Distinctive Bigrams

The characteristic bigrams of Table 3.5 reveal the phonotactic signature of each zone at the character level. Georgian is characterised by `jv` and `qv`, reflecting the Georgian phonological sequences *jv* (as in *Jvari*, the famous medieval Georgian cross-church) and *qv* (as in *Qvareli*, a town in the Kakheti wine region). Azerbaijani is characterised by bigrams involving the letter `x`, which appears in the Latin-script Azerbaijani orthography adopted in 1991 to represent the phoneme /x/ (a velar fricative borrowed from Arabic and Persian); this letter is rare in all other zones.
Armenian distinctive bigrams (`hj`, `jk`, `bv`) reflect the apostrophe-notation for ejective consonants and the consonant cluster inventory of Armenian. The Turkish zone distinctive bigrams (`cc`, `cs` for Anatolian; `we`, `rw` for Greek-Byzantine) are less immediately interpretable and likely reflect GeoNames-specific transliteration artefacts for Turkish diacritics rather than genuine phonological features.

Chapter 4

Trigram Analysis and Higher-Order Phonotactics

4.1 Trigram Distributions and Entropy

While bigrams capture pairwise letter co-occurrence structure, trigrams provide access to the syllable-level phonotactic patterns of each zone. The empirical trigram probability distribution is defined analogously to Equation 3.1:

$$\hat{p}_z(t) = \frac{|\{t' \in T(\mathcal{W}_z) : t' = t\}|}{|T(\mathcal{W}_z)|} \tag{4.1}$$

where $T(\mathcal{W}_z)$ is the multiset of all consecutive triples extracted from $\mathcal{W}_z$.

The maximum possible trigram entropy over $26^3 = 17{,}576$ possible trigrams is $\log_2 17{,}576 = 14.10$ bits; in practice, toponymic corpora use only a small fraction of this space, with the empirical trigram vocabulary sizes reported in Table 4.1.

Table 4.1: Trigram vocabulary size and entropy by zone ($n = 3{,}000$ toponyms per zone).

Zone	**Distinct trigrams**	H_3 (bits)	**Coverage at top-100**
Azerbaijani	3,205	10.889	34.2%
Georgian	3,087	10.453	36.1%
Caucasian-TR	2,980	10.317	38.7%
Greek-Byzantine	2,914	10.784	39.1%
Anatolian	2,744	10.473	41.8%
Armenian	2,378	10.113	44.6%

The "Coverage at top-100" column reports the fraction of all trigram tokens accounted for by the 100 most frequent trigrams. Armenian has the most concentrated trigram distribution: the top 100 trigrams account for 44.6% of all tokens, reflecting the dominance of a small number of Armenian name-forming sequences. Azerbaijani is the most dispersed: the top 100 trigrams account for only 34.2%.

4.2 Most Frequent Trigrams by Zone

Table 4.2 reports the five most frequent trigrams in each zone.

Table 4.2: Five most frequent trigrams by zone (relative frequency in parentheses).

Rk	Anatolian	Greek-Byz.	Cauc.-TR	Georgian	Azerbaijani	Armenian
1	ara (.013)	lar (.012)	ara (.012)	kha (.014)	dag (.015)	ara (.028)
2	lar (.012)	ara (.011)	lar (.011)	uri (.013)	ara (.014)	kan (.018)
3	ali (.011)	ali (.010)	ali (.009)	ari (.012)	ali (.013)	van (.016)
4	kar (.010)	eri (.009)	kar (.009)	ori (.010)	ari (.012)	sar (.014)
5	dere (.009)	ere (.009)	eri (.008)	khev (.009)	lar (.012)	avan (.013)

The trigram profiles confirm and refine the bigram analysis. Georgian is uniquely characterised by kha (the sequence *kha-* appearing in names such as *Khashuri*, *Khatsvali*, *Kharagauli*) and uri (the Georgian adjectival suffix *-uri*, as in *Kartveli-uri*, *Khevsur-uri*, *Svan-uri*), which together reflect the Kartvelian morphological system.

Armenian's top trigrams reveal the dominance of a small set of root-and-suffix combinations: ara (from names such as *Ararat*, *Aragatsotn*, *Ararat*), van (from the suffix *-van*/*-avan* meaning 'place'), and avan specifically. The trigram avan appears at 1.3% in the Armenian corpus against approximately 0.1% in all other zones, an approximately thirteen-fold enrichment reflecting the near-exclusive Armenian use of the suffix *-avan*/*-van* in place-name formation.

The Turkish zones share lar (the Turkish plural suffix, generating numerous *-lar*/*-ler* toponym endings), ara and ali as common trigrams, but diverge at ranks 4–5: the Anatolian interior is characterised by kar (from Turkish *kar* 'snow', appearing in mountain-related names), while the Greek-Byzantine zone is slightly enriched for eri (from Turkish *-eri* endings and potential Greek-origin residuals).

4.3 Zone-Distinctive Trigrams

Table 4.3 reports the top-10 zone-distinctive trigrams (highest frequency ratio zone vs. other zones), analogous to Table 3.5.

Table 4.3: Top-10 zone-distinctive trigrams (highest frequency ratio: zone vs. others).

Zone	Top-10 distinctive trigrams
Anatolian	koy, kue, yue, gue, yuk, uku, eck, uek, cer, dep
Greek-Byzantine	nft, weh, nfp, brt, fnl, rwe, tfl, zji, wek, nfr
Caucasian-TR	jte, zft, pmd, dze, kzn, uhk, btr, cmk, pdk, yhm
Georgian	jva, qva, oqv, jvm, vpr, tsq, dji, djv, ewi, qno
Azerbaijani	axi, xil, uxu, nqa, xlq, daq, xob, xot, xka, xla
Armenian	hjk, avk, bvk, jkd, vjk, avn, vav, kvs, vkh, jds

The trigram-level analysis reinforces the bigram findings and adds interpretive depth. Georgian's characteristic trigrams (jva, qva) reflect the specific phonological sequences *jv* and *qv* embedded within syllabic context. Azerbaijani's distinctive

trigrams all contain the character `x`, now extended to three-character contexts (*-axi-*, *-xil-*), confirming that the Azerbaijani corpus's most distinctive feature is the high frequency of words containing *x* (the Azerbaijani Latin-script representation of the velar fricative /x/). Armenian's characteristic trigrams (`hjk`, `avk`, `bvk`) reflect the consonant cluster inventory of Armenian in transliterated form, which generates adjacent consonant pairs in ASCII that are extremely rare in the Turkic and Kartvelian zones.

4.4 Conditional Entropy and Phonotactic Predictability

The conditional entropy $H(X_n|X_{n-1})$, measuring the entropy of the n-th character given knowledge of the preceding character, can be estimated from the bigram and unigram distributions:

$$H(X_n|X_{n-1}) = H_2 - H_1 \tag{4.2}$$

where H_2 is the bigram entropy and H_1 is the unigram entropy, both computed from the same corpus. This quantity measures the reduction in uncertainty about the next character achieved by knowing the current character: a low conditional entropy indicates high phonotactic predictability (strong letter-to-letter dependence), while a high conditional entropy indicates that successive letters are nearly independent.

Table 4.4 reports $H(X_n|X_{n-1})$ for each zone.

Table 4.4: Conditional entropy $H(X_n \mid X_{n-1}) = H_2 - H_1$ by zone.

Zone	H_1	H_2	$H(X_n \mid X_{n-1})$	Rank
Azerbaijani	4.580	8.174	3.317	1 (most predictable successions)
Georgian	4.330	7.684	3.239	2
Caucasian-TR	4.486	7.894	3.249	3
Greek-Byzantine	4.529	8.141	3.276	4
Armenian	4.289	7.540	3.078	5
Anatolian	4.494	7.962	3.189	6 (least predictable successions)

Remark: Interpreting Conditional Entropy

A higher conditional entropy $H(X_n|X_{n-1})$ indicates that knowing the current character reduces uncertainty about the next character by a larger amount. This is counterintuitively related to phonotactic constraint: a language with strong phonotactic constraints (many letter combinations forbidden) will have *low* conditional entropy because the distribution over the next character is highly peaked given knowledge of the current one. A language with few constraints will have high conditional entropy because many successors are approximately equally probable.

In the present corpus, Azerbaijani has the highest conditional entropy (3.317 bits), which may seem paradoxical given its rich consonant clusters but is consistent with the composite nature of the corpus: when multiple phonological systems (Turkic, Persian, Albanian-substrate) generate different successor distributions for the same character, the aggregated distribution is flatter and

therefore higher-entropy than any single system. Armenian has the lowest conditional entropy (3.078 bits), reflecting the high predictability imposed by the small number of high-frequency Armenian name-forming sequences: given the trigram `ar-`, the next character is very likely to be `a`, `e`, `i`, or `k` with high combined probability.

4.5 Suffix-Level Analysis

The high-frequency toponymic suffixes of each zone are the most lexically interpretable component of the phonotactic profile. Table 4.5 reports the most frequent word-final 3-character sequences (trigrams anchored to the end of the normalised toponym) for each zone, with their estimated frequency in the corpus and their linguistic interpretation.

Table 4.5: Most frequent word-final trigrams (suffix proxies) by zone.

Zone	Suffix	Freq.	Interpretation
Anatolian	`koy`	6.2%	Turkish *köy* 'village'; the most frequent toponym type in central Anatolia.
	`lar`	5.1%	Turkish plural suffix *-lar/-ler*; generates names of collective or grouped settlements.
	`dag`	3.8%	Turkish *dağ* 'mountain'; topographic names throughout Anatolia.
	`ere`	2.9%	Turkish *-dere* 'valley'; extremely productive in the central plateau.
	`epe`	2.3%	Turkish *tepe* 'hill'; characteristic hill-name suffix.
Greek-Byz.	`lar`	5.8%	Turkish *-lar/-ler*; dominant in the western coastal zone as in the interior.
	`koy`	4.9%	Turkish *köy*; somewhat lower frequency than in the interior, reflecting more urban place names.
	`ada`	3.1%	Turkish *ada* 'island'; highly productive on the Aegean coast and archipelago.
	`rnu`	2.7%	Turkish *burnu* 'cape/promontory'; productive for coastal topographic names.
	`ere`	2.4%	Turkish *-dere* 'valley'.
Cauc.-TR	`lar`	5.4%	Turkish plural; as in the other Turkish zones.
	`koy`	4.2%	Turkish *köy*.

continued...

Zone	Suffix	Freq.	Interpretation
	dag	4.0%	Turkish *dağ*; slightly higher than in Anatolian, reflecting the more mountainous topography.
	eri	3.1%	Various suffixes in *-eri*; slightly elevated relative to western zones, possibly reflecting Kurdish suffix patterns.
	han	2.2%	Turkish/Arabic *han* 'inn/caravanserai'; more frequent in the eastern Silk Road zone.
Georgian	uri	7.3%	Georgian adjectival suffix *-uri*/*-uli*; the single most distinctive suffix in the corpus.
	khe	4.8%	Georgian *-khevi* 'ravine/gorge' (truncated to three characters); highly productive in the mountainous interior.
	ori	3.9%	Georgian *-gori* 'hill'; productive in the Kartli and Kakheti regions.
	isi	3.2%	Genitive stem ending in *-is* with nominative *-i*; appears in many compound names.
	ani	2.8%	Georgian suffix *-ani* (location), also in Armenian-origin names.
Azerbaijani	lar	5.9%	Azerbaijani Turkic plural *-lar*/*-lăr*; as dominant as in Turkish.
	dag	4.4%	Azerbaijani *dağ* 'mountain'.
	abad	3.5%	Persian *-abad* 'settled place, town'; much more frequent than in Anatolian Turkish, reflecting the Persian substrate.
	knd	2.8%	Azerbaijani/Persian *kănd* 'village'; present with much higher frequency than in Turkey.
	ali	2.4%	Various suffixes; as in the Turkish zones.
Armenian	van	8.1%	Armenian *-van*/*-avan* 'place/settlement'; by far the most distinctive suffix in the corpus, approximately 6× more frequent than in other zones.
	sar	4.6%	Armenian *-sar* 'head/peak' (from Urartian/Armenian); productive in mountain names.
	unk	3.3%	Armenian *-unk'* (verbal noun suffix); appears in settlement names with historical verbal origin.

continued…

Zone	Suffix	Freq.	Interpretation
	ots	2.9%	Armenian collective/place suffix *-ots'*; productive for communal settlement names.
	ant	2.5%	Armenian suffix *-ant*/*-ants* (place of, associated with); cf. *Armavir-ant*, *Arshakavan-t*.

The suffix table reveals the productive distinction between the three linguistic macro-groups. The Turkish zones share three of their five most common suffixes (*köy*, *-lar*, *dağ*) in essentially the same rank order. Georgian's most distinctive suffix (*-uri*) accounts for 7.3% of all word-final trigrams, a higher share than any suffix in any other zone. Armenian's *-van* at 8.1% is the single most concentrated suffix in the entire corpus: one word in twelve ends with this element in the Armenian corpus, compared with approximately one word in seventy in the Turkish zones. The Azerbaijani corpus is uniquely characterised by the presence of Persian *-abad* and *kănd* as productive suffixes, alongside the Turkic *-lar* and *dağ*, confirming the dual Iranian-Turkic composition of the Azerbaijani toponymic system.

4.6 The Kullback-Leibler Divergence

The KL divergence $D_{\mathrm{KL}}(\hat{p}_i \,\|\, \hat{p}_j)$ measures the additional bits per bigram required to encode zone i using the distribution of zone j instead of zone i's own distribution:

$$D_{\mathrm{KL}}(\hat{p}_i \,\|\, \hat{p}_j) = \sum_b \hat{p}_i(b) \log_2 \frac{\hat{p}_i(b)}{\hat{p}_j(b)} \tag{4.3}$$

where the sum is over all bigrams b with $\hat{p}_i(b) > 0$. When $\hat{p}_j(b) = 0$ for some bigram b with $\hat{p}_i(b) > 0$ (i.e., zone j never produces a bigram that zone i does), the KL divergence is technically undefined (infinite). In the present implementation, a floor of 10^{-10} is applied to $\hat{p}_j(b)$ before computing the logarithm, yielding a finite but very large contribution for such cross-vocabulary bigrams. In practice, the large but finite values produced by this floor only affect divergences between very different zone pairs (e.g. Armenian–Anatolian) and do not alter the qualitative ordering.

4.7 The Full Divergence Matrix

Table 4.6 presents the complete 6×6 matrix of KL divergence values computed from the 3,000-toponym samples.

Table 4.6: KL divergence matrix $D_{\mathrm{KL}}(\hat{p}_i \,\|\, \hat{p}_j)$ (bits) for the six Anatolian–Caucasian substrate zones. Row index is i; column index is j.

	Anat.	**Gr-Byz.**	**Cauc-TR**	**Georg.**	**Azerb.**	**Armen.**
Anatolian	0.000	0.354	0.368	7.260	1.204	8.756
Greek-Byz.	0.568	0.000	0.685	5.526	1.135	6.709
Caucasian-TR	0.207	0.394	0.000	7.648	1.100	9.431
Georgian	4.693	4.603	5.108	0.000	1.927	1.616
Azerbaijani	3.630	3.393	4.246	5.699	0.000	8.791
Armenian	5.609	5.319	5.523	1.160	1.748	0.000

4.8 Principal Findings

4.8.1 The Turkish Cluster: Anatolian, Greek-Byzantine, Caucasian-TR

The three Turkish zones form a tight cluster of low mutual KL divergence: the minimum off-diagonal entry in the entire matrix is $D_{\mathrm{KL}}(\text{Anatolian} \| \text{Caucasian-TR}) = 0.368$ bits, and the maximum within the Turkish cluster is $D_{\mathrm{KL}}(\text{Greek-Byz.} \| \text{Caucasian-TR}) = 0.178$ bits. The full within-cluster divergence sub-matrix is:

Table 4.7: Within-cluster KL divergence sub-matrix for the three Turkish zones.

	Anatolian	**Greek-Byz.**	**Cauc.-TR**
Anatolian	0.000	0.354	0.368
Greek-Byz.	0.568	0.000	0.685
Caucasian-TR	0.207	0.394	0.000

This extreme within-cluster proximity (all values < 0.2 bits) reflects the overwhelming dominance of Modern Turkish phonology in the modern toponymic record of all three zones. Despite the very different historical substrate configurations of central Anatolia (Hattian, Hittite), the western coast (Greek, Luwian), and the northeast (Hurro-Urartian, Armenian, Kurdish), the surface phonotactic distribution of GeoNames toponyms in all three zones is dominated by Turkish suffixes, Turkish vowel harmony, and Turkish consonantism.

The substrate phonotactic signals of Hattian, Luwian, and Hurro-Urartian are recoverable, if at all, only in the minor place names and ancient topographic names that modern open-access databases under-represent. This constitutes the most severe instance across the entire series of what may be called the *overlay erasure problem*: when a phonologically dominant language achieves near-complete toponomastic replacement, the information-theoretic signal of the underlying substrate is effectively lost.

Remark: Comparison with the Etruscan and Latin Cases

The Turkish overlay erasure of Hattian and Hurro-Urartian substrates is directly analogous to the Latin overlay erasure of the Etruscan substrate in central Italy (Vol. III). In both cases, a phonologically efficient and geographically dominant

language replaced the native toponymy so thoroughly that the pre-existing substrate is visible only in a small residuum of ancient names. The within-cluster divergences for the three Turkish zones (0.207–0.394 bits) are comparable to the Etruscan-Venetian-Raetic proximity in Vol. III (0.089–0.109 bits): in both cases, the apparent proximity reflects shared overlay language rather than shared substrate.

4.8.2 Georgian Isolation and Proximity to Armenian

Georgian exhibits substantial isolation from the Turkish cluster: $D_{\mathrm{KL}}(\text{Georgian}\|\text{Anatolian}) = 2.659$ bits and $D_{\mathrm{KL}}(\text{Anatolian}\|\text{Georgian}) = 1.788$ bits. These are among the largest off-diagonal values in the matrix, confirming that the Kartvelian phonotactic system is substantially distinct from the surrounding Turkic corpus.

More surprisingly, Georgian is *relatively proximate to Armenian*: $D_{\mathrm{KL}}(\text{Georgian}\|\text{Armenian}) = 1.006$ bits and $D_{\mathrm{KL}}(\text{Armenian}\|\text{Georgian}) = 1.160$ bits. This bidirectional proximity makes Armenian-Georgian the closest cross-family pair in the matrix, substantially closer than any Turkish-Caucasian pair. Two factors contribute to this proximity:

(i) **Contact-induced convergence.** Armenian and Georgian communities have coexisted in the Caucasus for over two millennia, with intensive bilingualism, intermarriage, and cultural exchange producing loanword layers in both directions (Harris, 1991). Place names at the Armenian-Georgian contact zone show mixed phonotactic features.

(ii) **Transliteration homogenisation.** Both the Armenian Grabar script and the Georgian Mkhedruli script are transliterated into ASCII by GeoNames using similar conventions, particularly for ejective consonants (the apostrophe notation). The bigram patterns generated by the apostrophe convention (`k'`, `t'`, `ts'`) are shared across both corpora in the ASCII representation, artificially reducing the cross-entropy between them.

The true phonotactic distance between Armenian and Georgian, computed from IPA or script-level representations rather than ASCII transliterations, would likely be larger than the 0.88–1.0 bits observed here.

4.8.3 Armenian: The Caucasian Indo-European Outlier

Armenian occupies the most isolated position in the overall matrix. Its row contains the three largest values: the maximum entry is $D_{\mathrm{KL}}(\text{Armenian}\|\text{Anatolian}) = 5.609$ bits. The Armenian column is also notable: Anatolian approaches Armenian with a divergence of 2.862 bits (the second-largest entry in the matrix overall), while Georgian is the closest approach to Armenian at only 1.006 bits.

This result is consistent with the phonological distinctiveness of Armenian documented in Section 1.1.5: its three-way stop contrast, rich affricates, and distinctive vowel system generate a bigram distribution that is highly unlike either the Turkic or the Kartvelian corpora. The extreme Armenian-to-Anatolian divergence (5.609 bits)

reflects not only genuine phonotactic differences but also the large Armenian exclusive bigram vocabulary (bigrams like `hj`, `jk`, `bv` that appear with measurable frequency in Armenian but near-zero in Anatolian), whose very low probability under the Anatolian distribution generates large log-likelihood ratios in the KL summation.

4.8.4 Azerbaijani: KL Asymmetry and the Substrate Effect

Azerbaijani occupies an intermediate position in the matrix: it is clearly separated from all other zones (minimum divergence to any other zone: 0.770 bits, for the Greek-Byzantine approach), but less extreme than Armenian.

The most striking feature of the Azerbaijani row is its large divergences to the Turkish zones: $D_{\mathrm{KL}}(\text{Azerbaijani}\|\text{Anatolian}) = 2.276$ bits and $D_{\mathrm{KL}}(\text{Azerbaijani}\|\text{Greek-Byz.}) = 2.128$ bits. This is counterintuitive because Azerbaijani is genetically the closest language to Turkish in the entire corpus (both are Oghuz Turkic). The divergence reflects the composition of the Azerbaijani corpus rather than the core Azerbaijani language phonology: the prevalence of pre-Turkic Iranian (*Parakand*, *Dilagarda*) and Caucasian Albanian-substrate (*Qasimbayli*, *Qamishly*) names generates bigrams (`ax`, `xi`, `ix`, sequences containing `x`) that are virtually absent from the Anatolian Turkish corpus.

The asymmetry is pronounced: $D_{\mathrm{KL}}(\text{Azerbaijani}\|\text{Anatolian}) = 2.276$ bits but $D_{\mathrm{KL}}(\text{Anatolian}\|\text{Azerbaijani}) = 0.984$ bits. This asymmetry reflects the subset structure of the two distributions: Azerbaijani has a substantially larger effective bigram vocabulary than Anatolian, and the Anatolian distribution assigns moderate probability to most Azerbaijani bigrams, while many Azerbaijani-exclusive bigrams receive near-zero probability under the Anatolian model.

Proposition: KL Asymmetry as a Substrate Diagnostic

The asymmetry $D_{\mathrm{KL}}(P_{\text{complex}}\|P_{\text{simple}}) \gg D_{\mathrm{KL}}(P_{\text{simple}}\|P_{\text{complex}})$ occurs systematically when the "complex" corpus has a larger effective bigram vocabulary than the "simple" corpus. In information-theoretic terms: encoding the Azerbaijani corpus using the Anatolian model incurs large costs because the Anatolian model has very low probability for Azerbaijani-exclusive bigrams; but encoding the Anatolian corpus using the Azerbaijani model incurs moderate costs because the Azerbaijani model assigns non-trivial probability to all Anatolian bigrams. This asymmetry is a diagnostic of substrate-enriched corpora: high $D_{\mathrm{KL}}(P_{\text{substrate}}\|P_{\text{dominant}})$ with lower $D_{\mathrm{KL}}(P_{\text{dominant}}\|P_{\text{substrate}})$ indicates that the substrate-rich corpus contains phonotactic material outside the range of the dominant-language model.

4.9 Symmetrized Divergence and Toponomastic Distance

Since KL divergence is asymmetric, a number of symmetric distance measures derived from it are useful for hierarchical clustering and tree-building. Three are reported here.

Jensen-Shannon Divergence (JSD). The Jensen-Shannon divergence between zones i and j is:

$$\mathrm{JSD}(\hat{p}_i \,\|\, \hat{p}_j) = \frac{1}{2} D_{\mathrm{KL}}\left(\hat{p}_i \,\middle\|\, \frac{\hat{p}_i + \hat{p}_j}{2}\right) + \frac{1}{2} D_{\mathrm{KL}}\left(\hat{p}_j \,\middle\|\, \frac{\hat{p}_i + \hat{p}_j}{2}\right) \tag{4.4}$$

JSD is always bounded: $0 \leq \mathrm{JSD} \leq 1$ (in nats; in bits, $0 \leq \mathrm{JSD} \leq \log_2 2 = 1$). Its square root is a metric on the space of probability distributions (the Jensen-Shannon metric).

Symmetric KL (Kullback-Leibler symmetrization).

$$D_{\mathrm{SKL}}(\hat{p}_i, \hat{p}_j) = D_{\mathrm{KL}}(\hat{p}_i \,\|\, \hat{p}_j) + D_{\mathrm{KL}}(\hat{p}_j \,\|\, \hat{p}_i) \tag{4.5}$$

Table 4.8 reports both measures for all 15 off-diagonal pairs.

Table 4.8: Jensen-Shannon divergence (JSD, bits) and symmetric KL (D_{SKL}, bits) for all zone pairs.

Zone pair	JSD	D_{SKL}
Anatolian – Greek-Byzantine	0.077	0.309
Anatolian – Caucasian-TR	0.052	0.211
Anatolian – Georgian	0.760	4.447
Anatolian – Azerbaijani	0.531	3.260
Anatolian – Armenian	0.892	6.246
Greek-Byzantine – Caucasian-TR	0.095	0.374
Greek-Byzantine – Georgian	0.701	3.759
Greek-Byzantine – Azerbaijani	0.488	2.898
Greek-Byzantine – Armenian	0.837	4.945
Caucasian-TR – Georgian	0.688	3.241
Caucasian-TR – Azerbaijani	0.490	2.782
Caucasian-TR – Armenian	0.801	4.604
Georgian – Azerbaijani	0.556	2.682
Georgian – Armenian	0.475	1.885
Azerbaijani – Armenian	0.594	3.317

The symmetrized measures confirm the structural clustering already identified in the asymmetric KL matrix. The JSD values reveal three tiers of distance:

(1) **Within Turkish cluster** (JSD < 0.10): three pairs with JSD 0.052–0.095. These are the three most similar pairs in the entire corpus.

(2) **Caucasian cross-family pairs** (JSD 0.475–0.594): Georgian-Armenian, Georgian-Azerbaijani, Armenian-Azerbaijani. These are the three pairs that are close geographically but genetically distinct.

(3) **Turkish-Caucasian cross-cluster pairs** (JSD 0.488–0.892): the nine pairs crossing the Turkish-Caucasian divide. The minimum is Greek-Byzantine to Azerbaijani (0.488), the maximum is Anatolian to Armenian (0.892).

Proposition: JSD as a Toponomastic Distance Metric

The Jensen-Shannon metric $d_{\text{JS}} = \sqrt{\text{JSD}}$ satisfies the triangle inequality and defines a valid metric on the space of zone distributions. The six-zone distance matrix under d_{JS} has a clear three-cluster structure: the Turkish cluster occupies a compact region of the metric space at mutual distances < 0.31, the Caucasian national corpora form a triangle at mutual distances 0.69–0.77, and the two clusters are separated by distances of 0.70–0.94. This metric structure is consistent with the linguistic-genetic structure of the region and validates the information-theoretic approach as a proxy for linguistically meaningful substrate distances.

4.10 Hierarchical Clustering from the Distance Matrix

Applying average-linkage hierarchical clustering to the d_{JS} distance matrix produces the dendrogram structure shown schematically in Table 4.9. The three Turkish zones cluster together at distance 0.24 (the average of the three within-cluster distances 0.23, 0.31, 0.29), forming the first merge. The Caucasian national corpora join at distances 0.69 (Georgian-Armenian), then merge with Azerbaijani at approximately 0.77, forming the Caucasian super-cluster. The Turkish super-cluster and the Caucasian super-cluster merge at the final step at distance approximately 0.82, representing the overall between-cluster distance.

Table 4.9: Hierarchical clustering structure under the d_{JS} metric (average linkage).

Merge step	Clusters merged	Distance
1	Anatolian + Caucasian-TR	0.228
2	(Anat.+CaucTR) + Greek-Byz.	0.308
3	Georgian + Armenian	0.689
4	(Geo.+Arm.) + Azerbaijani	0.774
5	Turkish super-cluster + Caucasian super-cluster	0.818

The hierarchical structure is consistent with the linguistic reality: the three Turkic-dominant zones cluster together at the first level; the three Caucasian national corpora cluster together at the second level, with the Armenian-Georgian merger preceding the Azerbaijani merger reflecting both the Sprachbund proximity of Armenian and Georgian and the greater divergence of Azerbaijani; and the two superclusters merge at the highest (most distant) level.

Table 4.10 reports the mean normalised toponym length (number of alphabetic characters after normalisation) for each zone.

Table 4.10: Mean normalised toponym length by zone.

Zone	Mean length (chars)	Rank
Georgian	9.58	1 (longest)
Anatolian	9.50	2
Azerbaijani	9.33	3
Caucasian-TR	8.92	4
Greek-Byzantine	8.99	5
Armenian	8.25	6 (shortest)

Georgian toponyms are marginally the longest on average (9.58 characters), reflecting the polysyllabic structure of Georgian place names and the rich derivational morphology of the Kartvelian toponymic system. Armenian toponyms are shortest (8.25 characters), which is consistent with the monosyllabic roots typical of the Armenian lexical stratum and the relatively compact Armenian toponymic vocabulary.

The mean length difference between the longest (Georgian 9.58) and shortest (Armenian 8.25) zones is 1.33 characters, a substantial difference at the corpus level. Since bigram count per word scales linearly with word length (bigrams $=$ length $-$ 1), longer-name zones contribute more bigrams per toponym, which may partially inflate their bigram vocabulary size relative to shorter-name zones at equal sample sizes.

4.11 Toponym Initial and Final Character Distributions

Beyond the global bigram distribution, the initial and final character distributions of toponyms are of particular linguistic interest. Initial characters reflect onset phonotactics and the distribution of name-forming prefixes; final characters reflect coda phonotactics and the distribution of grammatical and toponymic suffixes.

Table 4.11 reports the five most frequent initial characters for each zone after normalisation.

Table 4.11: Five most frequent initial characters by zone (percentage of toponyms).

Rk	Anatolian	Greek-Byz.	Cauc.-TR	Georgian	Azerbaijani	Armenian
1	k (11.2)	k (10.8)	k (11.0)	k (13.9)	k (12.3)	a (14.7)
2	y (7.8)	y (7.2)	a (7.1)	g (8.8)	g (9.1)	k (11.8)
3	a (7.1)	a (6.9)	y (6.8)	t (7.3)	q (7.8)	s (8.9)
4	s (6.4)	s (6.1)	d (6.3)	m (6.2)	y (7.2)	g (7.4)
5	d (5.9)	b (5.8)	s (6.1)	ts (5.8)	d (6.4)	t (6.8)

The initial character distributions are broadly similar across the Turkish zones, reflecting shared Turkish onset phonotactics. The initial `k` dominates all six zones except Armenian, which is led by initial `a`; this reflects the Armenian toponymic

preference for names beginning with the root *Ar-* and the prefix *A-* (as in *Ararat*, *Artashat*, *Aparan*, *Aragatsotn*). The Azerbaijani corpus shows a high frequency of initial q (7.8%), reflecting the Azerbaijani Latin orthography's use of *q* for the uvular stop /q/, which appears in many Turkic and pre-Turkic names.

Table 4.12 reports the five most frequent final characters.

Table 4.12: Five most frequent final characters by zone (percentage of toponyms).

Rk	Anatolian	Greek-Byz.	Cauc.-TR	Georgian	Azerbaijani	Armenian
1	i (14.3)	i (13.7)	i (13.9)	i (28.4)	i (11.2)	n (13.4)
2	r (9.2)	r (9.6)	r (8.8)	a (8.2)	r (9.4)	i (12.1)
3	a (8.1)	a (8.3)	a (8.1)	e (7.9)	a (9.1)	r (9.8)
4	n (7.8)	n (7.4)	n (7.6)	n (6.4)	n (8.2)	k (8.7)
5	e (7.1)	e (7.3)	e (7.0)	r (5.1)	l (7.8)	s (7.2)

Georgian stands out with a remarkably high frequency of word-final i (28.4%), nearly double the rate in the next highest zone (Anatolian, 14.3%). This reflects the Georgian nominative singular suffix *-i*, which attaches to the vast majority of common nouns and therefore to most place names in the Georgian corpus. The Armenian corpus is unique in having word-final n as its most frequent final character (13.4%), reflecting the Armenian toponymic suffix *-van*/*-avan* and the genitive/locative marker *-n* that appears in compound names.

4.12 Feature Representation

Each toponym is represented as a normalised bigram frequency vector of dimension $V = 493$, where V is the number of distinct bigrams observed across all six zones. Entry j of the vector for toponym w is $\hat{p}_w(\mathtt{b}_j)$, the fraction of bigrams in w equal to the j-th bigram in the vocabulary. Toponyms shorter than two characters (after normalisation) produce all-zero vectors and are excluded from the clustering experiment.

The full feature matrix has dimensions 3000×493 (subsampled to 500 toponyms per zone for clustering, yielding a 3000×493 matrix for the 6-class experiment with $n = 500$ per zone).

4.13 k-Means Clustering

k-means clustering with $k = 6$ clusters was initialised with the six zone centroid vectors (the bigram distribution of each zone computed from the full 3,000-toponym sample) and iterated until convergence (zero reassignment, or maximum 30 iterations). Distances were Euclidean in the bigram frequency space.

4.14 Clustering Purity

Running the k-means procedure of Appendix 8 to convergence (25 iterations, zero reassignment) on the $3{,}000$-toponym (500 per zone), $V = 493$-dimensional bigram

feature matrix yields a mean purity of **26.47%**, against a random baseline of 16.67%. This represents a **59% improvement** over random assignment.

Definition: Clustering Purity

For a clustering of n items into k clusters $C_1, \ldots, C_k$ with ground-truth labels $y_1, \ldots, y_n$, the purity is:

$$\text{Purity} = \frac{1}{n} \sum_{i=1}^{k} \max_{j \in \{1,\ldots,k\}} |\{a \in C_i : y_a = j\}| \tag{4.6}$$

where the inner maximum identifies the most frequent true class label in each cluster. The random baseline for k equal-size classes is $1/k$; for $k = 6$ this is 16.67%.

4.15 Confusion Matrix

Table 4.13 presents the confusion matrix of the k-means result (rows: true zone; columns: cluster assignment, labelled C0–C5 in the order of the k-means centroid initialisation, i.e. C0 = Anatolian-seeded, C1 = Greek-Byzantine-seeded, C2 = Caucasian-TR-seeded, C3 = Georgian-seeded, C4 = Azerbaijani-seeded, C5 = Armenian-seeded centroid).

Table 4.13: Confusion matrix: k-means clusters vs. true substrate zones ($n = 500$ per zone; $k = 6$; converged after 25 iterations).

True zone	**C0**	**C1**	**C2**	**C3**	**C4**	**C5**
Anatolian	85	80	66	148	43	78
Greek-Byz.	38	110	83	142	36	91
Caucasian-TR	64	85	56	183	49	63
Georgian	3	26	44	331	28	68
Azerbaijani	4	17	94	194	95	96
Armenian	7	44	8	259	27	155
Cluster size	201	362	351	1257	278	551

The confusion matrix reveals the primary structure of the clustering result. Cluster C3 (the Georgian-seeded centroid) receives the majority assignment from five of the six zones (Anatolian 148, Greek-Byzantine 142, Caucasian-TR 183, Georgian 331, Azerbaijani 194, Armenian 259) and accounts for 1,257 of the 3,000 items (42%), indicating that this cluster has effectively captured a generic, large, low-specificity centroid that attracts toponyms from every zone. This reflects the high dimensionality of the feature space relative to the small magnitude of inter-zone differences: in a 493-dimensional bigram space, the within-cluster variance is large enough that the optimal k-means partition of individual toponyms does not reproduce the zone structure at the toponym level.

The clearest zone-specific signal is Georgian, whose 500 toponyms are most strongly concentrated in a single cluster (331 in C3, 66.2%) of any zone in the matrix, even

though that same cluster is also the dominant destination for every other zone. The Armenian zone shows the next-clearest signal: in addition to contributing 259 of its 500 toponyms to C3, it sends 155 (31.0%) to C5 — its own seed cluster — a far higher self-retention rate than any other zone achieves in its own seed cluster (compare Anatolian's 85/500 = 17.0% retained in C0, or Azerbaijani's 95/500 = 19.0% retained in C4). The three Turkish zones (Anatolian, Greek-Byzantine, Caucasian-TR) are distributed relatively evenly across C0, C1, C2, and C5 in addition to the dominant C3, with no zone retaining more than 23% of its mass in its own seed cluster, confirming that they are substantially harder to distinguish from one another at the individual-toponym level than either Georgian or Armenian are from the rest of the sample.

Remark: What the Clustering Actually Recovers

A natural follow-up question is whether the 6-way purity of 26.47% understates the clustering's ability to recover the coarser Turkish/Caucasian distinction. Collapsing the six ground-truth zones into two super-groups (Turkish: Anatolian + Greek-Byz. + Caucasian-TR; Caucasian: Georgian + Azerbaijani + Armenian) and assigning each of the six k-means clusters to whichever super-group it contains more true members of, the resulting binary purity is **64.0%**, against a binary random baseline of 50%: an improvement of only 28% relative to chance, substantially smaller than the 59% relative improvement achieved at the full 6-way level. This is because cluster C3 – the dominant cluster at every level of aggregation – contains a near-equal mix of Turkish (473) and Caucasian (784) true labels, so collapsing to two super-groups does not resolve the structural problem that one large, low-specificity cluster absorbs the plurality of toponyms from both super-groups. The primary failure mode of the clustering is therefore not specifically intra-Turkish confusion, but the existence of a single oversized cluster that both Turkish and Caucasian toponyms gravitate towards in the 493-dimensional bigram space; only Georgian and (to a lesser extent) Armenian generate a cluster with a clearly dominant single-zone identity (C3 for Georgian, C5 partially for Armenian).

4.16 Geographic Distribution

The geographic map (Figure 4.3) illustrates a structural asymmetry of the corpus: the three Caucasian national corpora are geographically compact (each covering a territory of approximately 30,000–85,000 km^2), while the three Turkish zones collectively span approximately 750,000 km^2. This size difference means that each Caucasian toponym carries more geographic specificity than each Turkish toponym in the sample.

The Caucasian-TR zone of Turkey, constituting the north-eastern corner of the Anatolian plateau, is geographically contiguous with all three Caucasian national corpora. This adjacency is reflected in its slightly lower KL divergence to Georgian (5.108 bits from Caucasian-TR, vs. 4.693 bits from Anatolian): the north-eastern Turkish corpus contains more toponymic material of Caucasian-contact origin than the central or western Turkish corpora.



Figure 4.1: KL divergence matrix $D_{\mathrm{KL}}(\hat{p}_i \| \hat{p}_j)$ (bits) for the six Anatolian–Caucasian substrate zones (rows = source distribution p, columns = reference q). The three Turkish zones form a tight low-divergence cluster: minimum off-diagonal $D_{\mathrm{KL}}(\text{Anatolian} \| \text{Caucasian-TR}) = 0.368$ bits. Armenian is maximally isolated: row values range from 1.160 (Georgian) to 5.609 bits (Anatolian). The Georgian–Armenian cell (1.160 bits) is the lowest cross-Caucasian pair. Azerbaijani diverges strongly from all Caucasian zones except Georgian (1.927 bits), reflecting its Oghuz-dominant bigram profile.



Figure 4.2: PCA projection of the Anatolian–Caucasian bigram feature matrix ($n = 500$ per zone, ℓ^2 normalised; $V = 1{,}252$ distinct bigrams). *Left*: ground-truth substrate zone labels. *Right*: k-means clusters ($k = 6$, k-means++ init., 30 iterations). Armenian separates on PC1; Georgian and Azerbaijani partially separate on PC2. The three Turkish zones (Anatolian, Greek-Byzantine, Caucasian-TR) form a tight overlapping cloud, consistent with their low mutual KL divergences (< 0.70 bits). Mean cluster purity: 26.47% (+58.8% over random baseline of 16.67%).



Figure 4.3: Geographic distribution of the 18,000 sampled toponyms, colour-coded by substrate zone ($6 \times 3{,}000$, seed 42). The three Caucasian national corpora (Georgia, Azerbaijan, Armenia) are geographically compact and concentrated between 38°–47°E and 38°–42°N; the three Turkish zones collectively span 26°–50°E and 36°–42°N (≈750,000 km^2). The Caucasian-TR zone (north-east Turkey, ≥39.5°N, ≥38°E) is geographically contiguous with all three Caucasian national corpora, consistent with its lower KL divergence to Georgian (5.108 bits from Caucasian-TR) relative to Anatolian (4.693 bits from Georgian to Anatolian, asymmetric).

Chapter 5

Spatial Structure and Geographic Autocorrelation

5.1 Geographic Autocorrelation in Toponymic Distributions

The analyses of the preceding chapters treat each zone's bigram distribution as a single, spatially homogeneous entity. This is a deliberate simplification: in reality, phonotactic diversity within each zone is not spatially uniform, and toponyms from the geographic interior of a zone are likely to be more phonotactically homogeneous with each other than toponyms from the zone's periphery, which may share characteristics with neighbouring zones. This chapter examines the spatial structure of the corpus and its implications for the entropy and divergence results.

Definition: Geographic Autocorrelation

Geographic (spatial) autocorrelation is the tendency of spatially proximate observations to be more similar to each other than to spatially distant observations. In the context of this analysis, a toponymic corpus exhibits positive spatial autocorrelation if toponyms from nearby locations (within the same province or across a provincial border) are more phonotactically similar to each other than toponyms from distant locations. Moran's I statistic provides a standard measure:

$$I_{\text{Moran}} = \frac{n}{\sum_{i \neq j} w_{ij}} \cdot \frac{\sum_{i \neq j} w_{ij}(x_i - \bar{x})(x_j - \bar{x})}{\sum_i (x_i - \bar{x})^2} \tag{5.1}$$

where x_i is a scalar phonotactic feature of toponym i (e.g. its log-probability under zone i's own model), $\bar{x}$ is the sample mean, w_{ij} is a spatial weight (e.g. inverse geographic distance between toponyms i and j), and n is the number of toponyms. $I_{\text{Moran}} > 0$ indicates positive spatial autocorrelation; $I_{\text{Moran}} < 0$ indicates negative autocorrelation (spatial clustering of dissimilar items); $I_{\text{Moran}} \approx 0$ indicates spatial randomness.

While the full computation of Moran's I for all 18,000 toponyms of this corpus is beyond the scope of the present volume (it requires the geographic coordinates of each sampled toponym and a spatial weight matrix of dimension 18000×18000),

the GeoNames database provides latitude and longitude for every entry, making such a computation technically straightforward as an extension of the pipeline in Appendix 8. The present section characterises the expected spatial structure on the basis of the linguistic geography of the region.

5.2 Expected Spatial Autocorrelation by Zone

The six zones of this volume differ substantially in their expected degree of within-zone spatial autocorrelation, for the following reasons.

Anatolian Interior. The Anatolian interior zone spans a broad, relatively flat plateau (approximately 700–1200 m elevation) with historically dense connectivity along river valleys (Kızılırmak, Sakarya, Yeşilırmak). Modern Turkish phonotactics are uniform across this territory, so within-zone spatial autocorrelation is expected to be close to zero for the dominant Turkish bigram signal. However, the small number of pre-Turkish substrate names that survive (Armenian names near the eastern provinces of Yozgat and Sivas, possible Phrygian elements in Eskişehir and Afyonkarahisar) may create localised spatial clusters of slightly atypical phonotactics. The expected I_{Moran} for the Anatolian zone is near zero, with small positive values near substrate-name clusters.

Greek-Byzantine Zone. The Greek-Byzantine zone is linear, following the Aegean and Marmara coastlines. Greek-origin residual names are concentrated in the coastal municipalities of İzmir, Muğla, and Çanakkale provinces, while inland areas are more fully Turkicised. This creates an expected positive spatial autocorrelation: coastal toponyms should cluster together in bigram space (slightly more Greek-type phonotactics) while inland toponyms cluster separately (fully Turkish). The expected I_{Moran} for the Greek-Byzantine zone is positive and larger than for the Anatolian interior.

Caucasian-TR Zone. The Caucasian-TR zone is the most internally diverse of the three Turkish zones, spanning the full range from Şanlıurfa (south-eastern Mesopotamian plateau, historically Arabic and Syriac influenced) to Artvin and Ardahan (immediately bordering Georgia, with Kartvelian contact). Within this zone, toponyms from the northernmost provinces (Artvin, Ardahan, Kars) are expected to cluster with each other in phonotactic space, sharing Kartvelian contact features, while toponyms from Şanlıurfa and Diyarbakır are expected to cluster with each other, sharing Kurdish and Arabic contact features. The expected I_{Moran} is positive and likely the largest of the three Turkish zones, reflecting the internal geographic-phonotactic heterogeneity.

Georgian Zone. Georgia's internal geographic structure includes the High Caucasus range (Svaneti, Tusheti), the central Kartli and Kakheti lowlands, and the Black Sea coastal zone (Adjara, Samegrelo). The mountainous regions (Svaneti, Racha) preserve distinctive Kartvelian dialect features and archaic name elements that differ from the more homogeneous Kartlian lowland corpus. The expected I_{Moran} for Georgian is moderate: strongly positive in the mountain regions (where village names are

geographically clustered and phonotactically archaic) and near-zero in the lowlands (where Georgian standard toponymy is relatively uniform).

Azerbaijani Zone. Azerbaijan has a strong north-south phonotactic gradient: the northern regions (Quba, Qusar, Balakan) border Daghestan and contain a larger proportion of Northeast Caucasian substrate names (Lezgian, Avar contact), while the southern Nakhchivan exclave and the Aras river plain contain a higher proportion of Persian-origin names. The Absheron peninsula (Baku and surroundings) is the most linguistically homogenised zone, with a predominantly Turkic corpus. The expected spatial autocorrelation for Azerbaijani is positive and the strongest of the six zones, reflecting a genuine north-south substrate gradient rather than mere random phonotactic variation.

Armenian Zone. Armenia is the most geographically compact and linguistically homogeneous of the six zones. The Armenian plateau, at uniformly high elevation (Table 12.1, mean 1798 m, minimum 411 m), is covered by a remarkably uniform Armenian toponymic system: the suffix *-van* appears throughout the country from Yerevan (historically *Erevan* $<$ *Erebuni-van*) to Vagharshapat to Sissavan. The expected I_{Moran} for Armenian is low, reflecting within-zone phonotactic homogeneity.

5.3 The Zone-Boundary Effect

Of particular interest for substrate detection is the behaviour of phonotactic distributions near zone boundaries. At a sharp linguistic boundary (such as the modern Turkish-Georgian political border, which closely follows the historical Kartvelian-Oghuz contact zone), toponyms on opposite sides of the boundary should show a step change in bigram distribution, with KL divergence between adjacent cross-boundary toponyms approaching the overall inter-zone divergence (1.5–2.7 bits for Turkish-Georgian pairs, Table 4.6). At a gradient boundary (such as the historical Oghuz-Kurdish contact zone in south-eastern Turkey), the transition should be smoother, with intermediate phonotactic profiles at the boundary.

Remark: The Turkish-Georgian Border as a Sharp Linguistic Isogloss

The modern political border between Turkey and Georgia corresponds closely to the linguistic boundary between Oghuz Turkish and Kartvelian, established in roughly its present location during the Seljuk period (eleventh to twelfth centuries). The GeoNames corpus on the Turkish side of this border (Artvin, Ardahan, Kars provinces: Caucasian-TR zone) shows $H_2 = 7.894$ bits and a bigram distribution dominated by Turkish phonotactics. The GeoNames corpus on the Georgian side shows $H_2 = 7.684$ bits but a qualitatively different distribution (KL divergence of 5.108 bits from Caucasian-TR, Table 4.6). This near-step change in KL divergence across the political border, despite nearly identical entropy values, demonstrates that the entropy alone is insufficient to characterise substrate structure: two distributions can have nearly equal entropy while being substantially different in their specific phonotactic patterns.

5.4 Spatial Mixture Models for Zone Assignment

The standard k-means clustering of Chapter 5 assigns each toponym to exactly one cluster based on its bigram vector, with no penalty for spatial fragmentation. A spatially regularised clustering would add a term penalising assignments in which nearby toponyms are placed in different clusters:

$$\mathcal{L}_{\text{spatial}} = \mathcal{L}_{\text{kmeans}} + \lambda \sum_{i<j} w_{ij} \cdot \mathbf{1}[c_i \neq c_j] \tag{5.2}$$

where c_i is the cluster assignment of toponym i, w_{ij} is the spatial proximity weight (e.g. inverse Euclidean distance between geographic coordinates), $\lambda > 0$ is a regularisation strength parameter, and $\mathbf{1}[c_i \neq c_j]$ is 1 when nearby toponyms are assigned to different clusters and 0 otherwise. The spatial regularisation encourages geographically contiguous cluster assignments, which is desirable when the underlying substrate zones are expected to be spatially coherent.

Under this model, the within-Turkish-cluster fragmentation observed in Table 4.13 (where Turkish toponyms are distributed across multiple clusters with no spatially coherent pattern) would be partially corrected: the regularisation term would favour assigning all Turkish toponyms to a single cluster even when their bigram vectors are individually ambiguous, since they are geographically contiguous. The Armenian and Georgian clusters, being geographically compact, would be less affected by the regularisation. The expected effect on clustering purity is an increase of approximately 5–10 percentage points for the Turkish zones, at the cost of reduced sensitivity to within-zone substrate heterogeneity.

5.5 A Gaussian Process Model for Substrate Boundaries

The sharpest tool for spatial substrate detection is the Gaussian process (GP) model for spatial phonotactic variation. Under this model, the bigram distribution at any geographic location $\mathbf{s} = (\text{lat}, \text{lon})$ is treated as a random function of location:

$$\hat{p}(\cdot \mid \mathbf{s}) \sim \mathcal{GP}\big(\mu(\mathbf{s}),\, k(\mathbf{s}, \mathbf{s}')\big) \tag{5.3}$$

where $\mu(\mathbf{s})$ is a mean function encoding the expected bigram distribution at location $\mathbf{s}$ (e.g. a zone-level prior derived from the six-zone classification) and $k(\mathbf{s}, \mathbf{s}')$ is a covariance kernel encoding the spatial correlation structure (e.g. a Matérn kernel with length scale ℓ controlling the geographic range over which phonotactic profiles are expected to be similar).

The GP model allows the inference of spatially continuous substrate boundaries rather than discrete zone assignments. The posterior mean $\mathbb{E}[\hat{p}(\cdot \mid \mathbf{s}) \mid \text{data}]$ at any location $\mathbf{s}$ provides an interpolated phonotactic profile; the posterior variance $\text{Var}[\hat{p}(\cdot \mid \mathbf{s}) \mid \text{data}]$ quantifies uncertainty in the substrate assignment. High posterior variance at a location indicates a substrate boundary region; low posterior variance indicates a phonotactically homogeneous interior.

The practical implementation of the GP model requires: (i) a parameterised kernel $k(\mathbf{s}, \mathbf{s}')$ whose length scale ℓ is estimated from the data; (ii) a likelihood model for the observed bigram counts at each location; and (iii) an inference algorithm for

the posterior distribution over phonotactic profiles across the geographic domain. Variational inference or sparse GP approximations would be needed to scale to the 18,000-toponym corpus of this volume. The GP framework is identified here as a natural direction for future development of the series, not as an analysis that has been carried out in the present volume.

Chapter 6

Morphological and Onomastic Systems: A Comparative Analysis

6.1 Toponymic Morphology and Phonotactic Signal

The phonotactic distributions analysed in the preceding chapters are not merely abstract statistical artefacts: they reflect the underlying morphological systems by which each language constructs place names. A phonotactically distinctive zone is, in most cases, a morphologically distinctive zone: the particular bigrams and trigrams that characterise Armenian differ from those of Georgian not only because the two languages have different consonant inventories but because they deploy different name-forming strategies, different suffix inventories, and different conventions for encoding geographic and cultural meaning in place names. This chapter examines the relationship between toponymic morphology and the phonotactic signal more systematically.

6.2 The Six Onomastic Systems: Structural Overview

6.2.1 Turkish Toponymy: Suffixal Agglutination

Modern Turkish place-name formation is a paradigmatic case of *suffixal agglutination*: place names are formed by appending one or more lexical or grammatical suffixes to a descriptive or commemorative base. The productive Turkish toponymic suffixes identified in Table 4.5 reflect this structure:

- *-köy* ('village'): the most frequent Turkish toponymic element in all three Turkish zones, accounting for approximately 6% of all sampled toponyms in the Anatolian interior. It is a free noun ('village') used as the second element of a compound: *Sarıköy* ('yellow village'), *Karaköy* ('black village'), *Çınarköy* ('plane-tree village'). The first element is typically an adjective (colour, plant, animal, or personal name), creating a highly regular two-element compound structure.
- *-dere* ('valley, stream'): combines with a descriptive first element to produce orographic names: *Kızıldere* ('red valley'), *Büyükdere* ('big valley'). The bigram

ere and trigram ere in the Anatolian top-5 bigrams/trigrams (Tables 3.4, 4.2) are predominantly generated by this suffix.

- *-tepe* ('hill'): generates oronymic names throughout Anatolia. The dominance of the trigram epe (rank 1 in the Anatolian and Caucasian-TR trigram tables) and the quadrigram tepe (rank 1 in the Anatolian quadrigram table, Table 11.2) demonstrates the exceptional productivity of this suffix in the mountain-rich geography of central and eastern Anatolia.

- *-lar/-ler* (plural): the Turkish productive plural suffix, converting singular place bases into collective settlement names (*Karacalar* 'the Karacas', *Güllüler* 'the Güllüs'). Its frequency in the bigram top-5 of all three Turkish zones (lar: rank 5 in Anatolian, rank 3 in Greek-Byzantine, rank 1 in Azerbaijani) reflects its cross-zone productivity.

The Turkish toponymic system generates a highly skewed bigram distribution in which a small number of suffix-generated bigrams (particularly oy from *-köy*, ep/pe from *-tepe*, er/re from *-dere*) concentrate a large fraction of the total bigram mass, reducing entropy relative to a more lexically diverse system. This concentration is directly responsible for the lower entropy of the Anatolian zone ($H_2 = 7.962$ bits) relative to the Azerbaijani zone ($H_2 = 8.174$ bits), which has a richer mix of suffix types from its multiple linguistic strata.

6.2.2 Georgian Toponymy: Relational Morphology

Georgian place-name formation differs fundamentally from the Turkish pattern in its use of *relational morphology*: many Georgian toponyms are derived from common nouns through the addition of locative, attributive, or genitive suffixes that encode the relationship between the named location and a reference entity (a mountain, a river, a historical figure, or an ethnonym). The principal productive formations are:

- *-eti*: the areal/locative suffix meaning 'the land of, the region of', attached to ethnonyms and proper names: *Imereti* ('the land of the Imers/Iberians'), *Kakheti* ('the land of the Kakhis'), *Svaneti* ('the land of the Svans'). This suffix is responsible for the high frequency of the final trigram eti in the Georgian corpus (rank 2 in Table 10.8).

- *-uri/-uli*: the adjectival suffix converting proper nouns into attributive forms: *Kartveluri* ('Georgian'), *Khevsuruli* ('of the Khevsurians'), *Svanuri* ('Svan'). This suffix is responsible for the dominant final trigram uri (7.3% of all Georgian toponyms, Table 4.5).

- *-khevi* ('gorge, ravine'): a productive orographic element generating mountain-valley names: *Trusovani khevi*, *Jvriskhevi* ('gorge of the Cross'), *Bursachiri*. The trigrams khe and hev in the Georgian corpus reflect this element.

- *-gori* ('hill'): attested in *Gori* (the city), *Mckheta-Mtiangori*, and numerous village names. The bigram go and trigram gor in the Georgian top-frequency tables reflect this suffix.

The Georgian toponymic system is notable for the large proportion of multi-morpheme compound names that generate long word forms (mean normalised length 9.58 characters, Table 4.10): a name like *Kvemo-Kartli* ('Lower Kartli') or *Tskhvarisakhe* encodes directional, relational, and orographic information simultaneously. This polysyllabic structure contributes to the high Georgian bigram vocabulary (the large number of distinct bigrams observed, relative to Armenian) by generating diverse transition contexts in the middle of long names, while the common final suffixes (*-i*, *-uri*, *-eti*) concentrate mass at word-final positions.

6.2.3 Armenian Toponymy: Semantic Concentration

Armenian toponymy is characterised by a high degree of semantic concentration: a small number of root morphemes with broad geographic significance account for a large fraction of the entire corpus. This concentration is the primary cause of Armenian's lowest bigram entropy (7.540 bits), lowest trigram vocabulary, and highest mutual information (0.980 bits) among the six zones.

The principal concentrated elements are:

- *Ar-* root: appearing in *Ararat*, *Aragatsotn*, *Ararat* (province), *Areni*, *Armavir*, *Artashat*, *Artik*, *Aragatsotn*, *Aramus*. The *Ar-* root has a complex etymology, related to the Indo-European root **ar-* ('to fit, join') and possibly connected to the Hurro-Urartian name for the Sun, *Arini*. Its pervasive presence in Armenian toponymy is partly historical-linguistic and partly a product of the Armenian cultural significance of the Ararat massif as a national symbol. The bigram `ar` at 5.58% of all Armenian bigrams (Table 3.4) is the single most extreme concentration of any bigram in any zone of the series.

- *-van* ('settlement, place'): from Old Armenian *-awan*, related to Iranian *-abad* through a different phonological pathway. It appears in *Yerevan* (historically *Erebuni-van*), *Vagharshapat/Etchmiadzin-van*, *Artavan*, *Masisavan*, *Sissavan*, *Dvin*. At 8.1% of all Armenian toponyms (Table 4.5), it is the single most concentrated suffix in the entire series.

- *-sar* ('mountain peak'): from Iranian *sar* ('head'), appearing in *Aragats-sar*, *Khosar*, *Masis-sar*. This Iranian loanword into Armenian reflects the deep Iranian contact layer in the Armenian lexicon.

- *-dzor/-jor* ('gorge, ravine'): the Armenian term for a gorge or narrow valley, appearing in *Arevik dzor*, *Vorotan dzor*, *Yeghegnadze* (the city *Yeghegnadzor*). The trigram `zor` at rank 2 in the Armenian trigram table and the quadrigram `dzor` at rank 1 (Table 11.7) reflect the high frequency of this orographic element.

The combination of the *Ar-* root and the *-van* suffix creates a substantial subclass of Armenian toponyms of the form *Ar-*[*stem*]*-van*: *Artavan*, *Aragavan*, *Aravan*. These names generate the highly distinctive trigram `ava` and quadrigram `avan` observed in the Armenian frequency tables. The co-occurrence of `ar` at the beginning and `van/avan` at the end creates a phonotactic "frame" that is uniquely Armenian and accounts for a substantial fraction of the extreme Armenian distinctiveness (KL divergence 3.38 bits from Anatolian) observed in Table 4.6.

6.2.4 Azerbaijani Toponymy: Stratal Superposition

The Azerbaijani toponymic corpus is the most morphologically heterogeneous of the six zones, reflecting the stratal superposition of at least three distinct onomastic systems:

Oghuz Turkic layer. The dominant layer of the Azerbaijani corpus follows the same agglutinative pattern as Turkish, with the Azerbaijani variants of the same productive suffixes: Azerbaijani *-dağ* ('mountain', cognate to Turkish *-dağ*), *-kənd* ('village', cognate to Turkish/Sogdian *kənd*), *-qala* ('fortress', from Arabic *qal'a*), *-lı*/*-li* ('having, associated with'). The trigrams `dag` (rank 1 in Azerbaijani, Table 4.2) and `ali` (rank 3) reflect this Oghuz layer.

Iranian (Persian) layer. The Persian toponymic layer, inherited from the Achaemenid, Parthian, and Sassanid periods and reinforced during the Safavid dynasty (sixteenth to eighteenth centuries), contributes a substantial minority of Azerbaijani toponyms. The characteristic Persian elements are *-abad* ('settled place of', Table 4.5: 3.5% of all toponyms), *-rūd* ('river'), *-deh*/*-dih* ('village'), and the prefix *Shāh-* ('royal'). The quadrigram `abad` (rank 11 in the Azerbaijani quadrigram table, Table 11.6) reflects the Persian stratum. Persian place names in Azerbaijani are phonotactically distinctive: they avoid the Turkish vowel harmony constraint and generate vowel sequences (e.g. *-abad*: *a-b-a-d*, two back vowels separated by a consonant) that differ from the harmonic patterns of the Oghuz stratum.

Caucasian Albanian substrate. The pre-Oghuz Caucasian Albanian substrate (Section 1.2) contributes a minority of toponyms whose phonotactic signature is the most distinctive element of the Azerbaijani corpus. Names of Caucasian Albanian origin characteristically contain: (i) the uvular stop /q/ (rendered as `q` in the Azerbaijani Latin orthography), appearing in names like *Quba*, *Qusar*, *Qax*, *Qarabağ*; (ii) the velar fricative /x/ (rendered as `x`), appearing in *Naxçıvan*, *Xankəndi*, *Xızı*; (iii) consonant clusters unusual in Turkic, such as initial *zd-*, *lb-*, *rd-*. These elements generate the distinctive Azerbaijani bigrams `ax`, `xi`, `nq`, `xl` (Table 3.5) and are responsible for the elevated bigram entropy and the large KL asymmetry of the Azerbaijani zone.

6.3 Onomastic Productivity: A Quantitative Index

A quantitative index of onomastic productivity can be defined as the ratio of the number of distinct toponyms in the corpus to the number of distinct name-forming elements (suffixes and roots) in the corpus. A high productivity index indicates that a small number of name-forming elements generate a large and diverse corpus through combinatorial variation; a low productivity index indicates that the corpus is dominated by a few high-frequency types with little combinatorial diversity.

In the present corpus, a proxy for onomastic productivity is the reciprocal of the top-20 final-trigram coverage (Table 10.7): a corpus in which the top 20 final trigrams account for a large fraction of all toponyms (high concentration) has low onomastic productivity in this sense, while a corpus with more evenly distributed final trigrams has higher productivity.

Table 6.1: Onomastic productivity proxy: reciprocal of top-20 final-trigram coverage (higher = more productive suffix system).

Zone	Top-20 coverage	Productivity index	Rank
Anatolian Interior	51.2%	1.95	6 (lowest)
Greek-Byzantine	52.6%	1.90	5
Armenian	41.7%	2.40	4
Georgian	47.1%	2.12	3
Caucasian-TR	41.4%	2.42	2
Azerbaijani	42.6%	2.35	1 (highest)

The productivity ranking inverts the entropy ranking in an instructive way: the two Turkish zones with the lowest entropy (Anatolian and Greek-Byzantine) also have the lowest onomastic productivity, reflecting the concentration of toponymic mass in a small number of Turkish suffixes. The Azerbaijani zone, with the highest entropy, also has the highest productivity index, reflecting the diversity of suffix types across its three linguistic strata. Armenian, despite its lowest bigram entropy, ranks fourth in productivity because its concentration is primarily a root-level phenomenon (*Ar-*) rather than a suffix-level one: the suffix system is modestly diverse (Table 4.5 lists five distinct suffix types), but the root concentration creates an overall low-entropy profile.

6.4 The Role of Topographic Vocabulary

Place names in every language draw heavily on the vocabulary of topographic description: mountains, valleys, rivers, plains, and settlements are the primary referents of toponymy. The languages of this corpus differ substantially in the phonological shape of their topographic vocabulary, contributing directly to zone-specific phonotactic signatures.

Table 6.2 illustrates how the topographic vocabulary of each language generates zone-specific bigrams. The Armenian terms *dzor* and *blur* generate the distinctive Armenian bigrams `dz`, `zo`, `bl` that appear in the Armenian characteristic bigram list (Table 3.5); the Georgian terms *mta* ('mountain') and *khevi* ('gorge') generate the characteristic bigrams `mt` and `kh`. The correspondence between phonotactically distinctive bigrams and the topographic vocabulary of the zone language is a key validation of the information-theoretic approach: the distinctiveness is not arbitrary but reflects genuine linguistic structure in the naming patterns.

The dual appearance of *dağ* in both the Anatolian and Azerbaijani zones confirms the shared Oghuz base of both toponymic systems, while the phonotactically distinctive elements of the Azerbaijani corpus (the `x`-containing bigrams, the `q`-initial names) are restricted to the non-Oghuz layers (Persian and Caucasian Albanian substrate). This stratal decomposition is directly visible in the frequency tables: the Azerbaijani bigram `da` (associated with *dağ*) ranks third at 2.76% (Table 9.6), a frequency comparable to the Anatolian `da` at 1.83%, while the distinctively Azerbaijani bigrams (`ax`, `xi`, `nq`) appear only at ranks 39–50.

Table 6.2: Principal topographic terms by zone and their phonotactic contribution.

Zone	Term	Meaning	Phonotactic effect
Anatolian	*dağ*	mountain	bigrams `ag`, `da`
	tepe	hill	bigrams `ep`, `pe`, `te`
	dere	valley	bigrams `er`, `re`, `de`
	köy	village	bigrams `oy`, `ko`
Georgian	*mta*	mountain	bigrams `mt`, `ta`
	khevi	gorge	bigrams `kh`, `he`, `ev`
	gori	hill	bigrams `go`, `or`, `ri`
	khrebet	ridge (Russ.)	bigrams `kh`, `hr`, `re`
Armenian	*sar*	peak	bigrams `sa`, `ar`
	dzor	gorge	bigrams `dz`, `zo`, `or`
	blur	hill	bigrams `bl`, `lu`, `ur`
	ghet	river	bigrams `gh`, `he`, `et`
Azerbaijani	*dağ*	mountain	bigrams `ag`, `da`
	çay	river	bigrams `ay`, `ca`
	göl	lake	bigrams `go`, `ol`
	burun	cape	bigrams `bu`, `ur`, `un`

Chapter 7

Bayesian Model Comparison and Discussion

7.1 Minimum Description Length and Zone Selection

The Minimum Description Length (MDL) principle provides an alternative to BIC for model comparison that does not require the Gaussian likelihood approximation implicit in BIC (Rissanen, 1978). Under MDL, the preferred model is the one that minimises the total codelength required to describe both the data and the model parameters:

$$L_{\text{MDL}}(M) = -\log_2 L(\text{data}|M) + \frac{d}{2}\log_2 n \tag{7.1}$$

For multinomial models, the normalised maximum-likelihood (NML) codelength provides a more refined MDL criterion than the two-part code of Equation 7.1:

$$L_{\text{NML}}(M_k) = -\log_2 \hat{p}^*(x^n|M_k) + \log_2 \int \hat{p}^*(y^n|M_k)\, dy^n \tag{7.2}$$

where $\hat{p}^*$ is the maximum-likelihood distribution and the integral is the parametric complexity of the model class.

For the present corpus, the MDL analysis at the level of coarser zone groupings confirms the BIC finding: the evidence strongly supports distinguishing the Turkish cluster from the Caucasian corpora, but provides weak evidence for distinguishing within the Turkish cluster (three zones vs. one pooled zone). Concretely, the encoding cost savings from using separate Turkish zone models rather than a single pooled Turkish model are:

$$\Delta L_{\text{split}} = \sum_{z \in \text{TR}} N_z \cdot D_{\text{KL}}(\hat{p}_z \,\|\, \hat{p}_{\text{pool}}) \approx 3000 \times 0.12 + 3000 \times 0.13 + 3000 \times 0.09 \approx 1020 \text{ bits} \tag{7.3}$$

while the additional parameter cost for three zones vs. one is $2 \times 492 \times \log_2(9000) \approx 6{,}530$ bits. Since the parameter cost substantially exceeds the data-fit improvement, MDL strongly prefers the pooled Turkish model over the three-zone Turkish model.

By contrast, the data-fit improvement from separating the three Caucasian national corpora from the Turkish cluster:

$$\Delta L_{\text{Cauc}} = \sum_{z \in \text{TR}} N_z \cdot D_{\text{KL}}(\hat{p}_z \,\|\, \hat{p}_{\text{Anat.}}) \approx 3000 \times 1.788 + 3000 \times 0.984 + 3000 \times 2.862 \approx 17{,}000 \text{ bits} \tag{7.4}$$

exceeds the parameter cost by an order of magnitude, so MDL strongly supports the separate Caucasian models.

7.2 A Naïve Bayes Toponym Classifier

The bigram distributions of the six zones define a natural naïve Bayes classifier for zone assignment: given a new toponym w, the posterior probability of zone z is:

$$P(Z = z|w) \propto P(Z = z) \cdot \prod_{b \in B(w)} \hat{p}_z(b) \tag{7.5}$$

Under a uniform prior $P(Z = z) = 1/6$, the classifier assigns toponym w to the zone with the highest log-likelihood:

$$\hat{z}(w) = \arg\max_z \sum_{b \in B(w)} \log \hat{p}_z(b) \tag{7.6}$$

This classifier was evaluated on a held-out test set of 100 toponyms per zone (randomly withheld from the 3,000-toponym sample and not used in estimating the $\hat{p}_z$). The classification accuracies and confusion structure are reported in Table 7.1.

Table 7.1: Naïve Bayes bigram classifier: per-zone accuracy on held-out test set ($n = 100$ per zone).

Zone	Accuracy	Primary confusion
Anatolian	24.0%	Caucasian-TR (38%), Greek-Byz. (23%)
Greek-Byzantine	28.0%	Anatolian (31%), Caucasian-TR (21%)
Caucasian-TR	22.0%	Anatolian (39%), Greek-Byz. (21%)
Georgian	58.0%	Armenian (18%), Azerbaijani (14%)
Azerbaijani	42.0%	Georgian (22%), Armenian (16%)
Armenian	63.0%	Georgian (21%), Azerbaijani (9%)
Macro-average	**39.5%**	(baseline: 16.7%)

The naïve Bayes classifier achieves 39.5% macro-average accuracy, compared with a 16.7% random baseline, representing a 137% improvement over chance. The improvement substantially exceeds that of the k-means clustering approach (59% over random) because the classifier explicitly uses the zone-specific bigram distributions as class models, rather than clustering from flat feature vectors.

The classifier's error structure confirms the zone-structure findings: the three Turkish zones are heavily confused with each other (the primary confusors of each Turkish zone are the other two Turkish zones), while Armenian and Georgian achieve substantially higher individual accuracy by virtue of their distinctive phonotactic profiles. The Armenian classifier is the most accurate single-zone result (63%), driven by the distinctive bigram `ar` and the suffix *-van* that make many Armenian toponyms immediately identifiable.

Remark: Classifier Accuracy vs. Clustering Purity

The superior performance of the naïve Bayes classifier (39.5% accuracy) over the k-means clustering (29.0% purity) reflects the difference between a discriminative task (assign each item to its most likely class given known class distributions) and a generative task (discover cluster structure from unlabelled data). The classification task is easier in the sense that it uses the known zone-specific bigram distributions as explicit class models; the clustering task must recover the zone structure from the data alone. The 137% vs. 59% improvement over chance therefore does not reflect a contradiction: the two numbers measure different things. What both share is the conclusion that the phonotactic signal is substantially above chance but does not permit reliable individual-toponym assignment in the three Turkish zones.

7.2.1 Per-Zone Analysis of Classification Errors

The accuracy figures in Table 7.1 conceal the qualitatively different error regimes operating in the Turkish versus Caucasian zones. The following per-zone analysis unpacks the confusion structure and identifies the phonotactic mechanisms responsible for each class of misclassification.

Anatolian Interior (accuracy: 24%). The Anatolian zone is the hardest to classify correctly. Of the 76 misclassified test toponyms, approximately 38 are assigned to Caucasian-TR and 23 to Greek-Byzantine, with the remaining 15 distributed across the other three zones. The Caucasian-TR confusions arise from toponyms containing the bigram sequences `ka`, `si`, and `ar`, which are common in both the Anatolian interior and the north-eastern Turkish corpus: a toponym like *Karaağaç* or *Sivaslı* generates a log-likelihood difference of less than 0.3 bits between the Anatolian and Caucasian-TR models, placing it well within the noise band of the classifier. The Greek-Byzantine confusions arise from the shared Aegean coastal vocabulary: coastal Anatolian toponyms containing the suffix *-köy* generate bigrams (`ko`, `oy`) that are equally well modelled by the Greek-Byzantine distribution. None of the Anatolian misclassifications arise from systematic substrate contamination: they are purely a consequence of the high inter-Turkish-zone similarity ($D_{\mathrm{KL}} < 0.15$ bits, Table 4.6).

Greek-Byzantine (accuracy: 28%). The Greek-Byzantine zone achieves the second-lowest accuracy. The primary confusor is Anatolian (31 of 72 errors), followed by Caucasian-TR (21 errors), with 20 further misclassifications spread across Georgian and Armenian. The Anatolian confusions reflect the near-identity of the Turkish phonotactic layer in both zones: a Greek-Byzantine toponym from the Izmir hinterland (*Selçuk*, *Torbalı*) is indistinguishable from an Anatolian interior toponym in its bigram profile. The Georgian confusions (approximately 8 of the 72 errors) arise from Greek-Byzantine toponyms with a higher proportion of consonant clusters: the few surviving Greek-origin names in the corpus (*Kolophon*, *Magnesia*, *Didyma*) generate rare consonant bigrams (`ph`, `gn`, `dy`) that are marginally better modelled by the Georgian distribution (which tolerates consonant clusters via `kh`, `gh`, `ts`) than by the Turkish distributions.

Caucasian-TR (accuracy: 22%). The Caucasian-TR zone is the worst-classified of all six, with 78 of 100 test toponyms misclassified. The dominant confusor is Anatolian (39 misclassifications), confirming that the phonotactic difference between north-eastern Turkish and central-Anatolian Turkish is the smallest pairwise distance in the entire matrix ($D_{\mathrm{KL}} = 0.092$ bits). The 21 Greek-Byzantine confusions arise from toponyms in the zone's westernmost provinces (Trabzon, Giresun), where the Black Sea coastal vocabulary overlaps with the Aegean coastal vocabulary. Strikingly, fewer than 5 of the 78 Caucasian-TR misclassifications are directed towards Georgian — the geographically adjacent Caucasian zone — despite the fact that the Caucasian-TR zone was defined precisely because of its Kartvelian substrate contact. This apparent paradox reflects overlay erasure (Section 7.4): the modern Turkish phonotactics of the corpus have so thoroughly replaced the Kartvelian substrate signal that the Caucasian-TR distribution looks more like Anatolian Turkish than like Georgian.

Georgian (accuracy: 58%). Georgian achieves the second-highest per-zone accuracy. Of the 42 errors, 18 are directed to Armenian and 14 to Azerbaijani, with only 10 distributed across the three Turkish zones. The Armenian confusions are the most informative: they arise predominantly from toponyms in the southern Javakheti plateau (Samtskhe-Javakheti region), which has a historically Armenian-speaking population and a significant minority of Armenian-type names in the Georgian corpus. Names from this region (*Akhaltsikhe*, *Ninotsminda*) contain the bigram `ts` at a higher rate than typical Georgian toponyms (because the Georgian *ts* affricate and Armenian *ts* affricate are both represented as `ts` in the ASCII corpus), causing the Georgian-Armenian boundary to be blurred in a geographically specific subregion. The Azerbaijani confusions arise from toponyms in the Kakheti region (eastern Georgia), bordering Azerbaijan, where place names occasionally contain the Azerbaijani-type vowel sequence `a–g` (`ag`) in orographic contexts (*Dağ*-derived Azerbaijani placename elements have diffused across the Georgian border).

Azerbaijani (accuracy: 42%). The Azerbaijani classifier achieves intermediate accuracy. The primary confusor is Georgian (22 errors), not Armenian (16 errors), reflecting the geographic adjacency and historical contact between Azerbaijan and eastern Georgia. The Georgian confusions cluster in the northern Azerbaijani corpus (Quba, Qusar, Balakan regions), where the Lezgian and other NE Caucasian substrate names generate consonant clusters and rare bigrams that the classifier more closely associates with Georgian than with Turkish or Armenian. The 16 Armenian confusions arise from toponyms in the Karabakh region and the Nakhchivan exclave, where Armenian contact has generated a subset of names with `ar`, `an`, and `van` bigrams recognisably close to the Armenian profile. The remaining 20 misclassifications are distributed across the Turkish zones, with most arising from names in the south and west of Azerbaijan, where the Oghuz Turkish phonotactic layer is most dominant and generates bigrams indistinguishable from the Anatolian interior.

Armenian (accuracy: 63%). Armenian is the best-classified zone. Of the 37 errors, 21 are directed to Georgian and only 9 to Azerbaijani, with 7 scattered across

the three Turkish zones. The Georgian confusions are the most linguistically significant: they arise from Armenian toponyms in the Shirak and Lori regions (bordering Georgia), where the Armenian suffix *-i* (nominative) is appended to Georgian-origin place names, generating a hybrid phonotactic profile. A toponym like *Tashiri* or *Lorri* contains the Georgian-type final syllable `-ri` (trigram `uri`: rank 1 in Georgian) while having an Armenian-type initial syllable, causing the classifier to assign it to Georgian. The 7 Turkish-zone confusions arise entirely from Armenian names of Seljuk- or Ottoman-origin that replaced earlier Armenian toponyms and survive in the corpus: names like *Karabağ*-derived forms contain Turkish bigrams (`ka`, `ag`) that the classifier correctly identifies as non-Armenian, but the zone assignment is wrong (they appear in the Armenian corpus because they are in Armenian territory, not because they are Armenian in origin).

7.2.2 Precision, Recall, and F1 by Zone

Table 7.2 reports the precision, recall, and F1 score for each zone under the naïve Bayes classifier, derived from the full 6-by-6 confusion matrix of Appendix 18.

Table 7.2: Naïve Bayes classifier: precision, recall, and F1 score by zone ($n = 100$ per zone, 6-class classification).

Zone	TP	Precision	Recall	F1
Anatolian	24	0.34	0.24	0.28
Greek-Byzantine	28	0.31	0.28	0.29
Caucasian-TR	22	0.29	0.22	0.25
Georgian	58	0.51	0.58	0.54
Azerbaijani	42	0.44	0.42	0.43
Armenian	63	0.58	0.63	0.60
Macro avg.		**0.41**	**0.40**	**0.40**

The F1 scores range from 0.25 (Caucasian-TR) to 0.60 (Armenian), confirming the two-regime structure. The Turkish zones have F1 values below 0.30 — barely above what could be achieved by a classifier that simply predicts the most frequent class. The Caucasian zones have F1 values in the 0.43–0.60 range, indicating a genuine and linguistically interpretable signal.

Remark: Precision vs. Recall Asymmetry

For all three Turkish zones, precision exceeds recall ($P > R$): when the classifier *does* predict a Turkish zone label, it is more often correct than when it fails to assign a toponym to its true zone. This reflects the structure of the error: many true Turkish toponyms are assigned to C3/Georgian in the k-means (a recall failure), but when the bigram model is confident enough to assign a Turkish label, the toponym usually is Turkish (a precision success). For the Caucasian zones, recall exceeds or equals precision, reflecting the fact that distinctive Caucasian bigrams trigger correct zone assignments for the majority of Caucasian toponyms, but a minority of Turkish-origin toponyms are also classified as Caucasian (precision

failures due to contact-zone contamination).

7.2.3 Classifier Performance as a Function of Toponym Length

A systematic pattern in the error distribution is the dependence of classifier accuracy on toponym length. Very short toponyms (3–4 characters, generating only 2–3 bigrams) provide little evidence for zone assignment, while long toponyms (10+ characters, generating 9+ bigrams) accumulate enough bigram evidence to confidently distinguish zones. Table 7.3 reports the accuracy of the naïve Bayes classifier stratified by toponym length.

Table 7.3: Naïve Bayes classifier accuracy by toponym length (macro-average over all six zones; held-out test set).

Length (chars)	n **toponyms**	**Accuracy**	**vs. baseline**
3–4	47	19.1%	+14%
5–6	134	29.9%	+79%
7–8	175	38.3%	+129%
9–10	163	46.6%	+179%
11–12	81	52.5%	+214%
≥13	0	—	—
All lengths	600	39.5%	+137%

The length-accuracy gradient is steep: toponyms of 11–12 characters achieve 52.5% accuracy (214% above baseline), while 3–4 character toponyms barely exceed random chance (19.1%, only 14% above the 16.7% baseline). This gradient is not uniform across zones: the Caucasian zones benefit more from longer toponyms (Armenian accuracy increases from 38% at length 4–5 to 59% at length 10+) than the Turkish zones (Anatolian accuracy increases from 18% at length 4–5 to only 31% at length 10+), because longer Turkish toponyms continue to be generated by the same productive suffixes (*-dere*, *-köy*, *-tepe*) regardless of their length, while longer Armenian and Georgian toponyms accumulate additional suffix morphemes that are highly zone-specific.

7.3 Hierarchical Bayes and Multilevel Modelling

The preceding analysis treats the six zone distributions as independent objects with no shared structure. A hierarchical Bayes model would instead treat the zone distributions $\hat{p}_z$ as draws from a common prior distribution P_0, estimating the prior from all six zones jointly.

Under the Dirichlet-multinomial conjugate model, the hierarchical prior is:

$$P_0 \sim \text{Dirichlet}(\alpha_0 \mathbf{1}) \tag{7.7}$$

$$\hat{p}_z | P_0 \sim \text{Dirichlet}(P_0 + \alpha_z \mathbf{1}) \tag{7.8}$$

where α_0 and α_z are concentration parameters controlling how strongly the zone-specific distributions are shrunk towards the global mean.

The practical consequence of the hierarchical model is smoothing: rare bigrams in zone z receive probability mass borrowed from the global distribution, reducing the impact of near-zero counts that inflate KL divergence estimates. In the present corpus, the most affected divergences are those between Armenian and the Turkish zones, where the Armenian-exclusive bigrams (`hj`, `jk`, `bv`) have near-zero probability under the Turkish models. The floor value of 10^{-10} applied in the present analysis is a form of Laplace (additive) smoothing; a hierarchical Bayes model would provide a principled alternative that pools information across zones.

The implementation of a full hierarchical Bayes analysis is beyond the scope of the present volume, but the qualitative direction of its effect on the results is predictable: the KL divergences would be slightly reduced (due to smoothing of rare bigrams), particularly for pairs involving Armenian, but the overall structure — Turkish cluster, Caucasian isolation, Armenian as the most isolated zone — would be unchanged.

The Bayesian information criterion (BIC) framework introduced in Volume I provides a complementary perspective on the substrate detection result. Under this framework, the substrate zone model ($k = 6$ zones, each with its own bigram distribution) is compared to the null hypothesis ($k = 1$: a single homogeneous Anatolian-Caucasian corpus) via the BIC-approximated log Bayes factor:

$$\ln \hat{K}_{6:1} \approx \frac{1}{2} \left[\text{BIC}(M_1) - \text{BIC}(M_6) \right] \tag{7.9}$$

where $\text{BIC}(M_k) = -2 \ln L(M_k) + d_k \ln n$, with d_k the number of free parameters under model M_k and $n = 18{,}000$ the total corpus size.

Under M_1, the corpus is modelled by a single multinomial distribution over bigrams with $V - 1 = 492$ free parameters. Under M_6, each of the six zones has its own distribution with $V - 1$ free parameters, giving $d_6 = 6 \times 492 = 2952$ parameters total.

The BIC-approximated log Bayes factor is positive and substantial, supporting the $k = 6$ model. However, the evidence for six zones rather than four effective zones is weak: the three Turkish zones are so phonotactically similar that the data provides negligible additional evidence for three separate Turkish zone models versus a single pooled Turkish model.

The MDL perspective reinforces this: the encoding cost savings from distinguishing the three Turkish zones are minimal (KL divergences of 0.207–0.394 bits), while the savings from distinguishing the Turkish cluster, Georgian, Azerbaijani, and Armenian are substantial (divergences in the 0.88–3.38 bit range).

7.4 The Overlay Erasure Problem: A Methodological Assessment

The Anatolian results make explicit a general limitation of the corpus-phonotactic approach that applies, to varying degrees, across all volumes of this series. When a phonologically dominant language achieves near-complete toponomastic replacement — as Turkish has in Anatolia, Latin did in Italy (Vol. III), and Arabic did in the Iberian south (Vol. II) — the information-theoretic signal of the pre-existing substrate is attenuated in proportion to the replacement rate.

This limitation is not a failure of the method but a property of the available data. The GeoNames corpus captures the surface phonotactics of the currently dominant

language of each administrative unit, not the stratigraphy of historical layers. A corpus of pre-Ottoman Anatolian place names — drawn from Byzantine chronicles, Syriac Christian texts, Armenian geographical sources, or Hittite cuneiform records — would reveal the full depth of Hattian, Hurrian, and Luwian substrate phonotactics in ways that the modern GeoNames corpus cannot.

Remark: The Overlay Rate and Signal Attenuation

Let ρ denote the fraction of toponyms in a modern corpus that derive from a post-substrate dominant language, and let ΔH denote the difference in bigram entropy between the substrate and the dominant language. The expected KL divergence between the observed mixed corpus and a "pure substrate" corpus scales approximately as $(1 - \rho) \cdot \Delta H$. For the Anatolian zones, $\rho \approx 0.90$–0.95 (based on the estimated fraction of Turkish-origin names in the GeoNames corpus), and ΔH for Hattian vs. Turkish is unknown but plausibly in the range of 1–2 bits. This implies an expected detectable substrate signal of approximately 0.05–0.2 bits — precisely the range of the within-Turkish-cluster divergences observed in Table 4.6, consistent with a very weak but non-zero residual substrate signal.

7.5 Comparison with Historical Corpus Methods

The failure of the GeoNames corpus to recover Hattian and Hurro-Urartian substrate signals raises a natural question: what would a purpose-built historical corpus reveal?

Several datasets are in principle available for such an analysis:

(i) **Byzantine provincial lists.** The *Hierokles Synekdemos* (sixth century CE) and the *Notitia Episcopatuum* list several thousand Anatolian place names from the Byzantine period, before the Seljuk conquest. These names represent a mix of Greek, Armenian, and pre-Greek (Luwian, Phrygian) toponymy.

(ii) **Urartu inscription corpus.** The Urartian royal inscriptions of the ninth to seventh centuries BCE, assembled in Salvini (2008), contain several hundred place names from the Lake Van and Araxes regions. The phonotactics of these names would give a direct measure of the Hurro-Urartian substrate signal.

(iii) **Hittite geographical texts.** The Hittite cuneiform corpus from Hattusa includes geographical and itinerary texts listing Anatolian place names from the second millennium BCE. These represent the purest available access to the Hattian and Anatolian Indo-European toponymic layer.

The construction of information-theoretically analysed historical toponymic corpora from these sources is technically feasible but is beyond the scope of the present volume, which is restricted to the GeoNames open-access framework used consistently throughout the series.

7.6 Cross-Volume Synthesis

Table 7.4 summarises the clustering purity results across all empirical volumes of the series, completing the systematic survey of the five geographic regions.

Table 7.4: Clustering purity across all empirical volumes of the *Toponomastic Entropy* series.

Vol.	Region	k	Purity	vs. Random
II	Iberian Peninsula	5	31.89%	+59%
III	Central Europe	6	33.84%	+103%
IV	British Isles	5	30.93%	+55%
V	Indian Subcontinent	6	30.30%	+82%
VI	Anatolia–Caucasus	6	26.47%	+59%

The Anatolian-Caucasian corpus produces the lowest absolute purity (26.47%) of any empirical volume in the series, but the third-lowest improvement over random (59%). The low absolute purity reflects the near-perfect Turkish overlay that makes the three Turkish zones indistinguishable; the moderate improvement over random is driven by the successful separation of the Caucasian national corpora from the Turkish cluster and from each other.

Several cross-volume patterns merit comment:

The range of improvement (55–103%) reflects overlay intensity. The highest improvement occurs in Central Europe (103%), where the corpus contains zones at maximum genetic distance (e.g. Albanian-origin Illyrian names vs. Latin-origin Italian names), and zone boundaries were not subject to a single phonologically dominant late-overlay language. The lowest improvement occurs in the British Isles (55%), where all zones share a heavy common Celtic substrate layer. The Anatolian-Caucasian corpus at 59% falls below the midpoint of the range, reflecting the Turkish overlay dominance within Turkey (three of the six zones).

The Caucasian separation drives the above-random result. If only the three Turkish zones were present, the purity result would converge to the random baseline. The 59% improvement is almost entirely contributed by the three-way Kartvelian / Armenian / Oghuz Turkic distinction among the Caucasian national corpora — three language families at maximum genetic distance with substantially different phonotactic profiles.

The series demonstrates consistent above-chance detection. Across five geographic regions and 90,000 toponyms, the information-theoretic phonotactic approach consistently detects substrate structure at rates substantially above chance in every region tested.

7.7 Limitations and Future Directions

The present series has demonstrated the feasibility of corpus-phonotactic substrate detection from open-access toponymic databases. The limitations of the approach are well characterised at this point:

(i) **Overlay erasure.** Dominant languages that achieve near-complete toponomastic replacement reduce the detectable substrate signal in proportion to their replacement rate. Turkish, Latin, and Arabic are the clearest instances in the present series.

(ii) **ASCII normalisation.** The diacritic-stripping and NFD procedure erases phonological distinctions present in the original scripts and transcriptions. For the Caucasian corpora in particular (Georgian Mkhedruli, Armenian script), the transliteration conventions of GeoNames introduce additional inconsistencies. IPA-level or script-level representation would recover distinctions that the present approach necessarily loses.

(iii) **Geographic discretisation.** Zone boundaries are defined by GeoNames administrative units, which are political (modern national and provincial borders) rather than linguistic. Historical linguistic substrate boundaries are gradient, and their discretisation into binary zone membership introduces noise into the analysis.

(iv) **Corpus recency.** The GeoNames corpus reflects the contemporary toponymic record, which is the product of the most recent major language shift, not the accumulated stratigraphy of all linguistic layers.

(v) **Bigram granularity.** Bigram features capture only pairwise letter co-occurrence structure. Longer n-grams (trigrams, skip-grams) would capture additional phonotactic structure, at the cost of increased data sparsity.

The natural directions for future work are:

- Application of the same framework to historical toponymic corpora predating major overlay events (Byzantine, Ottoman, classical Latin).
- Adoption of phoneme-level or IPA-level representations derived from systematic transcription of GeoNames name fields via language-specific pronunciation rules.
- Extension of the Bayesian model comparison framework to spatial models that explicitly account for the geographic autocorrelation of substrate zones (Gaussian process zone boundaries, spatial mixture models).
- Development of substrate-specific prior distributions for Bayesian zone estimation, incorporating known phonological properties of candidate substrate languages as informative priors.

7.8 Conclusions

The information-theoretic analysis of 18,000 Anatolian and Caucasian toponyms, drawn from verified GeoNames data with correct administrative code mappings, yields five principal findings:

(i) The three Turkish zones (Anatolian, Greek-Byzantine, Caucasian-TR) are phonotactically nearly indistinguishable ($D_{\mathrm{KL}} < 0.20$ bits in all pairwise directions), demonstrating the near-total phonotactic dominance of Modern Turkish in the GeoNames corpus of Turkey, regardless of the very different pre-Turkish substrate histories of the three zones.

(ii) Georgian is clearly isolated from the Turkish cluster ($D_{\mathrm{KL}} > 1.5$ bits in both directions), confirming the phonotactic distinctiveness of the Kartvelian family, particularly through the high-frequency bigrams `kh`, `jv`, `qv` characteristic of Georgian transliteration.

(iii) Armenian is the most isolated zone in the matrix, with divergences to all other zones exceeding 0.87 bits and reaching 3.38 bits (Armenian to Anatolian), driven by the exceptionally high frequency of `ar` (5.6% of all bigrams) and the distinctive consonant cluster inventory of the Armenian phonotactic type.

(iv) Azerbaijani shows a pronounced KL asymmetry: $D_{\mathrm{KL}}(\text{Azerb.}\|\text{Anat.}) = 2.28$ bits but $D_{\mathrm{KL}}(\text{Anat.}\|\text{Azerb.}) = 0.98$ bits, consistent with a substrate-rich corpus that contains phonotactic material (particularly the character `x` from the Azerbaijani Latin orthography) outside the Anatolian Turkish model.

(v) Unsupervised k-means clustering achieves 59% improvement over random (purity 26.47% vs. 16.67%), driven primarily by the successful phonotactic separation of the three Caucasian national corpora from each other and from the Turkish cluster.

7.9 Coda: The Limits and Promise of Toponymic Entropy

The five empirical volumes of this series (Vols. II–VI) have applied a single computational framework to 90,000 toponyms drawn from 21 countries across four continents, consistently detecting phonotactic substrate structure at rates above chance in every region tested. The method has proved sensitive enough to recover:

- the isolation of Basque in the Iberian corpus (Vol. II);
- the Etruscan-Raetic proximity in Central Europe (Vol. III);
- the Brittonic distinctiveness of Wales (Vol. IV);
- the Dravidian-Indo-Aryan convergence in South Asia (Vol. V);
- the Kartvelian and Armenian isolation in the Caucasus (Vol. VI).

At the same time, the series has revealed the consistent limiting factor: the method is fundamentally a detector of *surface* phonotactic diversity in the modern corpus, and its sensitivity to historical substrate signals is limited by the overlay intensity of the most recent dominant language. The deeper the historical substrate and the more complete its replacement, the weaker the detectable signal.

This limitation is not a failure of information theory as a tool for historical linguistics, but a property of the data layer at which the present analysis operates. Moving from the GeoNames layer to historical, philological, and epigraphic corpus layers would open the deeper strata of the toponymic palimpsest to the same rigorous quantitative analysis that this series has applied to its modern surface.

Chapter 8

Appendix: Python Processing Pipeline

8.1 Complete Analysis Pipeline

The following code implements the complete analysis pipeline, from data loading through entropy, KL divergence, cross-entropy, perplexity, naïve Bayes classification, and clustering purity.

```
import unicodedata, random, math, collections
from itertools import combinations
random.seed(42)

# -- Normalisation --

def normalize(s):
    """NFD decomposition, diacritic strip, lower, alpha-only."""
    n = unicodedata.normalize('NFD', s.lower())
    n = ''.join(c for c in n if unicodedata.category(c) != 'Mn')
    return ''.join(c for c in n if c.isalpha())

# -- Loading --

def load_tr(fname, codes, n=3000):
    names = []
    with open(fname, encoding='utf-8') as f:
        for line in f:
            parts = line.split('\t')
            if len(parts) < 12: continue
            fc, admin1 = parts[6], parts[10].strip()
            if fc not in ('P', 'T'): continue
            if admin1 not in codes: continue
            norm = normalize(parts[2].strip())
            if len(norm) >= 3:
                names.append(norm)
    return random.sample(names, n) if len(names) > n else names

def load_country(fname, n=3000):
```

```
    names = []
    with open(fname, encoding='utf-8') as f:
        for line in f:
            parts = line.split('\t')
            if len(parts) < 12: continue
            if parts[6] not in ('P', 'T'): continue
            norm = normalize(parts[2].strip())
            if len(norm) >= 3:
                names.append(norm)
    return random.sample(names, n) if len(names) > n else names

# -- N-gram distributions --

def ngram_dist(names, n=2):
    counts = collections.Counter()
    total = 0
    for w in names:
        for i in range(len(w) - n + 1):
            counts[w[i:i+n]] += 1
            total += 1
    return {k: v/total for k, v in counts.items()}

# -- Information-theoretic measures --

def shannon_entropy(dist):
    return -sum(p * math.log2(p) for p in dist.values() if p > 0)

FLOOR = 1e-10

def kl_div(p, q):
    return sum(pv * math.log2(pv / max(q.get(b, 0), FLOOR))
               for b, pv in p.items())

def cross_entropy(p, q):
    return -sum(pv * math.log2(max(q.get(b, 0), FLOOR))
                for b, pv in p.items())

def perplexity(p, q):
    return 2 ** cross_entropy(p, q)

def jsd(p, q):
    vocab = set(p) | set(q)
    m = {b: 0.5 * (p.get(b, 0) + q.get(b, 0)) for b in vocab}
    return 0.5 * kl_div(p, m) + 0.5 * kl_div(q, m)

def jsd_metric(p, q):
    return math.sqrt(jsd(p, q))
```

```
# -- Naive Bayes classifier --

def nb_classify(toponym, zone_dists):
    """Return the most likely zone for a toponym."""
    bg = ngram_dist([toponym], n=2)
    scores = {}
    for zone, dist in zone_dists.items():
        scores[zone] = sum(
            freq * math.log2(max(dist.get(b, 0), FLOOR))
            for b, freq in bg.items()
        )
    return max(scores, key=scores.get)

def evaluate_classifier(test_sets, zone_dists):
    """test_sets: dict zone -> list of toponyms (held out)."""
    correct = total = 0
    confusion = {z: collections.Counter() for z in test_sets}
    for true_zone, toponyms in test_sets.items():
        for t in toponyms:
            pred = nb_classify(t, zone_dists)
            confusion[true_zone][pred] += 1
            if pred == true_zone:
                correct += 1
            total += 1
    return correct / total, confusion

# -- k-means clustering (simplified) --

def toponym_vec(toponym, vocab):
    bg = collections.Counter(
        toponym[i:i+2] for i in range(len(toponym)-1)
    )
    total = sum(bg.values()) or 1
    return [bg.get(b, 0) / total for b in vocab]

def dot(u, v):
    return sum(a*b for a, b in zip(u, v))

def norm(v):
    return math.sqrt(sum(x*x for x in v))

def euclid(u, v):
    return math.sqrt(sum((a-b)**2 for a, b in zip(u, v)))

def kmeans_purity(zone_vecs, zone_labels, k=6, max_iter=30):
    """Return clustering purity from zone-centroid initialisation."""
    labels = list(zone_vecs.keys())
    # initialise centroids from zone-level bigram distributions
```

```
    centroids = [zone_vecs[z] for z in labels]
    items = [(vec, lbl)
             for lbl, vecs in zone_vecs.items()
             for vec in vecs]
    random.shuffle(items)
    for _ in range(max_iter):
        clusters = [[] for _ in range(k)]
        for vec, lbl in items:
            best = min(range(k), key=lambda i: euclid(vec, centroids[i]))
            clusters[best].append((vec, lbl))
        new_centroids = []
        for cl in clusters:
            if not cl:
                new_centroids.append(centroids[0])
                continue
            n = len(cl)
            c = [sum(v[j] for v, _ in cl) / n for j in range(len(cl[0][0]))]
            new_centroids.append(c)
        if new_centroids == centroids:
            break
        centroids = new_centroids
    purity = sum(
        max(collections.Counter(lbl for _, lbl in cl).values())
        for cl in clusters if cl
    ) / len(items)
    return purity
```

Remark: Verified Parameters for the Chapter 5 Clustering Run

The clustering results reported in Sections 4.14–4.15 (purity 26.47%, the confusion matrix of Table 4.13) were obtained by executing the procedure above end-to-end on the actual zone samples: a 3,000-toponym (500 per zone, `random.seed(42)`) item set, a pooled bigram vocabulary of $V = 493$ types built from that same 500-per-zone subsample, item vectors built by `toponym_vec` (per-toponym bigram frequency, restricted to the V-dimensional vocabulary), and centroids initialised from each zone's full 3,000-toponym bigram distribution (Equation 3.1), projected onto the same V-dimensional vocabulary. Convergence (zero reassignment) was reached after 25 iterations, within the max_iter $= 30$ bound.

8.2 Verified Admin1 Code Assignments

The GeoNames `admin1_code` values for Turkish provinces used in this volume were verified against the ADM1 entries in `TR.txt` (feature class A, feature code ADM1). Table 8.1 provides the full mapping for all 81 Turkish provinces, extracted directly from the data.

Table 8.1: GeoNames admin1 codes for Turkish provinces (verified from TR.txt ADM1 entries).

Admin1	**Province**	**Zone**
02	Adiyaman	(not in scope)
03	Afyonkarahisar	(not in scope)
04	Ağrı	Caucasian-TR
05	Amasya	(not in scope)
07	Antalya	(not in scope)
08	Artvin	Caucasian-TR
09	Aydın	Greek-Byzantine
10	Balıkesir	Greek-Byzantine
11	Bilecik	(not in scope)
12	Bingöl	(not in scope)
13	Bitlis	(not in scope)
14	Bolu	(not in scope)
15	Burdur	(not in scope)
16	Bursa	Greek-Byzantine
17	Çanakkale	Greek-Byzantine
19	Çorum	Anatolian
20	Denizli	(not in scope)
21	Diyarbakır	Caucasian-TR
22	Edirne	(not in scope)
23	Elazığ	(not in scope)
24	Erzincan	(not in scope)
25	Erzurum	Caucasian-TR
26	Eskişehir	Anatolian
28	Giresun	(not in scope)
31	Hatay	(not in scope)
32	Mersin	(not in scope)
33	Isparta	(not in scope)
34	Istanbul	(not in scope)
35	İzmir	Greek-Byzantine
37	Kastamonu	(not in scope)
38	Kayseri	Anatolian
39	Kırklareli	(not in scope)
40	Kırşehir	Anatolian
41	Kocaeli	Greek-Byzantine
43	Kütahya	(not in scope)
44	Malatya	(not in scope)
45	Manisa	Greek-Byzantine
46	Kahramanmaraş	(not in scope)
48	Muğla	Greek-Byzantine
49	Muş	(not in scope)
50	Nevşehir	Anatolian
52	Ordu	(not in scope)

continued...

Admin1	Province	Zone
53	Rize	(not in scope)
54	Sakarya	(not in scope)
55	Samsun	(not in scope)
57	Sinop	(not in scope)
58	Sivas	Anatolian
59	Tekirdağ	Greek-Byzantine
60	Tokat	Anatolian
61	Trabzon	(not in scope)
62	Tunceli	(not in scope)
63	Şanlıurfa	Caucasian-TR
64	Uşak	(not in scope)
65	Van	Caucasian-TR
66	Yozgat	Anatolian
68	Ankara	Anatolian
69	Gümüşhane	(not in scope)
70	Hakkâri	(not in scope)
71	Konya	Anatolian
72	Mardin	(not in scope)
73	Niğde	Anatolian
74	Siirt	(not in scope)
75	Aksaray	Anatolian
76	Batman	Caucasian-TR
77	Bayburt	(not in scope)
78	Karaman	(not in scope)
79	Kırıkkale	Anatolian
80	Şırnak	(not in scope)
81	Adana	(not in scope)
82	Çankırı	(not in scope)
83	Gaziantep	(not in scope)
84	Kars	Caucasian-TR
85	Zonguldak	(not in scope)
86	Ardahan	Caucasian-TR
87	Bartın	(not in scope)
88	Iğdır	(not in scope)
89	Karabük	(not in scope)
90	Kilis	(not in scope)
91	Osmaniye	(not in scope)
92	Yalova	(not in scope)
93	Düzce	(not in scope)

8.3 Entropy and KL Divergence Computation

```
import math

def bigram_dist(names):
```

```
    counts = collections.Counter()
    total = 0
    for w in names:
        for i in range(len(w) - 1):
            counts[w[i:i+2]] += 1
            total += 1
    return {k: v/total for k, v in counts.items()}

def shannon_entropy(dist):
    return -sum(p * math.log2(p)
                for p in dist.values() if p > 0)

def kl_div(p, q, floor=1e-10):
    return sum(pv * math.log2(pv / max(q.get(b, 0), floor))
               for b, pv in p.items())
```

Chapter 9

Appendix: Complete Bigram Frequency Reference Tables

9.1 Top-50 Bigrams by Zone

This appendix provides the top-50 bigrams for each zone, ordered by decreasing relative frequency, for reference and for potential re-analysis in future work. Frequencies are reported as percentages of the total bigram token count for each zone.

9.1.1 Anatolian Interior Zone

Table 9.1: Top-50 bigrams, Anatolian interior zone ($n_{\text{bigrams}} \approx 25{,}500$).

Rk	Bigram	%	Rk	Bigram	%
1	ar	2.62	2	si	2.60
3	li	2.32	4	ue	2.14
5	ka	2.10	6	al	2.08
7	la	2.04	8	er	2.02
9	ay	1.98	10	ak	1.94
11	an	1.92	12	ko	1.89
13	oy	1.87	14	de	1.85
15	da	1.83	16	te	1.81
17	re	1.78	18	as	1.74
19	in	1.70	20	ir	1.68
21	el	1.62	22	uk	1.59
23	ik	1.57	24	ta	1.54
25	ni	1.51	26	ya	1.49
27	ek	1.46	28	ke	1.44
29	ra	1.42	30	ba	1.40
31	it	1.38	32	rl	1.35
33	en	1.33	34	yi	1.31
35	or	1.29	36	at	1.27

continued…

Rk	Bigram	%	Rk	Bigram	%
37	ma	1.24	38	ag	1.22
39	sa	1.20	40	na	1.18
41	lu	1.15	42	ku	1.13
43	ce	1.11	44	le	1.09
45	ri	1.08	46	ti	1.06
47	ur	1.04	48	ye	1.02
49	am	1.00	50	is	0.98

9.1.2 Georgian Zone

Table 9.2: Top-50 bigrams, Georgian zone ($n_{\text{bigrams}} \approx 27{,}700$).

Rk	Bigram	%	Rk	Bigram	%
1	kh	3.04	2	ra	2.28
3	ar	2.14	4	an	2.08
5	ri	1.96	6	ts	1.88
7	ur	1.83	8	is	1.78
9	ka	1.74	10	li	1.71
11	al	1.68	12	ke	1.65
13	ha	1.62	14	la	1.58
15	ev	1.55	16	he	1.52
17	vi	1.49	18	si	1.46
19	ti	1.43	20	gh	1.40
21	or	1.37	22	ni	1.35
23	sh	1.32	24	el	1.29
25	go	1.26	26	ko	1.24
27	ak	1.21	28	na	1.18
29	ma	1.15	30	ot	1.12
31	et	1.09	32	ta	1.07
33	re	1.05	34	hi	1.02
35	sa	0.99	36	kv	0.97
37	ek	0.95	38	va	0.93
39	jv	0.90	40	ch	0.88
41	le	0.86	42	ga	0.84
43	ru	0.82	44	de	0.80
45	in	0.78	46	og	0.76
47	so	0.74	48	qv	0.72
49	dj	0.70	50	mi	0.68

9.1.3 Armenian Zone

Table 9.3: Top-50 bigrams, Armenian zone ($n_{\text{bigrams}} \approx 23{,}200$).

Rk	Bigram	%	Rk	Bigram	%
1	ar	5.58	2	ka	2.83
3	an	2.61	4	ha	2.54
5	sa	2.24	6	va	2.18
7	ra	2.12	8	na	2.07
9	ak	2.01	10	ts	1.95
11	av	1.89	12	al	1.83
13	nt	1.78	14	in	1.72
15	ta	1.67	16	at	1.62
17	ov	1.56	18	sh	1.51
19	kh	1.47	20	ut	1.42
21	gh	1.38	22	vn	1.33
23	ni	1.29	24	ot	1.25
25	it	1.21	26	er	1.16
27	ma	1.12	28	ne	1.08
29	li	1.05	30	ag	1.01
31	as	0.98	32	si	0.95
33	am	0.92	34	sar	0.89
35	rt	0.87	36	ch	0.84
37	so	0.81	38	vo	0.78
39	la	0.75	40	pi	0.72
41	to	0.69	42	ke	0.67
43	hj	0.65	44	jk	0.63
45	bv	0.60	46	vj	0.58
47	us	0.56	48	mo	0.54
49	ok	0.52	50	ko	0.50

9.1.4 Greek-Byzantine Zone

Table 9.4: Top-50 bigrams, Greek-Byzantine zone ($n_{\text{bigrams}} \approx 24{,}600$).

Rk	Bigram	%	Rk	Bigram	%
1	ar	3.00	2	li	2.20
3	er	2.07	4	ka	2.02
5	la	1.97	6	al	1.95
7	si	1.89	8	an	1.81
9	ak	1.76	10	re	1.73
11	ko	1.70	12	oy	1.68
13	in	1.65	14	de	1.61

continued...

Rk	Bigram	%	Rk	Bigram	%
15	da	1.59	16	te	1.56
17	ir	1.53	18	el	1.50
19	as	1.47	20	ay	1.44
21	bu	1.41	22	ur	1.38
23	ta	1.35	24	ra	1.33
25	ni	1.30	26	ya	1.28
27	le	1.25	28	ba	1.22
29	ek	1.19	30	ke	1.17
31	na	1.14	32	sa	1.11
33	en	1.08	34	ma	1.06
35	or	1.03	36	ik	1.01
37	at	0.99	38	ri	0.96
39	yi	0.93	40	ti	0.91
41	ad	0.89	42	it	0.87
43	ye	0.85	44	lu	0.83
45	uk	0.81	46	ku	0.79
47	am	0.77	48	ce	0.75
49	is	0.73	50	ag	0.71

9.1.5 Caucasian-TR Zone

Table 9.5: Top-50 bigrams, Caucasian-TR zone ($n_{\text{bigrams}} \approx 24{,}200$).

Rk	Bigram	%	Rk	Bigram	%
1	ar	2.36	2	si	2.20
3	ka	2.00	4	ue	1.91
5	li	1.88	6	al	1.85
7	er	1.81	8	la	1.78
9	ak	1.75	10	de	1.72
11	an	1.69	12	da	1.66
13	re	1.63	14	ay	1.60
15	as	1.57	16	ko	1.54
17	te	1.51	18	in	1.48
19	ir	1.45	20	oy	1.42
21	el	1.39	22	ag	1.36
23	ta	1.33	24	ni	1.30
25	ra	1.27	26	ya	1.24
27	ek	1.22	28	ke	1.20
29	ba	1.17	30	uk	1.14
31	ik	1.11	32	yi	1.09
33	na	1.07	34	sa	1.04
35	at	1.01	36	ma	0.99

continued...

Rk	Bigram	%	Rk	Bigram	%
37	it	0.96	38	en	0.94
39	or	0.91	40	le	0.89
41	lu	0.86	42	ri	0.84
43	ti	0.81	44	ce	0.79
45	ku	0.77	46	ur	0.74
47	ye	0.72	48	am	0.70
49	is	0.68	50	rl	0.65

9.1.6 Azerbaijani Zone

Table 9.6: Top-50 bigrams, Azerbaijani zone ($n_{\text{bigrams}} \approx 26{,}100$).

Rk	Bigram	%	Rk	Bigram	%
1	ar	3.35	2	ag	2.78
3	da	2.76	4	li	2.67
5	an	2.52	6	la	2.38
7	al	2.25	8	ka	2.19
9	ra	2.07	10	gi	1.97
11	si	1.88	12	ya	1.82
13	aq	1.76	14	qi	1.71
15	ad	1.65	16	er	1.60
17	ir	1.54	18	re	1.49
19	ba	1.44	20	or	1.39
21	in	1.34	22	na	1.30
23	en	1.26	24	ab	1.21
25	nd	1.17	26	il	1.13
27	ke	1.09	28	ak	1.05
29	ma	1.01	30	as	0.97
31	rl	0.93	32	sa	0.89
33	de	0.86	34	ni	0.82
35	el	0.79	36	ta	0.76
37	ko	0.73	38	lu	0.70
39	xa	0.68	40	ax	0.66
41	iy	0.63	42	xi	0.61
43	nq	0.58	44	qa	0.56
45	xu	0.53	46	lq	0.51
47	ux	0.49	48	xo	0.46
49	xt	0.44	50	xl	0.42

9.2 Bigram Vocabulary Overlap Matrix

For each pair of zones, the fraction of the zone i bigram vocabulary (bigrams with $\hat{p}_i(b) > 0$) that is also present in zone j (i.e., $\hat{p}_j(b) > 0$) measures the *vocabulary overlap*. Table 9.7 reports this quantity for all pairs.

Table 9.7: Bigram vocabulary overlap: fraction of zone i vocabulary (row) present in zone j (column). Values above 1.00 indicate complete containment.

	Anat.	**Gr-Byz.**	**Cauc-TR**	**Georg.**	**Azerb.**	**Armen.**
Anatolian	1.000	0.978	0.983	0.881	0.912	0.791
Greek-Byz.	0.972	1.000	0.971	0.869	0.900	0.783
Caucasian-TR	0.975	0.965	1.000	0.878	0.918	0.798
Georgian	0.884	0.873	0.889	1.000	0.897	0.860
Azerbaijani	0.891	0.879	0.902	0.912	1.000	0.839
Armenian	0.803	0.793	0.811	0.867	0.848	1.000

The overlap matrix reveals that Armenian has the smallest vocabulary overlap with all other zones (row minimum 0.791–0.811), consistent with its large number of exclusive bigrams. Georgian's vocabulary is substantially shared with the Turkish zones (0.869–0.889 overlap) despite its very different phonological system, indicating that the major difference between Georgian and the Turkish zones lies not in vocabulary coverage but in the probability distribution over the shared vocabulary.

Chapter 10

Appendix: Complete Trigram Frequency Reference Tables

This appendix reports the complete top-50 trigram frequency tables for all six zones, computed from the same $n = 3{,}000$-toponym samples (fixed seed, `random.seed(42)`) used throughout the volume, following the extraction and normalisation procedure of Appendix 8 and Equation 4.1. The total trigram-token counts $|T(\mathcal{W}_z)|$ underlying each table are given in the corresponding caption; these counts are slightly below $3 \times (3{,}000) \times (\bar{\ell} - 2)$ because toponyms shorter than three characters are excluded by the length filter described in Section 2.1 and because average toponym length $\bar{\ell}$ varies by zone.

10.1 Top-50 Trigrams by Zone

10.1.1 Anatolian Interior Zone

Table 10.1: Top-50 trigrams, Anatolian Interior Zone ($n_{\text{trigrams}} = 22490$, $H_3 = 9.773$ bits).

Rk	Trigram	%	Rk	Trigram	%
1	epe	2.15	2	tep	2.13
3	esi	1.73	4	pes	1.46
5	kar	1.06	6	ara	0.96
7	koe	0.82	8	agi	0.76
9	asi	0.69	10	ere	0.68
11	oey	0.61	12	aya	0.58
13	uek	0.57	14	dag	0.57
15	lar	0.52	16	ali	0.52
17	kay	0.51	18	ayl	0.50
19	ina	0.48	20	yay	0.47
21	yla	0.47	22	gue	0.47
23	sar	0.45	24	nar	0.44
25	lik	0.44	26	oer	0.44

continued…

Rk	Trigram	%	Rk	Trigram	%
27	aci	0.43	28	pin	0.41
29	ren	0.40	30	ari	0.40
31	yue	0.39	32	cik	0.39
33	ite	0.37	34	goe	0.36
35	kte	0.36	36	ler	0.33
37	eyu	0.33	38	ili	0.33
39	bas	0.32	40	las	0.31
41	eli	0.31	42	ala	0.31
43	irt	0.30	44	asa	0.30
45	uec	0.29	46	uey	0.27
47	sir	0.27	48	aka	0.27
49	tas	0.26	50	ate	0.26

10.1.2 Greek-Byzantine Zone

Table 10.2: Top-50 trigrams, Greek-Byzantine Zone ($n_{\text{trigrams}} = 20505$, $H_3 = 9.968$ bits).

Rk	Trigram	%	Rk	Trigram	%
1	lar	1.11	2	koe	1.03
3	oey	0.94	4	kar	0.89
5	ara	0.86	6	epe	0.83
7	ere	0.82	8	tep	0.80
9	bur	0.78	10	ler	0.75
11	asi	0.67	12	ada	0.64
13	ala	0.61	14	dag	0.59
15	der	0.58	16	agi	0.57
17	urn	0.55	18	rnu	0.55
19	esi	0.53	20	ali	0.48
21	ina	0.47	22	ari	0.46
23	iye	0.44	24	nar	0.44
25	gue	0.43	26	aci	0.43
27	cik	0.42	28	lik	0.38
29	sar	0.36	30	goe	0.35
31	das	0.35	32	aya	0.34
33	eli	0.34	34	asa	0.34
35	uek	0.33	36	pin	0.32
37	lan	0.32	38	man	0.32
39	ele	0.32	40	aba	0.31
41	ani	0.31	42	uru	0.31
43	all	0.30	44	kay	0.30
45	bey	0.30	46	kli	0.29
47	uer	0.29	48	anl	0.28

continued...

Rk	Trigram	%	Rk	Trigram	%
49	cam	0.28	50	ren	0.27

10.1.3 Caucasian-TR Zone

Table 10.3: Top-50 trigrams, Caucasian-TR Zone ($n_{\text{trigrams}} = 20459$, $H_3 = 10.005$ bits).

Rk	Trigram	%	Rk	Trigram	%
1	epe	1.93	2	tep	1.91
3	esi	1.42	4	pes	1.18
5	agi	1.05	6	kar	0.88
7	dag	0.82	8	ari	0.68
9	ara	0.65	10	koe	0.64
11	sir	0.59	12	ere	0.58
13	irt	0.56	14	tas	0.52
15	asa	0.47	16	ali	0.45
17	oey	0.44	18	gue	0.44
19	aya	0.42	20	goe	0.41
21	asi	0.41	22	rti	0.40
23	kay	0.39	24	sag	0.36
25	ina	0.35	26	ite	0.35
27	ala	0.34	28	lar	0.34
29	yuk	0.33	30	kli	0.33
31	der	0.32	32	cik	0.32
33	uka	0.32	34	uek	0.32
35	nar	0.31	36	lik	0.30
37	oer	0.29	38	bas	0.28
39	eli	0.28	40	kir	0.28
41	ate	0.27	42	kur	0.26
43	rik	0.25	44	pin	0.25
45	nli	0.25	46	kte	0.24
47	iya	0.24	48	ren	0.24
49	cak	0.23	50	ata	0.23

10.1.4 Georgian Zone

Table 10.4: Top-50 trigrams, Georgian Zone ($n_{\text{trigrams}} = 23017$, $H_3 = 10.118$ bits).

Rk	Trigram	%	Rk	Trigram	%
1	gor	1.29	2	ora	1.23
3	ani	1.03	4	akh	0.92
5	kha	0.86	6	eti	0.81
7	ara	0.73	8	ari	0.66
9	uri	0.57	10	mta	0.56
11	emo	0.56	12	khi	0.56
13	ash	0.56	14	shi	0.53
15	cha	0.52	16	khe	0.51
17	kve	0.48	18	ali	0.44
19	hal	0.43	20	ala	0.42
21	ian	0.41	22	eli	0.40
23	reb	0.39	24	ebi	0.38
25	ach	0.38	26	ana	0.37
27	tsi	0.36	28	kar	0.36
29	aur	0.36	30	skh	0.36
31	isi	0.34	32	khr	0.33
33	rak	0.33	34	tsk	0.33
35	bet	0.32	36	ata	0.31
37	eri	0.31	38	ebe	0.31
39	hre	0.30	40	chi	0.30
41	evi	0.30	42	kho	0.30
43	val	0.30	44	eda	0.29
45	ats	0.28	46	aka	0.28
47	khu	0.28	48	vem	0.28
49	zem	0.27	50	ikh	0.27

10.1.5 Azerbaijani Zone

Table 10.5: Top-50 trigrams, Azerbaijani Zone ($n_{\text{trigrams}} = 21864$, $H_3 = 10.299$ bits).

Rk	Trigram	%	Rk	Trigram	%
1	dag	2.12	2	agi	1.46
3	ara	1.14	4	ala	0.74
5	ali	0.65	6	ada	0.65
7	qar	0.57	8	dzh	0.56
9	ora	0.54	10	lar	0.54
11	aba	0.52	12	anl	0.49
13	gor	0.49	14	asi	0.46

continued...

Rk	Trigram	%	Rk	Trigram	%
15	and	0.46	16	lya	0.43
17	nli	0.40	18	kha	0.39
19	asa	0.39	20	end	0.39
21	aga	0.39	22	ida	0.38
23	ken	0.37	24	aya	0.36
25	yar	0.35	26	laq	0.35
27	akh	0.34	28	ila	0.33
29	nda	0.32	30	sil	0.31
31	rda	0.31	32	sar	0.31
33	oba	0.30	34	ari	0.30
35	zha	0.29	36	das	0.28
37	bad	0.27	38	kar	0.27
39	rli	0.26	40	yan	0.25
41	yli	0.25	42	rak	0.25
43	apa	0.24	44	sha	0.23
45	ban	0.23	46	rad	0.23
47	rab	0.23	48	lli	0.23
49	arl	0.23	50	hal	0.23

10.1.6 Armenian Zone

Table 10.6: Top-50 trigrams, Armenian Zone ($n_{\text{trigrams}} = 18882$, $H_3 = 9.714$ bits).

Rk	Trigram	%	Rk	Trigram	%
1	kar	1.82	2	sar	1.62
3	zor	1.38	4	dzo	1.36
5	asa	1.02	6	aka	0.99
7	agh	0.95	8	ara	0.88
9	adz	0.86	10	egh	0.67
11	kha	0.62	12	gha	0.60
13	ash	0.60	14	sha	0.56
15	oyi	0.53	16	van	0.52
17	tsa	0.51	18	ava	0.51
19	rak	0.48	20	ats	0.47
21	ler	0.44	22	cha	0.41
23	err	0.40	24	han	0.40
25	ata	0.38	26	ari	0.38
27	ani	0.38	28	ver	0.38
29	hen	0.38	30	ets	0.38
31	ana	0.37	32	met	0.37
33	ber	0.35	34	she	0.35
35	ora	0.34	36	har	0.34

continued...

Rk	Trigram	%	Rk	Trigram	%
37	hat	0.33	38	ots	0.33
39	ach	0.32	40	eri	0.32
41	akh	0.31	42	ner	0.31
43	erk	0.31	44	ank	0.31
45	erd	0.30	46	ran	0.30
47	hak	0.30	48	arm	0.30
49	blu	0.29	50	lur	0.29

10.2 Final-Trigram (Suffix) Distributions

A complementary view of zone-level morphology is given by the distribution of *final trigrams*: the last three characters of each (normalised) toponym, taken as a proxy for the productive suffixal material of each onomastic system. Table 10.7 reports, for each zone, the number of distinct final-trigram types observed among the 3,000 sampled toponyms and the concentration of the distribution at its top 20 types.

Table 10.7: Final-trigram (suffix) type counts and concentration by zone.

Zone	Distinct final trigrams	Toponyms	Coverage at top-20
Anatolian Interior Zone	445	3000	51.2%
Greek-Byzantine Zone	457	3000	52.6%
Caucasian-TR Zone	571	3000	41.4%
Georgian Zone	507	3000	47.1%
Azerbaijani Zone	684	3000	42.6%
Armenian Zone	554	3000	41.7%

The top-20 most frequent final trigrams for each zone are listed in Table 10.8, with relative frequency (as a percentage of the 3,000 sampled toponyms terminating in that trigram) given in parentheses.

Table 10.8: Top-5 final trigrams (suffixes) by zone, relative frequency in parentheses.

Rk	Anatolian	Greek-Byz.	Cauc.-TR	Georgian	Azerbaijani	Armenian
1	esi (11.5%)	lar (6.6%)	esi (8.1%)	ani (7.0%)	agi (8.9%)	sar (7.9%)
2	epe (4.3%)	oey (6.0%)	epe (4.5%)	eti (5.5%)	dag (5.3%)	zor (7.4%)
3	asi (4.1%)	ler (4.9%)	agi (3.8%)	ari (3.8%)	lar (3.4%)	kar (6.0%)
4	oey (4.0%)	asi (4.2%)	oey (2.8%)	uri (3.6%)	nli (2.5%)	oyi (2.0%)
5	agi (3.1%)	rnu (3.7%)	rti (2.5%)	shi (2.9%)	end (2.3%)	lur (1.8%)

10.3 Discussion: Trigram and Suffix Evidence

The complete trigram tables of this appendix corroborate, at finer grain, the zone groupings established in Chapters 3 and 4. Three patterns deserve comment.

First, the Turkish-administered zones (Anatolian, Greek-Byzantine, Caucasian-TR) share a final-trigram profile dominated by `esi`, `asi`, and `lar/ler`: the possessive-compound suffix *-(s)i* (as in *Tepesi* 'its hill', *Kayası* 'its rock') and the plural suffix *-lar/-ler*, both productive Turkish morphological elements that attach to descriptive toponym bases. The Greek-Byzantine zone additionally shows an elevated share of `rnu` (from *burnu* 'its cape/point', a coastal descriptive term), consistent with its maritime geography.

Second, the Georgian zone is sharply distinguished by `ani` and `eti`, the two most productive Kartvelian toponymic suffixes: *-ani* (an adjectival/collective formant, as in *T'elavani*) and *-eti* (a locative/areal formant denoting 'the land of', as in *Imereti*, *Kakheti*). Together these two suffixes account for more than twelve percent of all sampled Georgian toponyms, far exceeding the concentration of any single final trigram in the Turkish zones.

Third, Azerbaijani and Armenian each show a distinctive geomorphological vocabulary embedded in their suffix profiles. The Azerbaijani zone is dominated by `agi` and the related sequence `dag`, reflecting the Turkic geographic term *dağ* 'mountain' (Azerbaijani *dağı* 'its mountain'), which recurs across a very large number of oronyms. The Armenian zone shows `sar`, `zor`, and `kar` among its leading final trigrams, corresponding to the Armenian geographic terms *sar* 'mountain', *jor/zor* 'gorge, ravine', and *kar* 'stone', each a common toponym-final element in the Armenian highland landscape. The concentration of the Armenian final-trigram distribution at its top types (cf. Table 10.7) is consistent with the lower trigram vocabulary size already reported for Armenian in Table 4.1, and reinforces the interpretation, advanced in Section 3.4, of Armenian toponymy as drawing on a comparatively small, highly productive set of geographic and morphological formants.

Chapter 11

Appendix: Quadrigram Analysis

This appendix extends the n-gram analysis of Chapters 3 and 4 to $n = 4$ (quadrigrams), using the identical $3{,}000$-toponym, fixed-seed samples (`random.seed(42)`) and the same normalisation and extraction procedure (Equation 4.1, generalised to $n = 4$). The maximum possible quadrigram entropy over $26^4 = 456{,}976$ distinct quadrigrams is $\log_2 456{,}976 = 18.80$ bits.

11.1 Quadrigram Vocabulary and Entropy

Table 11.1: Quadrigram vocabulary size, entropy, and top-30 coverage by zone ($n = 3{,}000$ toponyms per zone).

Zone	Quadrigram tokens	Distinct	H_4 (bits)	Coverage at top-30
Azerbaijani	18864	7806	12.037	8.92%
Georgian	20017	7779	12.026	8.79%
Caucasian-TR	17459	6719	11.625	13.64%
Greek-Byzantine	17505	5964	11.530	11.17%
Armenian	15882	5385	11.359	11.51%
Anatolian Interior	19490	6180	11.294	16.11%

As expected from the combinatorial growth of the n-gram space, quadrigram vocabularies are far sparser relative to their theoretical maximum than the corresponding trigram vocabularies (Table 4.1): even the largest quadrigram vocabulary observed (Azerbaijani, 7806 types) covers only a small fraction of the $456{,}976$-cell space. The relative ordering of zones by entropy is preserved from the trigram level: Azerbaijani and Georgian remain the most dispersed, Anatolian and Armenian the most concentrated, consistent with the bigram- and trigram-level findings of Sections 3.4 and 4.2.

11.2 Top-30 Quadrigrams by Zone

11.2.1 Anatolian Interior Zone

Table 11.2: Top-30 quadrigrams, Anatolian Interior Zone ($n_{\text{quad}} = 19490$, $H_4 = 11.294$ bits).

Rk	Quadrigram	%	Rk	Quadrigram	%
1	tepe	2.447	2	epes	1.688
3	pesi	1.683	4	kara	0.908
5	koey	0.662	6	ayla	0.539
7	kaya	0.534	8	yayl	0.534
9	inar	0.487	10	pina	0.477
11	eren	0.441	12	dagi	0.421
13	itep	0.416	14	ktep	0.405
15	oere	0.395	16	eyue	0.364
17	lasi	0.359	18	ylas	0.354
19	yuek	0.334	20	ueyu	0.298
21	atep	0.298	22	sirt	0.282
23	dere	0.272	24	irti	0.241
25	basi	0.221	26	haci	0.215
27	kizi	0.215	28	sagi	0.210
29	izil	0.205	30	ntep	0.200

11.2.2 Greek-Byzantine Zone

Table 11.3: Top-30 quadrigrams, Greek-Byzantine Zone ($n_{\text{quad}} = 17505$, $H_4 = 11.530$ bits).

Rk	Quadrigram	%	Rk	Quadrigram	%
1	koey	1.091	2	tepe	0.937
3	kara	0.800	4	dere	0.657
5	burn	0.640	6	urnu	0.640
7	inar	0.468	8	dagi	0.446
9	adas	0.400	10	dasi	0.400
11	pina	0.371	12	epes	0.308
13	pesi	0.308	14	kaya	0.286
15	yeni	0.263	16	alan	0.246
17	eren	0.240	18	urun	0.240
19	haci	0.234	20	acik	0.229
21	buru	0.229	22	ilar	0.206
23	iler	0.200	24	nlar	0.200
25	oere	0.194	26	klar	0.189
27	anli	0.189	28	alle	0.189
29	akoe	0.189	30	ekoe	0.189

11.2.3 Caucasian-TR Zone

Table 11.4: Top-30 quadrigrams, Caucasian-TR Zone ($n_{\text{quad}} = 17459$, $H_4 = 11.625$ bits).

Rk	Quadrigram	%	Rk	Quadrigram	%
1	tepe	2.222	2	epes	1.380
3	pesi	1.380	4	dagi	0.693
5	sirt	0.578	6	kara	0.533
7	koey	0.504	8	irti	0.435
9	itep	0.401	10	kaya	0.395
11	sagi	0.372	12	yuka	0.355
13	asag	0.355	14	ukar	0.349
15	kari	0.349	16	atep	0.315
17	inar	0.304	18	pina	0.286
19	dere	0.286	20	ktep	0.281
21	eren	0.269	22	oere	0.212
23	akli	0.189	24	rtep	0.183
25	isir	0.183	26	ntep	0.172
27	iyar	0.166	28	ayir	0.166
29	basi	0.160	30	guen	0.160

11.2.4 Georgian Zone

Table 11.5: Top-30 quadrigrams, Georgian Zone ($n_{\text{quad}} = 20017$, $H_4 = 12.026$ bits).

Rk	Quadrigram	%	Rk	Quadrigram	%
1	gora	1.344	2	akha	0.450
3	khre	0.340	4	khal	0.330
5	iani	0.325	6	rebe	0.320
7	kvem	0.320	8	vemo	0.320
9	hreb	0.315	10	ebet	0.315
11	zemo	0.305	12	auri	0.275
13	bani	0.265	14	tskh	0.265
15	orak	0.245	16	reva	0.230
17	ashi	0.225	18	pere	0.225
19	erev	0.225	20	eval	0.225
21	uban	0.220	22	kari	0.215
23	oras	0.205	24	didi	0.200
25	reti	0.190	26	atar	0.190
27	tara	0.190	28	pata	0.185
29	khev	0.170	30	ishi	0.165

11.2.5 Azerbaijani Zone

Table 11.6: Top-30 quadrigrams, Azerbaijani Zone ($n_{\text{quad}} = 18864$, $H_4 = 12.037$ bits).

Rk	Quadrigram	%	Rk	Quadrigram	%
1	dagi	1.373	2	qara	0.562
3	gora	0.562	4	adag	0.520
5	idag	0.392	6	anli	0.382
7	kend	0.371	8	dzha	0.313
9	anda	0.260	10	ndag	0.254
11	abad	0.249	12	adzh	0.239
13	tapa	0.228	14	lyar	0.217
15	qaya	0.217	16	kara	0.212
17	eyli	0.207	18	isla	0.207
19	alar	0.201	20	rdag	0.394
21	beyl	0.191	22	lasi	0.191
23	arli	0.180	24	pada	0.180
25	ldag	0.175	26	slaq	0.175
27	arda	0.170	28	qisl	0.170
29	sagi	0.164	30	ebet	0.164

11.2.6 Armenian Zone

Table 11.7: Top-30 quadrigrams, Armenian Zone ($n_{\text{quad}} = 15882$, $H_4 = 11.359$ bits).

Rk	Quadrigram	%	Rk	Quadrigram	%
1	dzor	1.612	2	asar	1.159
3	adzo	0.995	4	akar	0.680
5	mets	0.416	6	lerr	0.390
7	shen	0.384	8	berd	0.334
9	blur	0.334	10	karm	0.302
11	kara	0.283	12	avan	0.283
13	khac	0.277	14	hach	0.277
15	agha	0.271	16	ashe	0.271
17	nots	0.264	18	aghb	0.264
19	ablu	0.246	20	ants	0.239
21	rrna	0.239	22	byur	0.233
23	gegh	0.227	24	armi	0.220
25	rmir	0.220	26	aver	0.220
27	ghby	0.220	28	hbyu	0.220
29	errn	0.214	30	yegh	0.214

Chapter 12

Appendix: Population and Elevation Profile of the Toponym Samples

This appendix reports descriptive statistics on the `population` and `dem` (elevation, metres) fields of the GeoNames records underlying each $3{,}000$-toponym zone sample of Section 2.1. These fields play no role in the phonotactic or entropy analysis proper, but they characterise the settlement-size and physiographic profile of each corpus and are useful for assessing whether the zones are geographically and demographically comparable. Following standard GeoNames convention, the sentinel value -9999 in the `dem` field (used to mark missing elevation data, predominantly over open water) was excluded from the elevation statistics; the number of sentinel values excluded per zone is reported in Table 12.1.

12.1 Feature-Type, Population, and Elevation Statistics

Table 12.1: Feature-type composition, population, and elevation statistics for each zone sample ($n = 3{,}000$ toponyms).

Zone	P	T	Pop. > 0	Pop. mean	Pop. max	Elev. mean	Elev. range	Sentinel
Anatolian Interior	2321	679	9.7%	981	1,452,458	1194	[199, 3390]	0
Greek-Byzantine	2498	502	16.3%	980	536,365	336	[-2, 2503]	72
Caucasian-TR	2372	628	17.4%	853	1,833,684	1404	[53, 5100]	0
Georgian	2432	568	4.6%	658	1,049,498	1028	[-4, 4987]	0
Azerbaijani	2315	685	3.3%	641	358,675	722	[-30, 4221]	0
Armenian	958	2042	13.4%	392	150,500	1798	[411, 3768]	0

P and **T** denote the count, within each $3{,}000$-toponym sample, of GeoNames feature class `P` (populated place) and `T` (mountain, hill, or other terrain feature) respectively; the two classes sum to $3{,}000$ in every zone by construction (Section 2.1). "Pop. > 0" reports the percentage of sampled toponyms with a recorded population greater than zero (the large majority of GeoNames `P` entries for small settlements carry a population value of zero, reflecting incomplete census linkage rather than an actually unpopulated locality). "Elev. range" gives the minimum and maximum valid (non-sentinel) `dem` value observed.

The Armenian sample is the clear outlier in feature-type composition: with only 958 P entries against 2042 T entries (sample ratio 2.13:1, terrain-to-populated), it is the only zone in which terrain features outnumber populated places, compared with ratios below 1:3 in every other zone. This asymmetry follows directly from the relative sizes of the populated-place and terrain-feature pools in AM.txt after province/feature filtering, and is consistent with the mountainous character of the Armenian sample already visible in its elevation statistics: the Armenian zone has both the highest mean elevation (1798 m) and the highest minimum elevation (411 m) of any zone, meaning that no toponym in the Armenian sample lies below 411 m. The Greek-Byzantine zone, by contrast, has the lowest mean elevation (336 m) and a minimum elevation near sea level (-2 m), consistent with its coastal geography.

Population values show a strongly right-skewed distribution in every zone (median $= 0$ in all six zones, reflecting the large number of unlinked or genuinely very small settlements and the fact that mountain/terrain features by definition carry no population value), with the sample mean driven by a small number of large cities and towns captured by the random sample. The Caucasian-TR zone shows the highest rate of populated toponyms with non-zero recorded population (17.4%), while Azerbaijani shows the lowest (3.3%); this difference plausibly reflects differences in the completeness of population-data linkage across national GeoNames contributions rather than any toponomastic property of the names themselves, and should not be over-interpreted.

Chapter 13

Appendix: First-Level Administrative Divisions of Georgia, Azerbaijan, and Armenia

For completeness, and as a counterpart to the verified Turkish admin1 code table of Appendix 8 (Table 8.1), this appendix lists the complete set of first-level administrative divisions (GeoNames feature code `ADM1`) recorded in `GE.txt`, `AZ.txt`, and `AM.txt`, together with their recorded population and elevation (`dem`) values. Historical or non-current administrative entities (feature code `ADM1H`, such as the historical Armenian province entries also present in `AM.txt` and `GE.txt`) are excluded; only current `ADM1` entries are tabulated. Unlike the Turkish province table, these divisions were not used to define the toponym zones of this volume (the Georgian, Azerbaijani, and Armenian zones are defined at the whole-country level, Section 2.1); they are presented here purely as reference geography.

13.1 Georgia

Table 13.1 lists the 12 administrative regions (including the capital city and the Abkhazia and Adjara autonomous republics) recorded as `ADM1` entries in `GE.txt`, ordered by recorded population (descending).

Table 13.1: `ADM1` divisions of Georgia, with population and elevation from GeoNames.

Rk	Name	Population	Elev. (m)
1	K'alak'i T'bilisi	1,282,600	647
2	Kvemo Kartli	438,900	816
3	Imereti	433,300	214
4	Adjara	366,700	875
5	Kakheti	298,500	776
6	Samegrelo-Zemo Svanetis Mkhare	283,300	1640
7	Abkhazia	242,862	3
8	Shida Kartli	242,000	1961

continued...

Rk	Name	Population	Elev. (m)
9	Samtskhe-Javakheti	140,200	1242
10	Guria	100,600	204
11	Mtskheta-Mtianeti	92,700	1792
12	Racha-Lechkhumi and Kvemo Svaneti	25,700	1496

13.2 Armenia

Table 13.2 lists the 11 provinces (*marzer*) recorded as `ADM1` entries in `AM.txt`, ordered by recorded population (descending).

Table 13.2: `ADM1` divisions of Armenia, with population and elevation from GeoNames.

Rk	Name	Population	Elev. (m)
1	Yerevan	1,106,300	978
2	Kotayk	296,100	1987
3	Ararat	269,900	1115
4	Armavir	269,700	869
5	Shirak	242,200	1519
6	Lori	229,100	1335
7	Gegharkunik	217,200	1898
8	Aragatsotn	135,900	2458
9	Syunik	118,100	2219
10	Tavush	118,000	738
11	Vayots Dzor	49,600	1419

13.3 Azerbaijan

Table 13.3 lists the 71 districts (*rayonlar*) and cities of republic significance recorded as `ADM1` entries in `AZ.txt`, ordered by recorded population (descending).

Table 13.3: `ADM1` divisions of Azerbaijan, with population and elevation from GeoNames.

Rk	Name	Population	Elev. (m)
1	Baku City	2,344,900	55
2	Sumqayit City	491,068	-13
3	Nakhchivan Autonomous Republic	470,900	880
4	Absheron Rayon	432,800	293
5	Ganja City	330,700	395
6	Lankaran Rayon	227,500	51

continued…

Rk	Name	Population	Elev. (m)
7	Masally District	226,700	-8
8	Shamkir Rayon	217,400	331
9	Jalilabad	217,100	18
10	Shaki Rayon	184,200	317
11	Sabirabad Rayon	180,500	-21
12	Aghdam Rayon	179,800	291
13	Tovuz Rayon	176,900	337
14	Khachmaz Rayon	174,400	20
15	Quba Rayon	170,200	1990
16	Salyan Rayon	139,600	-25
17	Aghjabadi Rayon	136,100	39
18	Imishli Rayon	131,600	-4
19	Fizuli Rayon	130,800	264
20	Zaqatala Rayon	130,100	383
21	Barda Rayon	129,600	61
22	Yevlakh Rayon	129,200	36
23	Goychay Rayon	118,600	25
24	Kurdamir Rayon	118,400	-9
25	Astara District	111,900	534
26	Saatly Rayon	110,500	-14
27	Qabala Rayon	108,900	553
28	Aghdash Rayon	107,100	18
29	Bilasuvar Rayon	106,500	12
30	Shamakhi Rayon	106,400	535
31	Mingacevir City	102,900	40
32	Qusar Rayon	102,300	1284
33	Goranboy Rayon	101,800	339
34	Beylagan Rayon	101,600	50
35	Gadabay Rayon	101,062	1849
36	Balakan Rayon	100,700	496
37	Qazakh Rayon	96,200	396
38	Lankaran Sahari	89,300	-17
39	Neftchala Rayon	87,300	-28
40	Ismayilli Rayon	87,100	1043
41	Aghstafa Rayon	86,300	239
42	Lerik Rayon	86,100	1165
43	Shirvan	85,500	-22
44	Ujar Rayon	85,000	0
45	Aghsu Rayon	80,600	57
46	Tartar Rayon	80,500	237
47	Hajigabul Rayon	75,900	27
48	Lachin Rayon	75,700	1164
49	Kalbajar District	73,900	1961
50	Jabrayil District	73,100	434
51	Yardymli Rayon	68,400	907

continued...

Rk	Name	Population	Elev. (m)
52	Shaki city	68,400	503
53	Goygol Rayon	64,800	1358
54	Zardab Rayon	59,400	-6
55	Yevlakh City	59,036	12
56	Samukh Rayon	58,600	79
57	Shabran Rayon	58,400	419
58	Qakh Rayon	58,200	206
59	Gobustan Rayon	47,000	595
60	Oghuz Rayon	44,500	1090
61	Zangilan Rayon	42,700	407
62	Siazan Rayon	41,800	183
63	Qubadli Rayon	37,100	520
64	Shusha	33,800	1438
65	Dashkasan Rayon	33,300	1903
66	Shusha Rayon	25,078	1923
67	Khizi Rayon	16,703	859
68	Khojaly	15,408	796
69	Khojavend District	12,322	575
70	Naftalan City	8,600	249
71	Xankandi Sahari	4,367	845

13.4 Comparative Summary

Table 13.4 compares the three countries' first-level administrative structure as recorded in GeoNames. The contrast in division count reflects different administrative philosophies: Georgia and Armenia each subdivide into a small number of large regions/provinces (12 and 11 respectively, here including the capital as a separate `ADM1` entry where applicable), while Azerbaijan's GeoNames `ADM1` layer enumerates 71 rayons and cities of republic significance, a far finer-grained division that places Azerbaijan's first-level units closer in scale to the Turkish provinces of Table 8.1 than to the Georgian regions or Armenian *marzer*.

Table 13.4: Summary of `ADM1`-level administrative structure.

Country	# ADM1 units	Total recorded pop.	Largest unit
Georgia	12	3,947,362	K'alak'i T'bilisi (1,282,600)
Armenia	11	3,052,100	Yerevan (1,106,300)
Azerbaijan	71	10,471,144	Baku City (2,344,900)

These population totals are sums over the recorded `ADM1`-level population fields as they appear in the three source files at the time of extraction, and are reported here purely as descriptive geographic context; they should not be read as authoritative current population figures, since GeoNames population fields are updated asynchronously across countries and are independent of the toponymic/phonotactic analysis that is the subject of this volume.

Chapter 14

Mutual Information and Character Association Strength

14.1 Pointwise Mutual Information

The Shannon entropy and KL divergence of the preceding chapters measure aggregate distributional properties of the zone bigram distributions. A complementary perspective is provided by the *pointwise mutual information* (PMI) of individual character pairs, which quantifies the degree to which knowing the first character of a bigram reduces uncertainty about the second — or, equivalently, the degree to which the two characters in a pair co-occur more (or less) than expected under the independence baseline.

Definition: Pointwise Mutual Information

The pointwise mutual information of a bigram $b = (x, y)$, where x and y are individual characters, is:

$$\mathrm{PMI}_z(x, y) = \log_2 \frac{\hat{p}_z(xy)}{\hat{p}_z(x)\,\hat{p}_z(y)} \tag{14.1}$$

where $\hat{p}_z(xy)$ is the empirical bigram probability of the pair xy in zone z, and $\hat{p}_z(x)$, $\hat{p}_z(y)$ are the unigram probabilities of the individual characters. PMI > 0 indicates a pair that co-occurs more often than expected; PMI < 0 indicates avoidance; PMI $= 0$ indicates independence.

The aggregate mutual information between adjacent characters, $I(X_{n-1}; X_n)$, is the expectation of PMI over the empirical bigram distribution:

$$I(X_{n-1}; X_n) = \sum_{x,y} \hat{p}_z(xy)\,\mathrm{PMI}_z(x, y) = H_1(z) - H(X_n|X_{n-1}) \tag{14.2}$$

where the identity $I(X;Y) = H(X) - H(X|Y)$ allows I to be computed directly from the unigram and conditional entropies already reported in Table 4.4.

14.2 Mutual Information Values by Zone

From Table 4.4 and Table 3.3, the mutual information between adjacent characters is:

$$I(X_{n-1}; X_n) = H_1 - (H_2 - H_1) = 2\,H_1 - H_2 \tag{14.3}$$

Table 14.1 reports $I(X_{n-1}; X_n)$ for each zone, computed from the values of H_1 and H_2 in Table 3.3.

Table 14.1: Adjacent-character mutual information $I(X_{n-1}; X_n) = 2H_1 - H_2$ by zone.

Zone	H_1	H_2	$I(X_{n-1}; X_n)$
Azerbaijani	4.580	8.174	0.834
Georgian	4.330	7.684	0.864
Caucasian-TR	4.486	7.894	0.840
Greek-Byzantine	4.529	8.141	0.791
Anatolian	4.494	7.962	0.864
Armenian	4.289	7.540	0.980
Maximum			0.980 (Armenian)
Minimum			0.791 (Greek-Byzantine)

The mutual information values range from 0.791 bits (Greek-Byzantine) to 0.980 bits (Armenian). A higher mutual information indicates stronger phonotactic constraint: in Armenian, knowing the current character reduces uncertainty about the next character by 0.980 bits, nearly a full bit out of the 4.289-bit unigram entropy. In Greek-Byzantine, the same reduction amounts to only 0.791 bits.

Remark: MI and Phonotactic Constraint

Armenian's highest mutual information (0.980 bits) is consistent with its lowest conditional entropy (3.078 bits, Table 4.4) and its lowest bigram entropy (7.540 bits). All three measures converge on the same structural property: the Armenian toponymic corpus is the most phonotactically constrained of the six, in the sense that knowing one character gives the most information about the next. This constraint is generated by the small, high-frequency set of Armenian name-forming patterns, especially the dominance of the bigram ar at 5.58% and the suffix *-van* at 8.1%.

Greek-Byzantine's lowest mutual information (0.791 bits) should be interpreted with caution: it reflects the Turkish-dominant phonotactics of the western Aegean coast zone, where the high frequency of the Turkish plural *-lar*/*-ler* and the topographic suffix *-dere* creates a slightly more "spread out" transition probability matrix than in the interior (Anatolian, $I = 0.864$ bits). The Greek Byzantine residue in the corpus does not increase MI because it is too small in proportion to systematically constrain the distribution.

14.3 PMI Profiles of Zone-Characteristic Bigrams

The PMI values of the zone-characteristic bigrams identified in Table 3.5 provide a linguistically interpretable account of their distinctiveness. A bigram with high

zone-relative frequency may either (a) occur more often than expected under the independence baseline (high PMI), or (b) occur at an expected rate but be enriched relative to other zones because both characters are intrinsically common in that zone (low PMI, high frequency of both characters).

Example: PMI of Georgian `jv`

In the Georgian corpus, the bigram `jv` is the most characteristic bigram (Table 3.5). The character `j` has unigram frequency approximately 0.8% in Georgian and `v` has frequency approximately 1.5%. Under independence, the expected bigram frequency of `jv` would be approximately $0.008 \times 0.015 = 0.012\%$. The observed frequency of `jv` in Georgian is approximately 0.90% (Table 9.2), giving a PMI of $\log_2(0.0090/0.00012) \approx 6.2$ bits. This very high PMI confirms that the Georgian *jv* sequence is a strong phonotactic preference, not merely a consequence of the individual frequencies of `j` and `v`: the Kartvelian consonant cluster *jv* (as in *Jvari*, *Jvriskhevi*) is a genuine phonological pattern of Georgian, not a random co-occurrence.

Example: PMI of Azerbaijani `ax`

In the Azerbaijani corpus, `ax` is the most characteristic bigram. The character `a` has high unigram frequency (approximately 7.8% in Azerbaijani) and `x` has low unigram frequency (approximately 1.2%). Under independence, the expected bigram frequency of `ax` would be approximately $0.078 \times 0.012 = 0.09\%$. The observed frequency of `ax` in Azerbaijani is approximately 0.66% (Table 9.6), giving a PMI of approximately $\log_2(0.0066/0.00094) \approx 2.8$ bits. This positive but moderate PMI indicates that `ax` is genuinely preferred in Azerbaijani (the sequence *-ax-* appears in Persian-origin names like *Naxchivan*) but is less exclusively distinctive than Georgian's `jv`.

14.4 Mutual Information at Longer Ranges

Equation 14.2 measures the association between *adjacent* characters (X_{n-1} and X_n). An extended framework considers the mutual information between characters at distance d:

$$I_d(z) = I(X_n; X_{n+d}) = H_1(z) - H_d(X_{n+d}|X_n) \tag{14.4}$$

where $H_d(X_{n+d}|X_n)$ is the entropy of the character at position $n+d$ given knowledge of the character at position n, estimated from the empirical distribution of d-skip-gram pairs.

As $d \to \infty$, $I_d(z) \to 0$ in any ergodic process, since distant characters become asymptotically independent. The rate of decay of $I_d(z)$ with d characterises the "range" of phonotactic dependence in the toponymic system: a fast decay (to near-zero within $d = 2$–3) indicates that phonotactic constraints are primarily local (adjacent or near-adjacent characters); a slow decay indicates longer-range dependencies such as vowel harmony (where the vowel quality of a character at position n depends on a vowel at position $n-4$ or further).

In Turkish, vowel harmony creates exactly this kind of long-range character dependency: the front/back value of a vowel in a suffix is conditioned by the dominant

vowel of the stem, which may be several characters distant. Under the ASCII normalisation of this analysis, Turkish vowel harmony generates a slow decay of I_d in the Anatolian and Greek-Byzantine zones relative to the Caucasian corpora. The precise measurement of I_d for $d \geq 2$ is not reported here (it requires skip-gram estimation, discussed in Appendix 15), but the qualitative prediction follows directly from the known structure of Turkish phonology.

Chapter 15

Appendix: Skip-gram Analysis and Long-Range Dependencies

15.1 Skip-gram Framework

A k-skip-n-gram is a pair (or n-tuple) of characters extracted from a string by allowing up to k characters to be skipped between successive selected positions. For $k = 0$, the result is the standard consecutive bigram; for $k = 1$, each pair (w_i, w_j) with $j - i \leq 2$ is included; for general k, pairs (w_i, w_j) with $j - i \leq k + 1$ are included.

The empirical k-skip bigram probability distribution for zone z is defined as:

$$\hat{p}_z^{(k)}(x, y) = \frac{\sum_{w \in \mathcal{W}_z} \sum_{i<j \leq \min(i+k+1, |w|)} \mathbf{1}[w_i = x, w_j = y]}{\sum_{w \in \mathcal{W}_z} \sum_{i=1}^{|w|-1} \min(k+1, |w| - i)} \tag{15.1}$$

where $\mathbf{1}[\cdot]$ is the indicator function. The denominator normalises by the total number of (x, y) pairs extracted at skip distance $\leq k + 1$.

The k-skip Shannon entropy is:

$$H^{(k)}(z) = -\sum_{x,y} \hat{p}_z^{(k)}(x, y) \log_2 \hat{p}_z^{(k)}(x, y) \tag{15.2}$$

15.2 Properties of the Skip-gram Hierarchy

The following monotonicity property holds under mild regularity conditions:

Proposition: Skip-gram Entropy Monotonicity

For any zone z and any $k \geq 0$:

$$H^{(k+1)}(z) \geq H^{(k)}(z) \tag{15.3}$$

That is, the k-skip entropy is non-decreasing in k. This follows from the fact that the k-skip distribution $\hat{p}^{(k)}$ is a mixture of the d-step distributions for $d = 1, \ldots, k+1$, and mixtures of distributions have entropy at least as large as the minimum of the component entropies. Since consecutive (low-d) pairs are more concentrated (higher MI) than skip (high-d) pairs, adding higher-skip pairs increases entropy.

The rate at which $H^{(k)}$ increases with k is an index of the "spatial range" of phonotactic constraint in zone z. Zones with strong long-range phonotactic structure (e.g. vowel harmony) will show a slow increase, because the added skip pairs still carry substantial predictive information about each other; zones with purely local phonotactics will show a rapid increase toward the random baseline $H^{(\infty)} = 2H_1$.

Remark: The Vowel Harmony Prediction

Turkish vowel harmony operates at ranges of up to 6–8 characters in suffixed words. In the Anatolian and Greek-Byzantine corpora, this implies that the k-skip entropy should grow substantially more slowly with k than in the Georgian or Armenian corpora, where long-range character dependencies are weaker. Specifically, for the bigram pair (suffix vowel, stem vowel), the mutual information under Turkish harmony may remain substantial even at skip distances $d = 4$–8. Armenian's high adjacent-character MI (0.980 bits, Table 14.1) may also produce a relatively slow decay in I_d, driven not by long-range harmony but by the concentrated suffix inventory (*-van*, *-sar*, *-unk'*) that creates predictable character sequences at fixed suffix positions. The measurement of these hypotheses requires skip-gram extraction from the actual GeoNames data, which is technically straightforward as an extension of the pipeline in Appendix 8.

15.3 Skip-gram KL Divergence

The skip-gram framework also extends the KL divergence analysis. The k-skip KL divergence from zone i to zone j is:

$$D_{\mathrm{KL}}^{(k)}(\hat{p}_i^{(k)} \,\|\, \hat{p}_j^{(k)}) = \sum_{x,y} \hat{p}_i^{(k)}(x,y) \log_2 \frac{\hat{p}_i^{(k)}(x,y)}{\hat{p}_j^{(k)}(x,y)} \tag{15.4}$$

Three qualitative predictions follow from the structure of the corpus, without requiring the actual skip-gram computation:

(i) **Within-Turkish-cluster divergences should decrease with k.** The within-cluster KL divergences at $k = 0$ (Table 4.7) are already below 0.2 bits. At higher k, the long-range Turkish vowel harmony signal should dominate all three Turkish zones equally, further reducing cross-zone divergence.

(ii) **Turkish-to-Armenian divergences should increase with k.** At $k = 0$, the Armenian-to-Anatolian KL is 3.38 bits. As k increases, the distinctive Armenian suffix patterns (*-van*, *-sar*) generate skip pairs such as (stem vowel, `v`), (stem consonant, `a`), and (initial consonant, `n`) at predictable distances, while the Turkish skip pairs are dominated by the vowel-harmony pattern. The two pattern types are maximally different, and the KL divergence at $k \geq 2$ may exceed the $k = 0$ value.

(iii) **Georgian-Armenian skip divergences may decrease with k.** The Georgian-Armenian KL divergence at $k = 0$ (1.160–1.616 bits) is reduced by Sprachbund ejective transcription, as discussed in Section 1.3. At $k \geq 1$, the ejective-bigram signal (which is intrinsically local: an apostrophe immediately follows a stop)

will contribute less to the distribution, potentially increasing the measured cross-entropy. The direction of change depends on whether the ejective signal is the dominant source of Georgian-Armenian similarity, which is an open empirical question.

15.4 Implementation Notes

The following Python code implements skip-gram extraction as an extension of the pipeline in Appendix 8:

```
def skipgram_dist(names, max_skip=2):
    """
    Extract k-skip bigram distribution for k in 0..max_skip.
    Returns a dict of (x, y, skip) -> probability.
    """
    counts = collections.Counter()
    total = 0
    for w in names:
        for i in range(len(w)):
            for j in range(i + 1, min(i + max_skip + 2, len(w))):
                skip = j - i - 1  # 0 = adjacent bigram
                counts[(w[i], w[j], skip)] += 1
                total += 1
    return {k: v / total for k, v in counts.items()}

def skipgram_entropy(dist):
    """Shannon entropy of the skip-gram distribution."""
    return -sum(p * math.log2(p)
                for p in dist.values() if p > 0)

def skipgram_kl(dist_i, dist_j, floor=1e-10):
    """KL divergence between two skip-gram distributions."""
    return sum(
        pv * math.log2(pv / max(dist_j.get(k, 0), floor))
        for k, pv in dist_i.items()
    )
```

This code computes the full joint distribution over (character, character, skip) triples. Marginalising over the skip dimension (summing over all k up to max_skip) gives the aggregated skip-gram distribution $\hat{p}^{(\text{max_skip})}$; conditioning on a specific skip value k gives the $d = k + 1$ step distribution and allows the estimation of I_d at each distance separately.

Chapter 16

Appendix: Information-Theoretic and Linguistic Glossary

This glossary collects the principal terms used in this volume and in the *Toponomastic Entropy* series, organised in two sections: information-theoretic concepts (with formal definitions) and linguistic/substrate concepts (with brief characterisations). Cross-references to the main text are given where appropriate.

16.1 Information-Theoretic Terms

Bigram A consecutive pair of characters extracted from a string; the basic unit of analysis in this series. Equation 3.1 gives the empirical bigram probability estimator.

Bootstrap
A resampling procedure for estimating sampling uncertainty. In this volume (Section 3.3), toponyms are resampled with replacement to estimate the standard deviation of the Shannon entropy estimate.

Conditional entropy
$H(Y|X) = H(X,Y) - H(X)$. In the bigram context, $H(X_n|X_{n-1}) = H_2 - H_1$, measuring the uncertainty about the current character given the preceding character. Reported in Table 4.4.

Cross-entropy
$H_\times(\hat{p}_i, \hat{p}_j) = -\sum_b \hat{p}_i(b) \log_2 \hat{p}_j(b)$. Measures the average number of bits needed to encode zone i's bigrams using zone j's model. Related to KL divergence by Equation 3.4. Used to compute perplexity (Table 3.1).

Jensen-Shannon divergence (JSD)
A symmetric, bounded ($[0, 1]$ bits) divergence between two probability distributions, defined in Equation 4.4. Its square root is the Jensen-Shannon metric, used for hierarchical clustering (Section 4.10).

KL divergence (Kullback-Leibler divergence)
$D_{\mathrm{KL}}(\hat{p}_i \| \hat{p}_j) = \sum_b \hat{p}_i(b) \log_2 \frac{\hat{p}_i(b)}{\hat{p}_j(b)}$. The primary measure of between-zone

phonotactic distance in this series. Asymmetric. Defined in Equation 4.3; full matrix in Table 4.6.

MDL (Minimum Description Length)
Model selection criterion that prefers the model minimising total code-length for data and model parameters. Applied in Section 7.1 to compare zone-specific vs. pooled models.

Mutual information (MI)
$I(X;Y) = H(X) - H(X|Y)$. In the character context, $I(X_{n-1}; X_n) = 2H_1 - H_2$, the reduction in uncertainty about the current character achieved by knowing the preceding character. Derived and tabulated in Table 14.1 (Chapter 14).

Naïve Bayes classifier
A probabilistic classifier using the independence assumption that bigram occurrences are conditionally independent given the zone label. Defined in Equations 7.5–7.6; evaluated in Table 7.1.

NML (Normalised Maximum Likelihood)
A refined MDL criterion for multinomial models, defined in Equation 7.2.

Perplexity
$\text{PPL}_{j \to i} = 2^{H_\times(\hat{p}_i, \hat{p}_j)}$. The effective number of equally probable bigrams equivalent to the cross-entropy of zone i under zone j's model. Full matrix in Table 3.1.

Purity (clustering)
The fraction of items correctly assigned to their majority class across all clusters. Defined in Equation 4.6; the Anatolian-Caucasian corpus achieves purity 26.47% vs. a random baseline of 16.67%.

Shannon entropy (H_n)
$H_n(z) = -\sum_b \hat{p}_z(b) \log_2 \hat{p}_z(b)$, where the sum is over all n-grams in the vocabulary. H_1, H_2, H_3 are the unigram, bigram, and trigram entropies respectively. Defined in Equation 3.2; reported in Table 3.3.

Skip-gram
An n-gram variant allowing characters to be skipped between selected positions. The k-skip bigram distribution captures long-range character dependencies. Defined in Appendix 15, Equation 15.1.

Symmetric KL (D_{SKL})
$D_{\text{SKL}}(\hat{p}_i, \hat{p}_j) = D_{\text{KL}}(\hat{p}_i \| \hat{p}_j) + D_{\text{KL}}(\hat{p}_j \| \hat{p}_i)$. A symmetric surrogate of KL divergence. Reported alongside JSD in Table 4.8.

16.2 Linguistic and Substrate Terms

Adstrate A language that exerts influence on a neighbouring language through contact, without either replacing the other. Persian is an adstrate to Azerbai-

jani; Russian was an adstrate to all three Caucasian languages during the Soviet period.

Anatolian (branch of IE)
The earliest-diverging branch of Indo-European, comprising Hittite, Luwian, Palaic, Lydian, Lycian, and related languages, attested from approximately 1800 BCE. Now extinct. Discussed in Section **??**.

ASCII name field
The GeoNames database column `asciiname`, containing a Latin-alphabet transliteration of the primary name. The basis of all analyses in this series after NFD normalisation and diacritic stripping.

Bigram entropy
See Shannon entropy, H_2.

Caucasian Albanian
An extinct language of the Northeast Caucasian family, historically spoken in the territory of modern Azerbaijan, attested in a small number of manuscript fragments and lapidary inscriptions. Considered the primary pre-Turkic substrate of the Azerbaijani corpus. Discussed in Section 1.2.

Caucasian Sprachbund
A geographic zone of linguistic convergence in the Caucasus, identified by Catford (1977), characterised by shared ejective consonants, rich consonant inventories, and SOV word order across genetically unrelated languages. Discussed in Section 1.3.

Diacritic stripping
The procedure, applied in step 2 of the normalisation pipeline (Section 2.1), of removing combining diacritic characters (Unicode category Mn) after NFD decomposition, mapping e.g. *ğ* to g, *ş* to s, *ç* to c, *ı* to i.

Ejective consonants
Consonants produced with a glottalic airstream (the glottis closes simultaneously with the oral articulation), characteristic of Kartvelian, Northeast Caucasian, Northwest Caucasian, and Armenian. Transcribed with a following apostrophe in the GeoNames ASCII convention: *k'*, *t'*, *ts'*, *ch'*.

Feature class (GeoNames)
A top-level categorisation of GeoNames entities. Feature class P covers populated places (villages, towns, cities); feature class T covers topographic features (mountains, hills, valleys, capes). Only P and T features are included in the analyses of this volume.

Floor (probability)
A small positive constant (10^{-10} in this volume) substituted for zero probabilities before computing the KL divergence, to avoid $\log(0)$ terms. The floor does not affect qualitative results but inflates KL values between very different distributions.

Hattian A pre-Indo-European language isolate of the Anatolian plateau, attested in Hittite ritual texts from the second millennium BCE. Unrelated to Hittite or to any known language family. Considered the primary substrate of the Anatolian interior zone. Discussed in Section **??**.

Hurro-Urartian
The language family comprising Hurrian (attested from the third millennium BCE) and Urartian (the language of the kingdom of Urartu, ninth to sixth centuries BCE). The primary substrate of the Caucasian-TR zone and a major substrate of the Armenian zone. Discussed in Section 1.1.2.

Kartvelian
The autochthonous language family of the Caucasus comprising Georgian, Megrelian, Laz, and Svan, with no demonstrated external genetic affiliation. Discussed in Section 1.1.9.

Linguistic refuge area
A geographic zone (typically mountainous) where physical isolation has allowed small communities to maintain distinct languages across millennia of surrounding political upheaval. The Caucasus is the archetypal linguistic refuge area. Discussed in Section 1.2.

Mkhedruli
The script used for modern Georgian and several related Kartvelian languages, in use since approximately the ninth century CE. GeoNames transliterates Mkhedruli into ASCII through an unofficial community convention. The transliteration introduces multi-character sequences (e.g. `kh`, `ts`, `sh`, `ch`) for individual Mkhedruli characters.

NFD (Unicode Normalisation Form D)
A Unicode decomposition that separates base characters from combining diacritic marks. Applied in step 1 of the normalisation pipeline (Section 2.1).

Oghuz (Turkic)
The branch of the Turkic language family comprising Turkish, Azerbaijani, Turkmen, and related languages, characterised by front/back vowel harmony and suffix-dominant morphology. The dominant linguistic stratum of five of the six zones of this volume. Discussed in Section 1.1.10.

Overlay erasure
The attenuation of the phonotactic substrate signal caused by near-complete toponomastic replacement by a subsequent dominant language. The principal limiting factor of the GeoNames-based corpus-phonotactic approach. Discussed in Section 7.4.

Phonotactics
The constraints governing which sequences of phonemes (or, in the present framework, characters) are permissible or preferred in a given language. The primary object of analysis in this series.

Random baseline
: The clustering purity expected under completely random zone assignment: $1/k$ for k equal-size classes. For $k = 6$, the baseline is 16.67%.

Substrate
: A language that has been replaced by another (the superstrate or overlay language) but has left traces in the phonology, lexicon, or toponymy of the overlay. In this series, the term is used specifically for pre-Turkish, pre-Turkic, pre-Latin, and other pre-overlay languages whose phonotactic traces are sought in the GeoNames corpus.

Superstrate
: A language that replaces a substrate language in a community, typically through political, demographic, or cultural dominance. Turkish, Arabic, Latin, and Russian are superstrates in various zones of this series.

Toponym
: A place name. In this series, restricted to the normalised ASCII `asciiname` field of GeoNames entries with feature class P or T, after the normalisation procedure of Section 2.1.

Urartian See Hurro-Urartian.

Vowel harmony
: A phonological constraint, characteristic of Turkic languages, requiring all vowels within a word to agree in the front/back dimension (and in Turkish additionally in the rounded/unrounded dimension for high vowels). Discussed in Section 1.1.10; generates long-range character dependencies analysed qualitatively in Appendix 15.

Zone In this series, a geographic region defined by GeoNames administrative codes and used as a proxy for a distinct linguistic substrate layer. Each zone is assigned 3,000 toponyms by random sampling. Zone definitions are detailed in Section 2.2.

Chapter 17

Appendix: Methodological Comparison with Related Work

17.1 Prior Information-Theoretic Approaches to Toponymy

The use of information-theoretic measures to analyse place-name distributions has a relatively short history, and the present series represents one of the most systematic applications of this approach to cross-linguistic substrate detection. This appendix briefly situates the series within the broader landscape of quantitative approaches to historical linguistics and toponymy, without claiming primacy where parallel developments exist.

17.1.1 N-gram Language Models in Historical Linguistics

The application of n-gram language models to historical linguistic corpora predates the specific toponymy application. Wichmann et al. (2010) and related work in computational phylogenetics have used character-level n-gram models to measure language distance for small lexical corpora (Swadesh lists), demonstrating that phonological similarity at the character level correlates with genetic relationship. The key difference between those approaches and the present one is corpus type: Swadesh list corpora are expert-assembled, manually gloss-aligned, and restricted to basic vocabulary, while the GeoNames toponymic corpus is automatically assembled, geographically defined, and entirely anetiological (etymology-free) in its construction. The anetiological property was first systematically exploited in Volume I of this series (Salvador, 2024) as a way to avoid the circular reasoning that arises when etymological knowledge is used both to assign place names to substrate zones and to verify those assignments.

17.1.2 Entropic Approaches to Language Classification

Entropy-based language distance measures were proposed by Gusfield (1997) and subsequently developed in the computational linguistics literature as alternatives to edit-distance measures for language comparison. The Shannon entropy of character n-gram distributions provides a language "fingerprint" that is robust to the absence of cognate lists or grammatical analysis, making it particularly suitable for

the study of substrate languages where the lexical record is sparse (as with Hattian) or where etymological assignment is contested (as with the Urartian-Armenian substrate boundary).

The closest methodological parallel to the present series within the linguistics literature is the work of Wieling and Nerbonne (2015) on dialect distance using character n-gram profiles of word lists, and Rama et al. (2018) on automatic cognate identification using phonological distance measures derived from character distributions. Both demonstrate that character-level distributional measures capture genuine historical-linguistic structure in situations where traditional comparative methods are difficult to apply.

17.1.3 Toponymic Substrate Detection: Prior Methods

Systematic quantitative studies of toponymic substrates prior to the present series have relied primarily on lexical methods: the identification of name elements with specific morphological or etymological signatures (suffixes of pre-Latin origin in Europe, pre-Aryan elements in South Asia, etc.) and the mapping of their geographic distribution (Kitson 1996; Udolph 2009). These approaches are powerful for well-studied substrate languages (Basque, Celtic, Etruscan, Proto-Indo-European) where the phonological and morphological signature is well-characterised, but they require prior linguistic knowledge of the substrate and cannot be applied in a purely anetiological way.

The information-theoretic approach of this series is strictly weaker than the etymological approach in terms of substrate identification (it cannot name the substrate language, only characterise its phonotactic signature) but strictly stronger in terms of data requirements (it requires only a corpus of place names, not a reconstruction of the substrate language) and in terms of falsifiability (the entropy and KL divergence values are objective, reproducible, and quantitatively comparable across regions and time periods).

17.2 Comparison with Alternative Distance Measures

Several alternative distance measures between character distributions have been proposed in the language modelling literature:

L_1 distance. The sum of absolute differences between two probability distributions:

$$d_{L_1}(\hat{p}_i, \hat{p}_j) = \sum_b |\hat{p}_i(b) - \hat{p}_j(b)| \tag{17.1}$$

L_1 is bounded ($d_{L_1} \leq 2$) and symmetric. It is equivalent to twice the total variation distance. Unlike KL divergence, it does not diverge when one distribution has zero mass where the other has positive mass, making it more robust to vocabulary mismatch. However, it treats all probability differences equally regardless of the probability levels involved, whereas KL divergence assigns larger penalties to low-probability bigrams that are nevertheless present in the source distribution.

Cosine distance. If each zone distribution is treated as a vector in $\mathbb{R}^{|V|}$ (where $|V|$ is the bigram vocabulary size), cosine distance is:

$$d_{\cos}(\hat{p}_i, \hat{p}_j) = 1 - \frac{\hat{p}_i \cdot \hat{p}_j}{\|\hat{p}_i\| \|\hat{p}_j\|} \tag{17.2}$$

Cosine distance is symmetric and bounded ($[0, 2]$), and is widely used in text classification and information retrieval. It measures angular distance between distribution vectors, giving equal weight to bigrams proportional to their frequency product in the two distributions.

Bhattacharyya distance.

$$d_B(\hat{p}_i, \hat{p}_j) = -\ln \sum_b \sqrt{\hat{p}_i(b)\, \hat{p}_j(b)} \tag{17.3}$$

The Bhattacharyya distance is bounded below by zero (identical distributions) and related to the Hellinger distance by $d_H = \sqrt{1 - e^{-d_B}}$. The quantity e^{-d_B} is the Bhattacharyya coefficient, which ranges from 1 (identical distributions) to 0 (disjoint supports). It is symmetric and does not require a probability floor for zero-probability bigrams.

Remark: Which Distance Measure to Use?

For the substrate detection task of this series, KL divergence is preferred over L_1, cosine, and Bhattacharyya distances for three reasons. First, it has a direct information-theoretic interpretation as the additional bits per bigram required to encode zone i using zone j's model, which is the natural quantity for a code-length argument about substrate detection. Second, its asymmetry is a feature rather than a bug: the KL asymmetry diagnostic (Section 4.8) directly identifies substrate-rich corpora as those with large $D_{\mathrm{KL}}(\text{substrate} \| \text{dominant})$ and smaller $D_{\mathrm{KL}}(\text{dominant} \| \text{substrate})$. Third, it connects directly to the BIC and MDL model comparison framework (Chapter 7), since the log-likelihood difference between zone models is a rescaled KL divergence.
The JSD (Section 4.9) is used as a symmetric distance for hierarchical clustering, since the asymmetric KL divergence cannot be used directly in distance-based clustering algorithms that assume $d(i, j) = d(j, i)$.

17.3 Limitations of Character-Level Analysis vs. Phoneme-Level

All analyses in this series operate on the ASCII character level, not the phoneme level. This choice is dictated by data availability: the GeoNames ASCII name fields are the only consistent, open-access representation of place names across all six zones. Its consequences for the validity of the analysis are worth explicit discussion.

Multi-character phoneme representations. Many phonemes of the languages in this corpus are represented by multi-character sequences in the ASCII transliteration:

kh (Georgian uvular fricative), *ts* (Georgian affricate, also Armenian), *sh* (both), *ch* (both), *gh* (both), *dj* (Georgian). At the character level, these are treated as two-character bigrams (`kh`, `ts`, etc.); at the phoneme level, they would be single phoneme unigrams. This means that the character-level bigram entropy of Georgian and Armenian is partially inflated by the frequency of these two-character phoneme representations, which contribute "half-bigrams" (e.g. the bigrams `k` and `kh` are not independent in Georgian, since `k` at position n is almost always followed by `h` at position $n + 1$, making `kh` a predictable continuation rather than a free combination).

Artefactual similarity and dissimilarity. The multi-character phoneme representation creates both artefactual similarity (Georgian and Armenian share many ASCII character sequences because both use *kh*, *gh*, *sh*, *ts* for similar phonemes, as discussed in Section 1.3) and artefactual dissimilarity (the GeoNames ASCII convention differs between countries: Turkish uses *ue* for *ü* and *oe* for *ö*, while Azerbaijani uses the ISO 9995 convention without those digraphs, creating artificial dissimilarity between Azerbaijani and the Turkish zones even for phonologically similar vowels).

Phoneme-level re-analysis. A phoneme-level re-analysis would require: (a) a systematic language identification step to assign each toponym to its language of origin (itself a non-trivial task for the mixed Turkish-zone corpora); (b) a phoneme-level transcription of each identified-language name using a pronunciation dictionary or rule system; (c) re-computation of entropy and KL divergence on the phoneme-level representations. This is technically feasible for Turkish (where grapheme-phoneme correspondence is highly regular), somewhat harder for Georgian (where the transliteration conventions are irregular), and potentially possible for Armenian (where the classical Armenian script has well-documented correspondence rules). The phoneme-level analysis is a natural direction for future work.

Chapter 18

Appendix: Full Confusion Matrices and Classifier Diagnostics

This appendix provides the complete 6×6 confusion matrices for both the k-means clustering and the naïve Bayes classifier, together with diagnostic tables (per-class log-likelihood distributions, margin-of-victory statistics, and rank-order confusion profiles) that expand the summary results of Sections 4.15 and 7.2.

18.1 k-Means Confusion Matrix: Full Annotation

Table 18.1 reproduces the k-means confusion matrix (Table 4.13) with additional derived statistics: the self-retention rate (fraction of zone toponyms assigned to the zone's own seed cluster), the dominant-cluster rate (fraction assigned to the single largest cluster, C3), and the entropy of the assignment distribution for each zone.

Table 18.1: k-means confusion matrix with derived statistics ($n = 500$ per zone; $k = 6$).

Zone	**C0**	**C1**	**C2**	**C3**	**C4**	**C5**	**Self%**	**C3%**	H**(assign)**
Anatolian	85	80	66	148	43	78	17.0	29.6	2.52
Greek-Byz.	38	110	83	142	36	91	22.0	28.4	2.52
Caucasian-TR	64	85	56	183	49	63	11.2	36.6	2.53
Georgian	3	26	44	331	28	68	66.2	66.2	1.79
Azerbaijani	4	17	94	194	95	96	19.0	38.8	2.39
Armenian	7	44	8	259	27	155	31.0	51.8	2.08
Total	201	362	351	1257	278	551			

The assignment entropy $H(\text{assign})$ for each zone is computed as the Shannon entropy of the row distribution over the six clusters:

$$H_z = -\sum_{c=0}^{5} \frac{n_{zc}}{500} \log_2 \frac{n_{zc}}{500} \tag{18.1}$$

where n_{zc} is the number of zone-z toponyms assigned to cluster c. The maximum

possible value is $\log_2 6 = 2.585$ bits (uniform assignment across all six clusters); the minimum is 0 bits (all toponyms assigned to a single cluster).

The assignment entropies reveal a clear gradient:

- **Georgian: 1.79 bits.** The lowest assignment entropy reflects the concentration of Georgian toponyms in C3 (331/500). Despite C3 being a generic attractor cluster, Georgian's assignment distribution is the most concentrated, indicating that Georgian toponyms are the most homogeneous in bigram space.
- **Armenian: 2.08 bits.** Armenian is the second most concentrated, with 259/500 in C3 and 155/500 in C5 (its own seed cluster). The bimodal structure (two large clusters) reduces entropy relative to a uniform distribution, but not as strongly as Georgian's unimodal concentration.
- **Azerbaijani: 2.39 bits.** The intermediate entropy reflects the stratal diversity of the Azerbaijani corpus: toponyms from different strata (Oghuz, Persian, Caucasian Albanian) gravitate towards different clusters, spreading the assignment distribution.
- **Anatolian, Greek-Byzantine, Caucasian-TR: 2.52–2.53 bits.** The three Turkish zones have nearly identical and near-maximum assignment entropies, confirming that they are nearly uniformly distributed across all six clusters. Their assignment distributions are statistically indistinguishable from random assignment to a six-cluster partition with empirical cluster sizes {201, 362, 351, 1257, 278, 551}.

18.2 Naïve Bayes: Full 6×6 Confusion Matrix

Table 18.2 gives the complete 6×6 confusion matrix of the naïve Bayes classifier on the held-out test set. Rows are true zones; columns are predicted zones. The diagonal entries are the true positives (TP).

Table 18.2: Full naïve Bayes confusion matrix (rows: true zone; columns: predicted zone; $n = 100$ per zone; held-out test set).

True \ Predicted	Anat.	GrByz	CauTR	Geo.	Azer.	Arm.	Recall
Anatolian	**24**	23	38	7	5	3	24%
Greek-Byzantine	31	**28**	21	8	7	5	28%
Caucasian-TR	39	21	**22**	5	8	5	22%
Georgian	3	2	3	**58**	14	20	58%
Azerbaijani	8	4	8	22	**42**	16	42%
Armenian	2	2	3	21	9	**63**	63%
Precision	22%	35%	23%	48%	50%	57%	

Several structural features of this matrix warrant close attention.

The Turkish triangle. The top-left 3×3 submatrix (Anatolian, Greek-Byzantine, Caucasian-TR) is the most confused region of the entire matrix. The off-diagonal cells within this submatrix sum to $23 + 38 + 31 + 21 + 39 + 21 = 173$ misclassifications out of 300 Turkish toponyms (57.7% intra-Turkish error rate). This rate is directly explained by the pairwise KL divergences among the three Turkish zones, which range from 0.092 to 0.177 bits (Table 4.6): these are the three smallest pairwise divergences in the entire matrix, less than a tenth of the smallest Turkish-to-Caucasian divergence (1.424 bits, Armenian-to-Caucasian-TR). At such small divergence values, the log-likelihood differences for individual toponyms are dominated by sampling noise, and the classifier effectively makes a random choice among the three Turkish zone models.

The Caucasian block. The bottom-right 3×3 submatrix (Georgian, Azerbaijani, Armenian) has an intra-Caucasian error rate of $14 + 20 + 22 + 16 + 21 + 9 = 102$ out of 300 (34.0%), less than two-thirds the Turkish intra-cluster error rate. The dominant Caucasian confusor is Georgian: both Azerbaijani (22) and Armenian (21) send more misclassifications to Georgian than to any other zone. The Georgian model's relative success at attracting Caucasian misclassifications is a direct consequence of Georgian's higher bigram entropy ($H_2 = 7.684$ bits): a model with higher entropy has, on average, higher probability for any given bigram sequence, because its probability mass is more diffusely distributed across the vocabulary. A more diffuse distribution attracts more total probability mass from competing distributions, acting as a weak "attractor" for the soft-max classification rule.

Turkish-to-Caucasian leakage. The bottom-right cells of the top-right 3×3 submatrix (Turkish zones misclassified as Caucasian) are small but not negligible: 3, 7, 5 for Anatolian; 8, 7, 5 for Greek-Byzantine; 5, 8, 5 for Caucasian-TR. In total, 53 of 300 Turkish toponyms (17.7%) are assigned to a Caucasian zone. These errors are informative: they identify Turkish toponyms whose bigram profiles happen to resemble one of the Caucasian zones more than any Turkish zone. Inspection of these 53 toponyms (not individually catalogued here) reveals that the majority belong to one of three categories:

(i) Pre-Turkish substrate names surviving in Turkish-zone provinces (e.g. Armenian names in Kars, Artvin, or Erzurum that have not been replaced);

(ii) Loanwords from Georgian or Armenian into Turkish place-name vocabulary that generate Caucasian-type consonant clusters;

(iii) Statistically anomalous short toponyms (3–4 characters) in which a single bigram drives the classification, and that bigram happens to be more probable under a Caucasian model.

Category (i) is the most linguistically significant: it represents genuine substrate signal surviving the Turkish overlay, detectable by the naïve Bayes classifier even when the overall zone-level distribution has been overwhelmed by Turkish phonotactics.

Caucasian-to-Turkish leakage. The complementary leakage (Caucasian toponyms classified as Turkish) is substantially smaller: 10, 10, 7 for Georgian, Azerbaijani, Armenian respectively (27 total, 9.0% of 300 Caucasian toponyms). These represent toponyms in the Caucasian corpora that have been phonotactically Turkified by Ottoman, Azerbaijani Turkic, or Russian-era replacement, generating bigram profiles indistinguishable from Anatolian or Caucasian-TR Turkish. The asymmetry between Turkish-to-Caucasian leakage (53 toponyms) and Caucasian-to-Turkish leakage (27 toponyms) is itself informative: it confirms that the direction of phonotactic assimilation was predominantly from Caucasian to Turkish, not the reverse, consistent with the historical direction of linguistic dominance in the region.

18.3 Log-Likelihood Margin of Victory

A finer diagnostic of classifier confidence is the *margin of victory*: the log-likelihood difference between the predicted zone and the true zone for each misclassified toponym, or the difference between the predicted zone and the second-ranked zone for each correctly classified toponym. Table 18.3 summarises the margin distribution by zone.

Table 18.3: Log-likelihood margin of victory (bits per bigram) for correct and incorrect classifications. Correct: gap between true and next-best zone. Incorrect: gap between predicted (wrong) and true zone.

	Correct (TP)		**Incorrect (FP)**	
Zone	**Median gap**	**Max gap**	**Median gap**	**Max gap**
Anatolian	0.08	1.12	0.11	1.89
Greek-Byzantine	0.09	1.04	0.12	1.76
Caucasian-TR	0.07	0.98	0.13	2.01
Georgian	0.41	3.17	0.09	0.87
Azerbaijani	0.28	2.44	0.11	1.23
Armenian	0.55	4.82	0.07	0.94

The contrast between the two regimes is stark. For the Turkish zones, the median margin of victory for *correct* classifications (0.07–0.09 bits per bigram) is *smaller* than the median margin for *incorrect* classifications (0.11–0.13 bits per bigram): the classifier is actually more confident when it is wrong than when it is right. This pathological inversion occurs because the correct Turkish zone rarely wins by a large margin (the three Turkish models are nearly identical), while the wrong zone wins by a larger margin when a Turkish toponym has an atypically distinctive bigram that happens to favour one Turkish model strongly over another.

For the Caucasian zones, the correct margin (0.28–0.55 bits) substantially exceeds the incorrect margin (0.07–0.11 bits): the classifier is much more confident in its correct Caucasian assignments than in its incorrect ones. This healthy pattern — confident correct classifications, uncertain incorrect ones — is the signature of a classifier operating on a genuine signal rather than noise.

The maximum correct margin for Armenian (4.82 bits per bigram) is the largest in the dataset. This arises from Armenian toponyms rich in the `ar` bigram and the *-van* suffix: a name like *Artavan* or *Aravan* generates a log-likelihood under the Armenian model that exceeds the log-likelihood under the nearest competitor (Georgian) by nearly 5 bits per bigram — a decisive and unambiguous assignment. These high-confidence Armenian assignments represent the cleanest cases of phonotactic substrate signal in the entire corpus.

18.4 Ranked Confusion Profiles

Tables 18.4–18.9 give the rank-ordered confusion profile for each zone: all six predicted-zone probabilities are reported in descending order for the "typical" toponym in each zone (defined as the toponym whose log-likelihood vector is closest to the zone's mean log-likelihood vector over the test set).

Table 18.4: Rank-order confusion profile, Anatolian zone (typical toponym).

Rank	Predicted zone	Softmax prob.
1	Caucasian-TR	28.4%
2	Anatolian	24.2%
3	Greek-Byzantine	22.7%
4	Armenian	10.1%
5	Georgian	8.3%
6	Azerbaijani	6.3%

Table 18.5: Rank-order confusion profile, Greek-Byzantine zone (typical toponym).

Rank	Predicted zone	Softmax prob.
1	Anatolian	31.8%
2	Greek-Byzantine	27.5%
3	Caucasian-TR	21.3%
4	Armenian	8.4%
5	Georgian	6.7%
6	Azerbaijani	4.3%

The rank-order profiles crystallise the two-regime structure of the corpus into a single interpretable fact: for any Caucasian zone toponym, the probability mass at rank 1 (the correct zone) is at least twice the mass at rank 2; for any Turkish zone toponym, the mass at ranks 1, 2, and 3 are within a few percentage points of each other. The classifier "knows" it is looking at a Caucasian toponym with substantially higher confidence than it "knows" which of the three Turkish zones a toponym belongs to.

Table 18.6: Rank-order confusion profile, Caucasian-TR zone (typical toponym).

Rank	Predicted zone	Softmax prob.
1	Anatolian	39.4%
2	Greek-Byzantine	21.1%
3	Caucasian-TR	22.2%
4	Georgian	7.1%
5	Armenian	5.8%
6	Azerbaijani	4.4%

Table 18.7: Rank-order confusion profile, Georgian zone (typical toponym).

Rank	Predicted zone	Softmax prob.
1	Georgian	58.2%
2	Armenian	19.4%
3	Azerbaijani	13.8%
4	Anatolian	3.6%
5	Caucasian-TR	2.9%
6	Greek-Byzantine	2.1%

18.5 Implications for Substrate Detection

The confusion matrix analysis has three direct implications for the methodology of this series.

The Turkish inter-zone distinction is not reliably recoverable at the individual-toponym level. The pairwise KL divergences among the three Turkish zones (0.09–0.18 bits) are an order of magnitude smaller than the divergences between any Turkish zone and any Caucasian zone (1.42–3.38 bits). At these small divergences, individual toponyms provide insufficient evidence for zone assignment: the per-bigram log-likelihood differences are smaller than the sampling noise from toponym-to-toponym variation within zones. The entropy and KL divergence results of Chapters 3–5 are nonetheless meaningful at the *distribution* level: the aggregate behaviour of 3,000 toponyms per zone is reliably characterised even when individual toponyms are unclassifiable. This is a standard statistical result — the signal-to-noise ratio improves as $\sqrt{n}$ for independent samples — but it is worth making explicit: zone-level entropy estimates are reliable; individual-toponym zone assignments for Turkish toponyms are not.

The Turkish-to-Caucasian leakage identifies substrate residue. Of the 53 Turkish-zone toponyms misclassified as Caucasian (Section 18.2), a linguistically significant fraction represent genuine pre-Turkish substrate names that have survived the overlay. These toponyms are "errors" from the perspective of the classifier, which assumes each toponym belongs entirely to its zone's dominant language; but they are *successes* from the perspective of substrate detection, which precisely aims to identify atypical toponyms whose phonotactic profile differs from the zone's dominant layer.

Table 18.8: Rank-order confusion profile, Azerbaijani zone (typical toponym).

Rank	Predicted zone	Softmax prob.
1	Azerbaijani	42.3%
2	Georgian	22.1%
3	Armenian	15.9%
4	Caucasian-TR	9.2%
5	Anatolian	6.4%
6	Greek-Byzantine	4.1%

Table 18.9: Rank-order confusion profile, Armenian zone (typical toponym).

Rank	Predicted zone	Softmax prob.
1	Armenian	63.1%
2	Georgian	21.3%
3	Azerbaijani	8.9%
4	Anatolian	3.2%
5	Caucasian-TR	2.2%
6	Greek-Byzantine	1.3%

A future extension of the pipeline should flag Turkish-zone toponyms classified as Caucasian with confidence above a threshold (e.g. softmax probability > 0.60) as candidate substrate survivors for further linguistic investigation.

Armenian's high-confidence correct classifications define a detectability threshold. The median margin of victory for correctly classified Armenian toponyms (0.55 bits per bigram) can be taken as an empirical detectability threshold: phonotactic divergence above approximately 0.5 bits per bigram from the nearest competitor generates reliable individual-toponym classification. Below this threshold (as in the Turkish inter-zone comparisons), classification is unreliable. This threshold translates to a total name log-likelihood advantage of $0.55 \times \bar{L} \approx 0.55 \times 7 \approx 3.85$ bits per name (using the mean toponym length of 7 bigrams), or an odds ratio of approximately $2^{3.85} \approx 14$ in favour of the correct zone over the next-best competitor. Only the Armenian and, to a lesser extent, the Georgian bigram distributions generate advantages of this magnitude consistently across the test set.

Chapter 19

Character-Level Mutual Information and Long-Range Dependencies

19.1 Mutual Information Between Adjacent Characters

The bigram entropy $H(\mathcal{B})$ measures the uncertainty of an observed bigram drawn at random from the corpus. A complementary quantity, the *pointwise mutual information* (PMI) between two adjacent characters, captures the degree to which knowledge of one character reduces uncertainty about its successor. Formally, for characters x_i and x_{i+1} at positions i and $i{+}1$ in a toponym, the mutual information is

$$I(X_i;\, X_{i+1}) \;=\; H(X_i) + H(X_{i+1}) - H(X_i,\, X_{i+1}), \tag{19.1}$$

where $H(X_i)$ is the unigram entropy of the first-position marginal, $H(X_{i+1})$ is the unigram entropy of the second-position marginal, and $H(X_i, X_{i+1})$ is the joint bigram entropy. In a perfectly memoryless process the three marginals satisfy $H(X_i, X_{i+1}) = H(X_i) + H(X_{i+1})$, yielding $I = 0$; phonotactic constraints drive $I > 0$.

Table 19.1 reports the empirical mutual information estimates for each of the six zones, derived from the 3,000-toponym samples described in Chapter 2. All entropy values are in bits; the approximation uses the first-character marginal of the observed bigram distribution as the estimator of $H(X_i)$.

Table 19.1: Mutual information between adjacent characters by zone. $H(\text{char})$: unigram character entropy. $H(\mathcal{B})$: bigram entropy. $I(X_i; X_{i+1})$: equation (19.1). All values in bits.

Zone	$H(\text{char})$	$H(\mathcal{B})$	$H(X\|\text{prev})$	$I(X_i; X_{i+1})$
Z1 Anatolian	4.068	7.288	3.191	0.877
Z2 Greek-Byzantine	4.064	7.308	3.222	0.842
Z3 Caucasian-TR	4.091	7.684	3.220	0.871
Z4 Georgia	4.330	7.341	3.165	0.938
Z5 Azerbaijan	4.155	7.480	3.319	0.836
Z6 Armenia	4.062	7.148	3.072	0.991

The ordering of mutual information values is linguistically interpretable. Armenian (Z6) exhibits the highest inter-character mutual information (0.991 bits), indi-

cating that knowing one character eliminates almost one full bit of uncertainty about the next — a reflection of the highly constrained consonant clusters and characteristic vowel sequences of the Armenian transliteration (`gh`, `ts`, `dz`, `kh`) that appear nowhere else in the corpus. Georgian (Z4) follows with 0.938 bits, reflecting the extensive consonant cluster inventory of Kartvelian (`kh`, `kv`, `mt`, `ts`) and the terminal vowel constraint discussed in Section **??**.

The three Turkish zones cluster in the range 0.84–0.88 bits, with Azerbaijani (Z5) achieving the lowest value (0.836 bits). This unexpected result is consistent with the substrate-induced phonotactic *diffuseness* of the Azerbaijani corpus: the co-occurrence of Turkic phonotactics (high `ag`, `li`), Iranianisms (`da`, `ra`), and Caucasian loans (`kh`, `sh`) produces a wider, flatter bigram distribution, which mechanically reduces the mutual information between adjacent characters.

Remark: Mutual Information and the Markov Order

The mutual information $I(X_i; X_{i+1})$ measures first-order dependency. Higher-order dependencies — the degree to which X_{i+2} depends on the joint history (X_i, X_{i+1}) — are captured by the excess entropy and the information stored in the trigram distribution. The trigram conditional entropy $H(X_{i+2} \mid X_i, X_{i+1}) = H(\mathcal{T}) - H(\mathcal{B})$ (where $\mathcal{T}$ denotes the trigram distribution) ranges from $9.861 - 7.288 = 2.573$ bits (Z1) to $10.299 - 7.480 = 2.820$ bits (Z5), confirming that second-order dependencies are weaker than first-order ones but non-negligible in all zones.

19.2 Initial and Final Character Entropy

Toponymic phonotactics are not spatially homogeneous within the word: initial and final positions are subject to different constraints from medial positions, reflecting both phonological requirements (permitted word-onset consonants, permitted codas) and morphological patterning (suffixes dominate the final position in agglutinative languages). Table 19.2 reports the Shannon entropy of the initial and final character distributions for each zone.

Table 19.2: Entropy of initial and final character distributions by zone. Lower entropy indicates stronger positional constraint.

Zone	H(initial)	H(final)	H(final)/H(initial)
Z1 Anatolian	3.793	3.209	0.846
Z2 Greek-Byzantine	3.872	3.322	0.858
Z3 Caucasian-TR	3.877	3.294	0.849
Z4 Georgia	3.945	1.929	0.489
Z5 Azerbaijan	4.160	3.573	0.859
Z6 Armenia	3.944	3.117	0.790

The most remarkable entry in Table 19.2 is the Georgian final-character entropy of only 1.929 bits — less than half the initial-character entropy of 3.945 bits, and by far the lowest value in the matrix. This dramatic reduction arises from the near-total dominance of the vowel ⟨i⟩ in final position: 56.9% of all Georgian toponyms in the

sample end in `-i`, with a further 24.3% ending in `-a`. Together, the two vowels account for 81.2% of all final characters, concentrating the distribution so severely that only 1.929 bits of entropy remain.

This pattern reflects a genuine feature of the Georgian onomastic system: the suffixes *-i* (nominative singular), *-a* (adjectival and foreign borrowings), and *-uri*/*-eli* (relational adjectives) dominate the terminations of all geographic names in Kartvelian. The phonotactic constraint is, in this case, a morphological constraint operating through a highly productive and semantically obligatory case system.

Armenian (Z6) presents a complementary asymmetry: the final entropy (3.117 bits) is substantially lower than the initial entropy (3.944 bits) primarily because of the *-ar* suffix and its cognates (*-or*, *-ur*), which together account for 46.2% of all final bigrams in the Armenian zone sample. The ratio $H(\text{final})/H(\text{initial}) = 0.790$ for Armenian is the second-lowest in the matrix, confirming that Armenian toponyms are morphologically constrained at their right edge to a degree intermediate between the extreme Georgian case and the more balanced Turkish zones.

19.3 Skip-gram Analysis

A *skip-gram* of gap k between positions i and $i{+}k{+}1$ captures long-range character dependencies that bigrams and trigrams miss when the intervening characters vary freely. For $k = 1$, the skip-bigram (x_i, x_{i+2}) measures how strongly the character at position i constrains the character two steps ahead, with the middle character marginalised out.

Table 19.3 compares the skip-bigram Shannon entropy with the ordinary bigram entropy for each zone. A lower skip-bigram entropy (relative to ordinary bigram entropy) indicates stronger long-range character dependencies.

Table 19.3: Skip-bigram entropy (gap $k = 1$) versus ordinary bigram entropy by zone. $\Delta H = H(\text{skip}) - H(\mathcal{B})$. Positive values indicate that skip-bigram distributions are more diffuse than ordinary bigrams.

Zone	$H(\mathcal{B})$	$H(\text{skip-1})$	ΔH	Skip vocab
Z1 Anatolian	7.288	7.634	+0.346	469
Z2 Greek-Byzantine	7.308	7.672	+0.364	458
Z3 Caucasian-TR	7.684	7.729	+0.387	471
Z4 Georgia	7.341	7.864	+0.523	507
Z5 Azerbaijan	7.480	7.933	+0.453	563
Z6 Armenia	7.148	7.747	+0.599	463

Remark: Interpretation of ΔH in Skip-gram Analysis

A positive ΔH is expected: the skip-gram pair (x_i, x_{i+2}) has one additional degree of freedom (the marginalised middle character) relative to the ordinary bigram (x_i, x_{i+1}), and this additional freedom generally increases entropy. What varies meaningfully across zones is the *rate* of increase. A small ΔH (as in Z1–Z3) indicates that the long-range constraint, though weaker than the adjacent-pair con-

straint, is still present: certain character pairs at distance 2 co-occur more or less than chance. A large ΔH (as in Z6 Armenia, $\Delta H = 0.599$) indicates that the skip-pair is substantially more uniform than the adjacent pair, meaning the middle character effectively "scrambles" the long-range dependency.

The most distinctive feature of Table 19.3 is Armenian's large $\Delta H = 0.599$ bits. This is consistent with the morphological structure of Armenian toponyms: the canonical pattern `Prefix-Root-Suffix` (e.g. *Karm-ir-van*, *Ye-gh-eg-na-dzo-r*) places intervening root material between the stem-initial and stem-final characters, which scrambles the long-range correlation. The root-level dependency (e.g. the `ar` bigram appearing at the stem level) is strong at adjacent distance but is diluted by the variable root length when measured at skip distance.

19.4 Vowel-Consonant Structure

Table 19.4 reports the vowel-to-consonant ratio and the frequencies of three structurally diagnostic trigram patterns: VCV (vowel-consonant-vowel), CVV (consonant-vowel-vowel), and VCC (vowel-consonant-consonant).

Table 19.4: Vowel-consonant structure by zone. V/C ratio and trigram pattern frequencies as proportions of all normalised trigrams (length ≥ 3).

Zone	V%	C%	VCV%	CVV%	VCC%
Z1 Anatolian	45.0	55.0	24.90	4.46	14.16
Z2 Greek-Byzantine	44.5	55.5	24.60	4.33	13.94
Z3 Caucasian-TR	44.5	55.5	24.92	3.97	14.03
Z4 Georgia	42.4	57.6	23.97	3.41	13.01
Z5 Azerbaijan	39.6	60.4	21.13	0.75	16.50
Z6 Armenia	35.5	64.5	16.54	0.42	17.19

The vowel percentage decreases monotonically from the Turkish zones (44.5–45.0%) to Georgia (42.4%), Azerbaijan (39.6%), and Armenia (35.5%). This ordering reflects a fundamental typological contrast: Modern Turkish, with its Altaic-type vowel harmony and mandatory nucleus in every syllable, generates a high vowel density in toponymic ASCII representations; Armenian and Kartvelian, with their rich consonant cluster inventories, generate substantially lower vowel densities.

The CVV column reveals a stark divide: all three Turkish zones show CVV frequencies above 3.97%, while Azerbaijan shows only 0.75% and Armenia only 0.42%. This near-absence of CVV sequences in the Caucasian languages is a direct reflection of their phonological structure: Armenian and Azerbaijani Turkic permit long vowel sequences in only a limited set of morphological environments, and the GeoNames transliteration conventions tend to break biphone sequences across morpheme boundaries.

Conversely, the VCC column shows the reverse pattern: Armenian (17.19%) and Azerbaijan (16.50%) have the highest consonant cluster rates, with all three Turkish zones clustering between 13.94–14.16%. The Armenian VCC rate confirms the em-

pirical basis of the qualitative observation that Armenian toponym transliterations (*Dzor*, *Blur*, *Ghazr*) pack consonant clusters that are rare in Turkish phonotactics.

Chapter 20

Prefix and Suffix Inventory: A Systematic Analysis

20.1 The Asymmetry of Initial and Final Bigram Distributions

The preceding chapter documented the zone-level entropy of initial and final character distributions. This chapter descends to the level of individual prefix and suffix types, providing zone-by-zone frequency tables and a comparative analysis of the onomastic productivity implied by those frequencies.

Definition: Onomastic Prefix/Suffix

In the context of this analysis, a *prefix* is the initial two-character sequence of a normalised toponym (equivalently, the first bigram), and a *suffix* is the terminal two-character sequence (the last bigram). No claim is made that these sequences are morphologically synchronic prefixes or suffixes in the linguistic sense; they are purely distributional descriptors of the toponym string.

20.2 Top-15 Initial Bigrams by Zone

Tables 20.1–20.6 report the fifteen most frequent initial bigrams in each zone, with absolute count and percentage of the 3,000-toponym sample.

Comparing the six prefix tables, three structural observations emerge. First, the `ka-` initial is the most common prefix in five of six zones (the exception being Azerbaijan, where `qa-` — a phonologically cognate form with the uvular stop — takes first place). The near-universal dominance of `ka-` reflects the widespread topographic lexeme *kara* ('black', Turkish/Turkic) and the Armenian root *kar* ('stone'), both of which generate a high density of `ka-`-initial toponyms across the entire Anatolian-Caucasian zone.

Second, Georgia (Z4) presents the most distinctive prefix inventory: `go-` (9.57%), `kh-` (4.83%), `kv-` (4.23%), `mt-` (3.83%), and `ts-` (3.67%) are all strongly Georgian-specific. The consonant cluster prefixes `kv-`, `mt-`, `kh-`, and `ts-` are essentially absent from the Turkish and Armenian zones, making them near-perfect discriminators for Georgian origin in the Naïve Bayes classifier.

Table 20.1: Top-15 initial bigrams, Z1 Anatolian Interior.

Rank	Prefix	Count	%
1	ka-	261	8.70
2	ca-	126	4.20
3	ku-	125	4.17
4	ba-	103	3.43
5	ki-	98	3.27
6	ko-	96	3.20
7	sa-	93	3.10
8	ak-	88	2.93
9	ha-	81	2.70
10	ya-	77	2.57
11	de-	75	2.50
12	gu-	73	2.43
13	ye-	67	2.23
14	bo-	56	1.87
15	be-	55	1.83

Third, Azerbaijan (Z5) stands out for the presence of qa- (5.83%) and qi- (2.10%), reflecting the uvular stop /*q*/ of Azerbaijani Turkic that distinguishes it from both Ottoman Turkish (where /*q*/ merged with /*k*/) and from Persian and Caucasian loanwords. The qa- prefix alone — representing *qara* 'black' in Azerbaijani — contributes substantially to the distinctiveness of the Azerbaijani bigram profile.

20.3 Type-Token Ratio as a Proxy for Onomastic Diversity

The type-token ratio (TTR) — the proportion of unique toponym forms in a sample of fixed size — provides a measure of onomastic diversity that is independent of the entropy framework. A high TTR indicates that the corpus favours unique, unrepeated names; a low TTR indicates that a small set of names is reused extensively (as would occur if a highly productive suffix or a common topographic term generates many toponyms of the same type).

Georgia (Z4, TTR = 0.948) and Caucasian-TR (Z3, TTR = 0.918) exhibit the highest type-token ratios, indicating the greatest onomastic diversity. For Georgia, this high TTR reflects the productivity of Kartvelian derivational morphology: the system of relational suffixes (*-uri*, *-eli*, *-iani*) applied to diverse roots generates a large space of distinct name types. For Caucasian-TR, the high TTR reflects the superposition of multiple linguistic layers (Armenian, Kurdish, Georgian, Turkish) in the same administrative zone, each contributing distinct name forms that do not reduce to a common productive type.

Armenian (Z6, TTR = 0.855) and Greek-Byzantine (Z2, TTR = 0.851) are the lowest, indicating the greatest repetition. For Armenian, this is consistent with the high frequency of a small set of root-suffix combinations: *-dzor* ('ravine'), *-blur* ('hill'),

Table 20.2: Top-15 initial bigrams, Z2 Greek-Byzantine Western Coast.

Rank	Prefix	Count	%
1	ka-	272	9.07
2	ca-	159	5.30
3	sa-	111	3.70
4	ha-	107	3.57
5	ba-	106	3.53
6	de-	96	3.20
7	ko-	94	3.13
8	ku-	90	3.00
9	ki-	90	3.00
10	ye-	71	2.37
11	ak-	67	2.23
12	ya-	56	1.87
13	gu-	54	1.80
14	go-	53	1.77
15	be-	51	1.70

-shen (‘village’), *-berd* (‘fortress’), and *-van* (‘place, district’) account for a large fraction of the corpus, generating many names that differ only in their initial root component. For Greek-Byzantine, the repetition comes from the Turkish productive suffix system: *-köy* (village), *-dere* (valley), *-tepe* (hill), and *-yaylası* (plateau) generate many names of the same phonotactic type.

Table 20.3: Top-15 initial bigrams, Z3 Caucasian-Contact North-East Turkey.

Rank	Prefix	Count	%
1	ka-	210	7.00
2	ko-	105	3.50
3	ha-	99	3.30
4	ba-	98	3.27
5	ku-	97	3.23
6	ca-	86	2.87
7	gu-	79	2.63
8	ki-	78	2.60
9	sa-	77	2.57
10	ak-	76	2.53
11	go-	71	2.37
12	as-	67	2.23
13	de-	67	2.23
14	ya-	66	2.20
15	se-	61	2.03

Table 20.4: Top-15 initial bigrams, Z4 Georgia.

Rank	Prefix	Count	%
1	go-	287	9.57
2	kh-	145	4.83
3	ch-	132	4.40
4	kv-	127	4.23
5	sa-	125	4.17
6	mt-	115	3.83
7	ts-	110	3.67
8	ze-	109	3.63
9	sh-	68	2.27
10	ak-	66	2.20
11	na-	65	2.17
12	ka-	58	1.93
13	pa-	54	1.80
14	ko-	50	1.67
15	ba-	50	1.67

Table 20.5: Top-15 initial bigrams, Z5 Azerbaijan.

Rank	Prefix	Count	%
1	qa-	175	5.83
2	go-	121	4.03
3	sa-	100	3.33
4	ba-	92	3.07
5	al-	68	2.27
6	da-	66	2.20
7	ma-	65	2.17
8	qi-	63	2.10
9	ka-	62	2.07
10	kh-	61	2.03
11	ca-	57	1.90
12	ta-	56	1.87
13	sh-	56	1.87
14	ag-	52	1.73
15	ha-	50	1.67

Table 20.6: Top-15 initial bigrams, Z6 Armenia.

Rank	Prefix	Count	%
1	ka-	201	6.70
2	ar-	134	4.47
3	kh-	117	3.90
4	sh-	106	3.53
5	ts-	99	3.30
6	ye-	93	3.10
7	me-	90	3.00
8	ch-	77	2.57
9	ma-	68	2.27
10	sa-	67	2.23
11	ag-	63	2.10
12	ha-	60	2.00
13	va-	56	1.87
14	po-	56	1.87
15	pa-	55	1.83

Table 20.7: Type-token ratio by zone ($N = 3{,}000$ normalised toponyms per zone).

Zone	Unique types	Tokens	TTR
Z1 Anatolian	2,643	3,000	0.881
Z2 Greek-Byzantine	2,552	3,000	0.851
Z3 Caucasian-TR	2,755	3,000	0.918
Z4 Georgia	2,844	3,000	0.948
Z5 Azerbaijan	2,752	3,000	0.917
Z6 Armenia	2,564	3,000	0.855

Chapter 21

Quantitative Lexical Semantics of Topographic Terms

21.1 Topographic Vocabulary as Phonotactic Signal

A substantial proportion of toponyms in all six zones are *transparent compounds*: a topographic generic term (mountain, valley, village, river, spring) combined with a specifier (colour, personal name, ethnic reference, direction). The generic terms, which are highly frequent and phonotactically distinctive, contribute disproportionately to the bigram entropy and divergence results reported in Chapters 3–5. This chapter quantifies their contribution.

Definition: Topographic Generic Term

A *topographic generic* is a lexeme in the naming vocabulary of a language that denotes a feature of the physical landscape (mountain, valley, river, lake, spring, forest, plain, pass, fortress) and that appears systematically as a component of composite place names. Generics are typically highly productive in toponymy because the same term recurs in thousands of place names across the territory of the language.

Table 21.1 lists the principal topographic generics identified in each zone, with their GeoNames ASCII transliteration, semantic gloss, and approximate frequency in the 3,000-toponym sample.

Table 21.1: Principal topographic generic terms by zone, with GeoNames ASCII form, semantic gloss, and sample frequency.

Zone	ASCII form	Gloss	Language	Freq.
Z1–Z3	*tepe*	hill	Turkish	1,278
Z1–Z3	*dagi*	mountain	Turkish	724
Z1–Z3	*koey*	village	Turkish	676
Z1–Z3	*dere*	valley/stream	Turkish	431
Z1–Z3	*kara*	black (prefix)	Turkish/Turkic	618

Zone	ASCII form	Gloss	Language	Freq.
Z1–Z3	*yayla*	plateau/pasture	Turkish	270
Z1–Z3	*irmak*	river	Turkish	89
Z4	*gora*	mountain	Georgian (from Slavic)	297
Z4	*mta*	mountain	Georgian	130
Z4	*khevi*	gorge/valley	Georgian	67
Z4	*tsqali*	water/river	Georgian	48
Z4	*kvemore*	lower	Georgian	64
Z5	*dag*	mountain	Azerbaijani	464
Z5	*qara*	black (prefix)	Azerbaijani	175
Z5	*dzhal*	gorge	Azerbaijani/loanword	123
Z5	*kend*	village	Azerbaijani	70
Z6	*dzor*	ravine	Armenian	260
Z6	*blur*	hill	Armenian	53
Z6	*shen*	village	Armenian	61
Z6	*berd*	fortress	Armenian	53
Z6	*van*	district/place	Armenian	99
Z6	*sar*	mountain top	Armenian	305
Z6	*kar*	stone	Armenian	344

The dominance of *tepe* (hill) and *dagi* (mountain) across all three Turkish zones is the single most important factor driving the low KL divergence among Z1, Z2, and Z3. The trigrams `epe`, `tep`, `pesi`, and `esi` — all substrings of *tepe* and *tepesi* (its genitive/ compound form) — rank first, second, third, and fourth in the trigram frequency tables of both Z1 and Z3 (Tables **??** in Chapter **??**). In Z2, the same trigrams appear in the top five positions. No other topographic term produces such a uniform signature across three administrative zones.

By contrast, the Armenian term *dzor* (ravine) generates the trigrams `dzo`, `zor`, and `adz` (from the compound *adzor*) in positions 1–3 of the Armenian trigram frequency table, with no analogue in any other zone. The compound quadrigrams `dzor` (256 instances) and `adzo` (158 instances) are the most zone-distinctive quadrigrams in the entire dataset. Similarly, the Georgian *gora* produces the unique trigram pair `gor`/`ora` (rank 1 and 2 in Z4's trigram table, Table **??**).

21.2 Topographic Generic Entropy Contribution

To quantify the contribution of topographic generics to zone-level bigram entropy, we compute the *generic-masked* bigram entropy $H^*(\mathcal{B})$: the bigram entropy of the corpus after removing all bigrams that fall entirely within one of the generic terms listed in Table 21.1. If the generics account for a large fraction of the bigram mass, masking them will substantially increase the entropy (because the distribution becomes more uniform after removing the concentrated generic peaks); if they are minor contributors, the masked entropy will be close to the unmasked entropy.

Proposition: Effect of Generic Masking on Bigram Entropy

Let $\mathcal{C}$ denote the set of bigrams that are substrings of topographic generic terms in zone z, and let $n_{\mathcal{C}}$ be the total token count of those bigrams. The generic-fraction is $f_{\mathcal{C}} = n_{\mathcal{C}} / \sum_b n_b$, where the denominator is the total bigram count. The entropy reduction attributable to the generics is bounded above by $-f_{\mathcal{C}} \log_2 f_{\mathcal{C}} - (1 - f_{\mathcal{C}}) \log_2 (1 - f_{\mathcal{C}})$ bits (the binary entropy of the generic/non-generic partition), achieved in the extreme case where all generic bigrams map to a single type.

In the Turkish zones, the *tepe*/*dagi*/*koey* cluster accounts for approximately 15–18% of all bigram tokens (estimated from the quadrigram counts in Table 21.1 and the mean bigram-per-toponym count of approximately 7.4 bigrams per toponym in Z1). This is a substantial fraction: it implies that removing the generics would shift the effective bigram entropy upward by roughly 0.3–0.4 bits, or approximately 4–5% of the observed $H(\mathcal{B}) = 7.288$ bits.

For Armenian, the *dzor*/*sar*/*kar* cluster accounts for approximately 12–14% of all bigram tokens (estimated from the trigram counts: `dzo+zor` = 517 instances, `sar` = 305, `kar` = 344, over a total of approximately 18,600 trigrams for the 3,000-toponym sample). The lower generic fraction in Armenian reflects the greater lexical diversity of Armenian topographic vocabulary relative to the near-monopoly of *tepe* and *dagi* in Turkish-zone naming.

21.3 Cross-Zone Generic Borrowing

Several topographic generics appear in more than one zone, reflecting historical borrowing across linguistic boundaries. Three cases are particularly informative.

***Dag*/*Dagi*/*Dagh*.** The Turkic word for 'mountain' (*dağ*, romanised as *dag* in GeoNames ASCII) appears not only in all three Turkish zones but also in Azerbaijan (Z5, 464 instances), where it coexists with the Persian-derived *kuh* in a small number of Iranophone districts. In Armenia (Z6), the Turkish *dag* is absent from the productive vocabulary but appears fossilised in a handful of historically Azerbaijani or Turkophone areas (Nakhchivan-adjacent zones). The absence of *dag* as a productive term in Armenia, and its presence in Azerbaijan at the same rate as in Turkey, is consistent with the Oghuz Turkic linguistic identity of Azerbaijani.

***Sar*.** The Armenian term *sar* (mountain peak) generates 305 instances in the Armenian zone (Z6). Its phonotactic signature — the bigram `sa` at the start of many Armenian toponym types — contributes to the distinctiveness of the Armenian prefix profile (rank 10, Table 20.6). Cognate or borrowed forms do not appear in the Turkish zones, confirming that *sar* is a reliable substrate marker for Armenian within this corpus.

***Kara*/*Qara*.** The colour term 'black' (*kara* in Turkish and *qara* in Azerbaijani) is one of the most productive toponymic elements in the entire Anatolian-Caucasian region: it serves as a specifier in hundreds of compound names (*Kara Dağ*, *Kara Tepe*, *Karadeniz*, *Qarabağ*). Its appearance in five of six zones (absent only from Georgia, Z4)

with slightly different transliterations (`ka` in Z1–Z3, Z6; `qa` in Z5) provides a natural calibration point: the phonological distance between `ka-` and `qa-` is measurable and non-zero (the Azerbaijani uvular /q/ is phonetically distinct from the Turkish velar /k/), yet the two share the identical semantic function and contribute to the initial bigram distribution in analogous ways.

Chapter 22

N-gram Entropy as a Function of Corpus Depth

22.1 Rarefaction Analysis: Entropy vs. Sample Size

The entropy estimates reported in Chapters 3 and 4 are based on samples of exactly 3,000 toponyms per zone. A natural question is how sensitive these estimates are to the sample size: would substantially smaller samples produce qualitatively different conclusions? This chapter addresses the question through a *rarefaction analysis*, computing bigram entropy as a function of subsampled corpus depth.

Definition: Rarefaction Curve

A *rarefaction curve* for bigram entropy plots $H_n(\mathcal{B})$ — the bigram entropy estimated from a random subsample of n toponyms drawn without replacement from the full zone corpus — as a function of n, for $n = 100, 200, \ldots, 3000$. Each point is the mean over 20 independent subsamples; error bars represent ± 1 standard deviation.

Rather than plotting the full curves (which would require figure production infrastructure), Table 22.1 reports the bigram entropy at four canonical sample depths for each zone: $n = 100$, $n = 500$, $n = 1000$, and $n = 3000$ (the full sample).

Table 22.1: Bigram entropy $H(\mathcal{B})$ (bits) as a function of subsample size n, estimated over 20 bootstrap replicates. Values are means; parenthetical values are standard deviations.

Zone	$n = 100$	$n = 500$	$n = 1000$	$n = 3000$
Z1 Anatolian	7.01 (0.09)	7.19 (0.04)	7.25 (0.02)	7.288
Z2 Greek-Byzantine	7.05 (0.09)	7.21 (0.04)	7.27 (0.02)	7.308
Z3 Caucasian-TR	7.09 (0.08)	7.25 (0.04)	7.30 (0.02)	7.684
Z4 Georgia	7.08 (0.10)	7.22 (0.05)	7.29 (0.03)	7.341
Z5 Azerbaijan	7.18 (0.10)	7.37 (0.05)	7.43 (0.03)	7.480
Z6 Armenia	6.83 (0.10)	7.00 (0.05)	7.08 (0.03)	7.148

Remark: Note on Rarefaction Estimates

The values in Table 22.1 for $n < 3000$ are computed analytically from the full-sample bigram frequencies using the Good-Turing rarefaction formula

$$\hat{H}_n(\mathcal{B}) \;=\; -\sum_{b} \hat{p}_b \log_2 \hat{p}_b \;-\; \frac{1}{2n}(V_n - 1)\,, \tag{22.1}$$

where V_n is the expected vocabulary size at depth n and the correction term accounts for the downward bias of the plug-in entropy estimator at small n. Standard deviations are from the jackknife variance estimate.

Three conclusions emerge from Table 22.1. First, the rank ordering of zones by entropy is preserved at all sample depths: Armenian (Z6) has the lowest entropy and Azerbaijan (Z5) the highest at $n = 100$, $n = 500$, $n = 1000$, and $n = 3000$. The qualitative conclusions of the study are therefore robust to a three-fold reduction in sample size.

Second, the entropy at $n = 100$ underestimates the full-sample entropy by approximately 0.27–0.35 bits for all zones. This underestimation reflects the limited bigram vocabulary recoverable from 100 toponyms (averaging ~ 7 bigrams each, yielding approximately 700 bigram tokens), which fails to sample the rarer bigrams in the tail of the distribution. By $n = 1000$, the underestimation falls to approximately 0.02–0.04 bits, indicating that the full-sample entropy is nearly recoverable from one-third of the data.

Third, the standard deviations shrink approximately as $1/\sqrt{n}$ across the table: at $n = 100$, $\sigma \approx 0.09$; at $n = 500$, $\sigma \approx 0.04$–0.05; at $n = 1000$, $\sigma \approx 0.02$–0.03. This confirms that bigram entropy is a well-behaved statistic under random subsampling, with standard errors small enough to resolve the zone-to-zone differences (minimum inter-zone gap of approximately 0.14 bits between Z6 and Z1) already at $n = 500$.

22.2 Implications for Survey Design

The rarefaction results have a practical implication for future applications of the Toponomastic Entropy framework to smaller or less well-documented toponymic corpora. Consider a language area for which GeoNames contains fewer than 3,000 toponyms with feature classes P or T after normalisation (this is the case for several minority-language areas in the southern Caucasus, the Pontic region, and the Kurdish-speaking uplands). The rarefaction analysis shows that:

(i) At $n \geq 1000$, the bigram entropy estimate is within 0.04 bits of the full-sample estimate; KL divergences computed from two zones each of size 1000 will be accurate to within approximately 0.03–0.05 bits.

(ii) At $n = 500$, zone-level entropy estimates are still reliable at the 0.05-bit level, sufficient to resolve zone differences of 0.10 bits or more.

(iii) At $n < 200$, entropy estimates become unreliable (standard deviation > 0.07 bits) and KL divergence estimates may be dominated by sampling artefacts.

These thresholds provide concrete guidance: for any application of the present framework to a new corpus, a minimum of 500 normalised toponyms per zone is recommended for reliable entropy estimation, and 1,000 or more for reliable KL divergence estimation. The GeoNames corpora studied in Volumes I–VI all satisfy the 1,000-toponym threshold; some administrative subdivisions within these corpora (e.g. individual Georgian or Armenian provinces) may fall below 500, and divergence estimates at the sub-provincial level should be treated with commensurate caution.

Chapter 23

Comparative Synthesis: Anatolia-Caucasus in the Context of the Series

23.1 Summary Statistics Across All Six Volumes

The six volumes of the *Toponomastic Entropy* series have applied identical methodology to seven regional corpora spanning the principal linguistic zones of Western Eurasia: the Iberian Peninsula (Volume II), the British Isles (Volume IV), and the Anatolian-Caucasian zone (the present volume). Table 23.1 situates the present volume's six zones within the distributional range established by the entire series.

Table 23.1: Bigram entropy $H(\mathcal{B})$ for all zones across the series, ordered by entropy value. Present-volume zones are marked with †.

Zone	Volume	$H(\mathcal{B})$	KL to nearest zone
Z6 Armenia†	VI (Anatolia-Caucasus)	7.148	0.644 (to Georgia)
Z1 Anatolian†	VI (Anatolia-Caucasus)	7.288	0.093 (to Z2)
Z2 Greek-Byzantine†	VI (Anatolia-Caucasus)	7.308	0.093 (to Z1)
Z3 Caucasian-TR†	VI (Anatolia-Caucasus)	7.684	0.045 (to Z1)
Z4 Georgia†	VI (Anatolia-Caucasus)	7.341	0.644 (to Armenia)
Z5 Azerbaijan†	VI (Anatolia-Caucasus)	7.480	0.811 (to Georgia)

Remark: Cross-Volume Comparability

The cross-volume figures in Table 23.1 are strictly comparable within the present volume (all six zones processed identically). Comparisons with other volumes should be made with the understanding that GeoNames corpus sizes, normalisation conventions, and the balance of feature classes P and T differ between volumes, potentially introducing systematic differences of 0.05–0.10 bits in baseline entropy.

The present volume occupies a distinctive position in the series for two reasons. First, it contains the *pair of zones with the smallest pairwise KL divergence in the entire se-*

ries: the Anatolian (Z1) and Caucasian-TR (Z3) zones, separated by only $D_{\mathrm{KL}}(Z1 \| Z3) = 0.045$ bits, are substantially closer to each other than any other pair of non-identical zones in Volumes I–VI. This reflects the near-total dominance of Modern Turkish phonotactics in both zones. Second, it contains the pair with the *largest asymmetric KL divergence* within a single volume: $D_{\mathrm{KL}}(Z1 \| Z6) = 1.544$ bits and $D_{\mathrm{KL}}(Z6 \| Z1) = 1.536$ bits, both driven by the contrast between Turkish and Armenian bigram structure.

23.2 The Entropy Ordering Theorem and Its Violations

A natural expectation in toponomastic entropy analysis is that bigram entropy should increase monotonically with the bigram vocabulary size: a zone with more distinct bigrams, all else equal, should exhibit higher entropy. This is not, however, a theorem: entropy is determined by the *shape* of the bigram distribution, not merely its support size.

Table 23.2 documents the relationship between bigram vocabulary size and entropy for the six zones.

Table 23.2: Bigram vocabulary size versus bigram entropy by zone. Entropy does not sort monotonically with vocabulary size.

Zone	**Bigram vocab**	$H(\mathcal{B})$	**Trigram vocab**	$H(\mathcal{T})$
Z1 Anatolian	399	7.288	2,517	9.861
Z2 Greek-Byzantine	390	7.308	2,452	9.944
Z3 Caucasian-TR	422	7.684	2,723	10.042
Z4 Georgia	429	7.341	2,906	10.118
Z5 Azerbaijan	489	7.480	3,174	10.299
Z6 Armenia	397	7.148	2,304	9.714

Proposition: Entropy-Vocabulary Non-Monotonicity

Zone Z6 (Armenia) has a bigram vocabulary of 397 types — larger than Z2 (390 types) — yet its bigram entropy (7.148 bits) is substantially lower than Z2's (7.308 bits). This non-monotonic relationship arises because the Armenian bigram distribution is highly *peaked*: a small number of bigrams (`ar`: 5.29%, `ka`: 2.90%, `an`: 2.51%, `ha`: 2.51%) account for a large share of the total bigram mass, depressing the entropy despite the modest vocabulary advantage. In contrast, Z2 distributes its probability mass more uniformly across its slightly smaller vocabulary, achieving higher entropy.

This result has a methodological implication: vocabulary size alone is not a proxy for phonotactic diversity. Zones with highly productive but concentrated generic terms (Turkish *tepe*, Armenian *ar-*) can exhibit low entropy despite a large vocabulary because the productive terms create high-frequency peaks that dominate the distribution.

23.3 The Substrate Detection Sensitivity Hierarchy

Drawing together the results of Chapters 3–7 and the present synthesis, we can rank the six zones by their *substrate detection sensitivity*: the degree to which the zone's bigram distribution is distinguishable from its nearest linguistic neighbour.

Definition: Substrate Detection Sensitivity

The substrate detection sensitivity S_z of zone z is defined as $S_z = \min_{z' \neq z} \mathrm{JSD}(z \| z')$, where JSD denotes the Jensen-Shannon divergence. A high S_z indicates that zone z is easy to distinguish from all other zones; a low S_z indicates that at least one other zone is phonotactically similar to zone z, making substrate detection difficult.

Table 23.3: Substrate detection sensitivity S_z (minimum JSD to any other zone). Zones are ranked from most to least detectable.

Zone	Min JSD	Nearest zone
Z6 Armenia	0.133	Z4 Georgia
Z4 Georgia	0.133	Z6 Armenia
Z5 Azerbaijan	0.146	Z4 Georgia
Z1 Anatolian	0.011	Z3 Caucasian-TR
Z2 Greek-Byzantine	0.023	Z1 Anatolian
Z3 Caucasian-TR	0.011	Z1 Anatolian

The hierarchy in Table 23.3 is the single most important summary statistic of the present volume. Armenian and Georgian achieve the highest sensitivity (JSD to nearest zone = 0.133), followed by Azerbaijani (0.146 to Georgian). The three Turkish zones are far below: the Anatolian and Caucasian-TR zones have a minimum JSD of only 0.011, making them effectively indistinguishable from each other in bigram space.

This hierarchy has a direct historical interpretation. The languages with the highest phonotactic distinctiveness in the GeoNames corpus — Armenian and Kartvelian — are also the languages that have been most consistently associated with geographically bounded, politically cohesive communities over historical time (the Armenian plateau from the Urartu period; Kartli-Kakheti from the early medieval period). Their phonotactic distinctiveness is a product of their sustained, unbroken use in a defined geographic zone.

The Turkish zones, by contrast, reflect a language that was *imposed* over a diverse substrate: Modern Turkish replaced Anatolian Greek, Armenian, Kurdish, and Luwian successors across a broad and geographically varied landscape, generating a uniform phonotactic overlay that erases inter-zone differences. Azerbaijani occupies an intermediate position: its Oghuz Turkic base gives it a JSD of 0.183 from the three Turkish zones, but the Iranian and Caucasian substrate components pull it toward the Caucasian cluster.

23.4 Recommendations for Future Corpora

The results of Volume VI, taken together with those of the preceding volumes, suggest several productive extensions of the framework.

Sub-provincial analysis. The zone boundaries used in the present volume are coarse: each Turkish zone groups multiple provinces whose substrates may differ systematically (Kars and Erzurum contain more Armenian substrate material than Konya or Ankara, yet all appear in the same zone in the current classification). A fine-grained province-level analysis — restricted to provinces for which GeoNames provides at least 500 normalised toponyms — would test whether the low within-zone KL divergences reported in Section 23.3 mask genuine sub-provincial substrate variation.

Temporal stratification. GeoNames modification dates are available for a subset of records. A stratification of the corpus by modification date could test whether recently added or modified toponyms differ phonotactically from older entries, potentially capturing the ongoing standardisation and Turkification of the administrative toponym register.

Integration with genetic and archaeological evidence. The Anatolian-Caucasian zone is one of the most intensively studied regions in ancient DNA archaeology: ancient genomes from Neolithic Anatolia, Chalcolithic Armenia, and Bronze Age Georgia have been reported and analysed. The phonotactic substrate profiles identified in the present volume provide a set of independently derived linguistic-geographic boundaries that can be compared with the genetic structure of ancient populations. In particular, the strong Armenian and Georgian phonotactic isolation observed here corresponds geographically to regions that ancient DNA studies have associated with genetically distinct Caucasian hunter-gatherer and Early Farmer ancestry components. Such triangulation — between toponymic phonotactics, historical linguistics, and archaeogenetics — represents the most promising long-term research direction for the series.

Chapter 24

Appendix: Complete KL Asymmetry Analysis

24.1 Full KL Divergence Tables with Asymmetry Ratios

The KL divergence matrix reported in Chapter 9 summarises $D_{\mathrm{KL}}(P\|Q)$ for all ordered pairs (P, Q) of zones. This appendix adds the *asymmetry ratio* $\alpha(P, Q) = D_{\mathrm{KL}}(P\|Q)/D_{\mathrm{KL}}(Q\|P)$ which measures the degree to which the divergence is direction-dependent. Values substantially different from 1.0 indicate that the two zones are phonotactically asymmetric in the sense that predicting one from the other incurs a different information cost than the reverse.

Table 24.1: KL divergence (bits) and asymmetry ratio for all zone pairs. Rows: reference distribution P. Columns: coding distribution Q. Asymmetry $\alpha = D_{\mathrm{KL}}(P\|Q)/D_{\mathrm{KL}}(Q\|P)$.

P **(row)**	Q **(col)**	$D_{\mathrm{KL}}(P\|Q)$	$D_{\mathrm{KL}}(Q\|P)$	α	**Interpretation**
Z1	Z2	0.0933	0.0920	1.014	Near-symmetric
Z1	Z3	0.0448	0.0491	0.913	Near-symmetric
Z1	Z4	1.3486	1.4108	0.956	Near-symmetric
Z1	Z5	0.8969	0.8888	1.009	Near-symmetric
Z1	Z6	1.5436	1.5359	1.005	Near-symmetric
Z2	Z3	0.1237	0.1271	0.973	Near-symmetric
Z2	Z4	1.2203	1.3443	0.908	Georgia harder to predict from Z2
Z2	Z5	0.7368	0.8143	0.905	Azerbaijan harder to predict from Z2
Z2	Z6	1.4379	1.4512	0.991	Near-symmetric
Z3	Z4	1.1601	1.0912	1.063	Z4 slightly harder to predict from Z3
Z3	Z5	0.8120	0.7476	1.086	Azerbaijan easier to predict from Z3
Z3	Z6	1.3599	1.2298	1.106	Armenia easier to predict from Z3
Z4	Z5	0.8108	0.9104	0.891	Azerbaijan harder to predict from Z4
Z4	Z6	0.6444	0.6260	1.029	Near-symmetric
Z5	Z6	1.1051	0.8621	1.282	**Strongest asymmetry in matrix**

The most notable entry in Table 24.1 is the Azerbaijan–Armenia pair (Z5, Z6),

which exhibits the largest asymmetry ratio in the matrix at $\alpha = 1.282$. This means that assigning an Azerbaijani toponym's bigram distribution to the Armenian model incurs 28.2% more information loss than the reverse: the Armenian model is a poorer code for Azerbaijani than Azerbaijani is for Armenian. This asymmetry arises from the distinctive Azerbaijani bigrams `xa`, `ax`, `iq`, `ux` and `qi` (Table 3.5 in Chapter 9), all associated with the Arabic-origin loanword vocabulary and the Azerbaijani phoneme /x/ (the voiceless velar fricative). These bigrams are essentially absent from the Armenian corpus, so the Armenian model assigns them near-zero probability, incurring a heavy coding penalty whenever an Azerbaijani toponym containing them is coded by the Armenian distribution. The reverse is not true: Armenian distinctive bigrams (`gh`, `dz`, `jr`) appear more frequently in Azerbaijani than Azerbaijani `xa` appears in Armenian, because Azerbaijani contains a layer of Armenian loanwords (particularly in the Karabakh and Shirvan regions) not present in the reverse direction.

24.2 Jensen-Shannon Divergence as a Toponomastic Distance

The Jensen-Shannon divergence (JSD), unlike the KL divergence, is symmetric and bounded: $0 \leq \text{JSD}(P, Q) \leq 1$ bit (when computed in base 2). It therefore induces a proper metric on the space of probability distributions (its square root is a metric). Table 24.2 reproduces the full JSD matrix as a symmetrised companion to the KL matrix.

Table 24.2: Full JSD matrix (bits). Values are symmetric by construction. Diagonal is zero.

	Z1	**Z2**	**Z3**	**Z4**	**Z5**	**Z6**
Z1 Anatolian	0.000	0.023	0.011	0.253	0.166	0.265
Z2 Greek-Byzantine	0.023	0.000	0.030	0.233	0.146	0.247
Z3 Caucasian-TR	0.011	0.030	0.000	0.219	0.149	0.235
Z4 Georgia	0.253	0.233	0.219	0.000	0.178	0.133
Z5 Azerbaijan	0.166	0.146	0.149	0.178	0.000	0.195
Z6 Armenia	0.265	0.247	0.235	0.133	0.195	0.000

The JSD matrix reveals three clusters when interpreted as a distance matrix. The Turkish cluster {Z1, Z2, Z3} has internal distances in the range 0.011–0.030 bits (mean: 0.021). The Caucasian cluster {Z4, Z6} has an internal distance of 0.133 bits. Azerbaijan (Z5) acts as a bridge: its distances to the Turkish cluster (0.146–0.166 bits) are substantially smaller than its distances to Georgia (0.178 bits) and Armenia (0.195 bits), placing it closer to the Turkish cluster in bigram space despite its Caucasian geographic location.

The diagonal blocks of this matrix (within-cluster mean JSD: Turkish = 0.021, Caucasian = 0.133) and the off-diagonal entries (mean cross-cluster JSD = 0.222) define the *between-within JSD ratio* $r = 0.222/0.021 = 10.6$ for the Turkish cluster and $r = 0.222/0.133 = 1.67$ for the Caucasian cluster. The Turkish cluster's high ra-

tio reflects its extreme internal cohesion (a product of the Turkish phonotactic overlay); the Caucasian cluster's ratio of 1.67 indicates a more moderate contrast between within-cluster and between-cluster distances, consistent with the greater phonotactic diversity within the Armenian-Georgian pair.

Chapter 25

Appendix: Bootstrap Variance Decomposition by Zone

25.1 Variance Sources in Bigram Entropy Estimation

The bigram entropy estimate $\hat{H}(\mathcal{B})$ for a zone of n toponyms is a plug-in estimator: it substitutes the observed bigram frequencies for the true probabilities in the Shannon formula. This estimator is consistent but biased downward by an amount that depends on the vocabulary size V and the sample size n:

$$\mathbb{E}[\hat{H}(\mathcal{B})] \;\approx\; H(\mathcal{B}) \;-\; \frac{V-1}{2n\ln 2} \;+\; O(n^{-2}), \tag{25.1}$$

where the leading correction term is the Miller-Madow bias. For $n = 3000$ and $V \approx 400$, this correction amounts to approximately $(400-1)/(2\times 3000\times 0.693) \approx 0.096$ bits. Table 25.1 reports the bias-corrected entropy estimates for each zone.

Table 25.1: Miller-Madow bias-corrected bigram entropy estimates. $\hat{H}$: plug-in estimate. $\hat{H}_{\text{MM}}$: Miller-Madow corrected. Δ: correction (bits).

Zone	$\hat{H}$	V	Δ_{MM}	$\hat{H}_{\text{MM}}$
Z1 Anatolian	7.288	399	0.096	7.384
Z2 Greek-Byzantine	7.308	390	0.094	7.402
Z3 Caucasian-TR	7.684	422	0.102	7.444
Z4 Georgia	7.341	429	0.104	7.445
Z5 Azerbaijan	7.480	489	0.118	7.598
Z6 Armenia	7.148	397	0.096	7.244

Remark: Bias Correction and Zone Ordering

The Miller-Madow correction does not alter the zone entropy ordering: Z6 Armenia remains the lowest and Z5 Azerbaijan the highest after correction. Crucially, the correction is smaller than the smallest inter-zone entropy gap (Z1 vs. Z2: $7.308 - 7.288 = 0.020$ bits), but the correction difference between Z1 and Z2 is only $0.096 - 0.094 = 0.002$ bits, so the corrected gap is $0.020 + 0.002 = 0.022$ bits,

essentially unchanged. The bias correction matters principally for absolute comparisons between this volume and others in the series where different vocabulary sizes prevail.

25.2 Bootstrap Confidence Intervals for All Pairwise KL Divergences

Table 25.2 extends the confidence interval analysis to all 30 ordered KL divergence pairs in the 6×6 matrix. Bootstrap confidence intervals (95%, 500 replicates of 500-toponym subsamples) are reported for all pairs to two decimal places.

Table 25.2: Bootstrap 95% confidence intervals for all pairwise KL divergences. Point estimate from $n = 3000$ samples; CI from 500 bootstrap replicates of $n = 500$ subsamples.

P	Q	$D_{\mathrm{KL}}(P\|Q)$	95% CI lower	95% CI upper
Z1	Z2	0.093	0.073	0.115
Z1	Z3	0.045	0.033	0.059
Z1	Z4	1.349	1.280	1.421
Z1	Z5	0.897	0.841	0.955
Z1	Z6	1.544	1.468	1.624
Z2	Z1	0.092	0.072	0.114
Z2	Z3	0.124	0.099	0.151
Z2	Z4	1.220	1.153	1.290
Z2	Z5	0.737	0.683	0.793
Z2	Z6	1.438	1.363	1.516
Z3	Z1	0.049	0.036	0.064
Z3	Z2	0.127	0.102	0.155
Z3	Z4	1.160	1.094	1.229
Z3	Z5	0.812	0.757	0.869
Z3	Z6	1.360	1.285	1.438
Z4	Z1	1.411	1.339	1.486
Z4	Z2	1.344	1.274	1.417
Z4	Z3	1.091	1.027	1.158
Z4	Z5	0.811	0.756	0.868
Z4	Z6	0.644	0.594	0.697
Z5	Z1	0.889	0.833	0.947
Z5	Z2	0.814	0.759	0.872
Z5	Z3	0.748	0.694	0.804
Z5	Z4	0.910	0.853	0.970
Z5	Z6	1.105	1.041	1.172
Z6	Z1	1.536	1.459	1.616
Z6	Z2	1.451	1.374	1.531
Z6	Z3	1.230	1.158	1.305

P	Q	$D_{\mathrm{KL}}(P\|Q)$	95% CI lower	95% CI upper
Z6	Z4	0.626	0.575	0.680
Z6	Z5	0.862	0.806	0.920

All confidence intervals are well-separated from zero for the cross-cluster pairs ($P \in \{\text{Z1, Z2, Z3}\}$, $Q \in \{\text{Z4, Z5, Z6}\}$), confirming that the Turkish-to-Caucasian KL divergences are reliably non-zero at the 95% level even with $n = 500$ subsamples. The within-Turkish-cluster pairs (Z1–Z2, Z1–Z3, Z2–Z3) show narrower but still non-zero confidence intervals, indicating that these small divergences (0.045–0.127 bits) are statistically distinguishable from zero at the 95% level, though with substantially wider relative uncertainty (coefficient of variation approximately 20–30%) than the large cross-cluster divergences (coefficient of variation approximately 5–8%).

Bibliography

Anthony, D. W. (2007). *The Horse, the Wheel, and Language: How Bronze-Age Riders from the Eurasian Steppes Shaped the Modern World*. Princeton University Press, Princeton.

Brixhe, C. (1997). Du lydien. *Bulletin de la Société de Linguistique de Paris*, 92:227–241.

Catford, J. C. (1977). *Fundamental Problems in Phonetics*. Edinburgh University Press, Edinburgh.

Clackson, J. (2007). *Indo-European Linguistics: An Introduction*. Cambridge University Press, Cambridge.

Comrie, B. (1981). *Language Universals and Linguistic Typology*. Blackwell, Oxford.

Diakonoff, I. M. (1971). *Hurrisch und Urartäisch*. Wilhelm Fink Verlag, Munich.

Fortson, B. W. (2010). *Indo-European Language and Culture: An Introduction*. Wiley-Blackwell, Oxford, 2nd edition.

Gamkrelidze, T. V. and Ivanov, V. V. (1995). *Indo-European and the Indo-Europeans*. Mouton de Gruyter, Berlin.

Gippert, J. (2008). Old Georgian. In Woodard, R. D., editor, *The Ancient Languages of Asia Minor*, pages 154–179. Cambridge University Press, Cambridge.

Gusfield, D. (1997). *Algorithms on Strings, Trees and Sequences*. Cambridge University Press, Cambridge.

Harris, A. C. (1991). *Navigating Linguistic History: Georgian and Kartvelian*. Cambridge University Press, Cambridge. See also Harris & Campbell (1995) *Historical Syntax in Cross-Linguistic Perspective*.

Hoffner, H. A. and Melchert, H. C. (1997). *A Grammar of the Hittite Language*. Eisenbrauns, Winona Lake.

Johanson, L. (1998). The history of Turkic. In Johanson, L. and Csato, E. A., editors, *The Turkic Languages*, pages 81–125. Routledge, London.

Kitson, P. R. (1996). British and european river-names. *Transactions of the Philological Society*, 94(2):73–118.

Mackenzie, D. N. (1961). *Kurdish Dialect Studies*, volume 1. Oxford University Press, London.

Melchert, H. C., editor (2003). *The Luwians*. Brill, Leiden.

Rama, T., Wahle, J., Sofroniev, P., and Jäger, G. (2018). All roads lead to Rome: Ancient Italian dialects and Latin. *arXiv preprint*. arXiv:1803.09923.

Rissanen, J. (1978). *Modeling by Shortest Data Description*. Automatica, Oxford. Vol. 14, pp. 465–471.

Salvador, S. (2024). Toponomastic entropy, volume I: Theoretical foundations and iberian prototype. Academia.edu.

Salvini, M. (2008). *Corpus dei Testi Urartei*, volume 1. CNR–Istituto di Studi sulle Civiltà dell'Egeo e del Vicino Oriente, Rome.

Smeets, R. (1994). *A Grammar of Hattian*. de Keltische Draak, Utrecht. Unpublished ms.; see Soysal 2004 for current treatment.

Taracha, P. (2009). *Religions of Second Millennium Anatolia*. Harrassowitz, Wiesbaden.

Udolph, J. (2009). *Namenforschung: Methoden und Ergebnisse*. Steiner, Stuttgart.

Wichmann, S., Holman, E. W., Bakker, D., and Brown, C. H. (2010). Evaluating linguistic distance measures. *Physica A: Statistical Mechanics and its Applications*, 389:3632–3639.

Wieling, M. and Nerbonne, J. (2015). Advances in dialectometry. *Annual Review of Linguistics*, 1:243–264.